



**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world

# ROCKWOOD CATALOG – ACCESSORIES

## Table of Contents

Page #

<b>General Information</b>	1-10
Section A – Behavioral Health Solutions, Push and Pull Bars	A1-A23
Behavioral Health Solutions	A1
Push and Pull Bar Mounting Details	A2
Push Bars, Pull Bars, Push and Pull Bar Sets	A3-A10
Series 47 Push and Pull Bar Mounting Details	A11
Series 47 Solid & Tubular Push Bars	A12-A13
Series 47 Solid Straight/Offset Push & Pull Bar Sets	A14-A19
Series T 47 Tubular Straight/Offset Push & Pull Bar Sets	A20-A22
Single Bar Sets with Santoprene™	A23
Section B – Push and Pull Plates, Door Pulls	B1-B39
Push Plate Order Information	B1
Push Plates	B2-B7
Flush & Pocket Pulls	B8-B12
Straight Door Pulls, Mounting Details	B13-B22
Pull Plates	B23-B26
Offset Door Pulls, Mounting Details	B27 -B32
Door Pulls	B33
Hands Free Pulls	B34-B35
Vandal Resistant Trim, Pull	B36-B39
Section C – Door Plates, Door Edges & Protectors	C1-C26
Door Plates	C1-C5
Angle Plates	C6
Door Edges (Mortise, Non-Mortise, Overlapping)	C7-C9
Door Edge Order Forms & Worksheets	C10-C14
Wrap Around Plates	C15
Protector Bars	C16-C20
Vertical Rod Covers	C21
Custom Strikes	C22-C23
Corner Guards	C24
Latch Protectors	C25-C26
Section D – Stops	D1-D24
Wall Stops	D1-D3
Dome Stops	D4-D5
Roller and Kick Down Stops	D6-D8
Heavy Duty Door Stops	D9-D10
Standard, Automatic, and Spring Base Door Stops	D11-D19
Hinge Pin Stop	D19
Overhead Holders & Stops	D20-D24
Section E – Bolts and Latches	E1-E20
Lever Extension Flush Bolts	E1-E4
Strikes & Gravity Coordinator	E4
Surface Bolts	E5-E6
Roller Latches	E7-E8
Gate Latch & Door Guards	E9
Privacy Door Latch & Silencers	E10
Door Coordinators	E11-E12
Mounting Brackets	E13
Automatic & Combination Flush Bolts	E14-16
Bottom Fire Bolts	E17
Automatic & Self Latching Flush Bolts	E18-E19
Pivots	E20
Section F – Auxiliary Hardware	F1-F18
Door Knockers & Viewers	F1-F2
Door Signs	F2-F6
Hand Rail Brackets	F7
Coat Hooks	F8
Knobs and Wire Pulls	F9
Flush, Edge, & Pocket Pulls	F10-F11
Magnetic & Ball Catches	F12-F13
Filler Plates & Hinge Shims	F14-F18

**ROCKWOOD®****ASSA ABLOY**Experience a safer  
and more open world800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

No.	Description	Page	No.	Description	Page
10-PB	Push Bar.....	A3	95B	Flush Pull.....	B11
11-PB	Push Bar.....	A3	95R	Flush Pull - Round.....	B11
12-PB	Push Bar.....	A3	96	Flush Pull.....	B11
14-PB	Push Bar.....	A4	98	Flush Pull - Flat Pocket.....	B12
15-PB	Push Bar.....	A4	99-RKW	Flush Pull - Radius Pocket.....	B12
18-PB	Push Bar.....	A4	102-RKW	Straight Door Pull.....	B14
18BFB	Bottom Fire Bolt - Metal Door.....	E16	102 x 70	Pull Plate.....	B23
19-PB	Push Bar.....	A4	105	Straight Door Pull.....	B14
19BFB	Bottom Fire Bolt - Wood Door.....	E16	105 x 70	Pull Plate.....	B23
20-PB	Pull Bar.....	A5	106-RKW	Straight Door Pull.....	B14
21-PB	Pull Bar.....	A5	106 x 70	Pull Plate.....	B23
22-PB	Pull Bar.....	A5	107	Straight Door Pull.....	B14
23-PB	Pull Bar.....	A5	107 x 70	Pull Plate.....	B23
25-PB	Push Bar.....	A6	108	Straight Door Pull.....	B14
26-PB	Push Bar.....	A6	109	Straight Door Pull.....	B14
27-PB	Push Pull Bar Set.....	A6	110-RKW	Straight Door Pull.....	B14
28-PB	Push Pull Bar Set.....	A6	110 x 70	Pull Plate.....	B23
29-PB	Push Pull Bar Set.....	A6	111	Straight Door Pull.....	B14
30-PB	Push Pull Bar Set.....	A6	111 x 70	Pull Plate.....	B23
31-PB	Pull Bar.....	A7	111A	Straight Door Pull.....	B14
32-PB	Pull Bar.....	A7	112	Straight Door Pull.....	B14
33-PB	Push Bar.....	A7	118	Straight Door Pull.....	B14
34-PB	Push Bar.....	A7	120	Door Pull.....	B18
35-PB	Push Pull Bar Set.....	A7	121	Door Pull.....	B18
36-PB	Push Pull Bar Set.....	A7	122-RKW	Door Pull.....	B18
40-PB	Screen Door Guard.....	A8	122 x 70	Pull Plate.....	B24
41-PB	Screen Door Guard.....	A8	123	Door Pull.....	B18
42-PB	Screen Door Guard.....	A8	123 x 70	Pull Plate.....	B24
43-PB	Push Bar.....	A9	125-RKW	Door Pull.....	B19
44-PB	Push Bar.....	A9	125 x 70	Pull Plate.....	B24
45-PB	Push Bar.....	A9	126-RKW	Door Pull.....	B19
47 Series	Series 47 Push Bar.....	A12	126 x 70	Pull Plate.....	B24
48-PB	Series 47 Push Bar.....	A12	130-RKW	Cast Door Pull.....	B19
49-PB	Push Bar.....	A13	131-RKW	Cast Door Pull.....	B19
50-PB	Pull Bar.....	A10	132-RKW	Cast Door Pull.....	B20
51-PB	Push Bar.....	A10	132 x 70	Pull Plate.....	B25
52-PB	Push Pull Bar Set.....	A10	134-RKW	Cast Door Pull.....	B20
53-PB	Door Pull.....	A10	137	Cast Door Pull.....	B21
70 Series	Push Plate - .050".....	B2	137 x 70	Pull Plate.....	B25
71 Series	Push Plate - .062".....	B3	137L	Cast Door Pull.....	B21
73 Series	Push Plate - .125".....	B4	138	Cast Door Pull.....	B21
73BL	Concealed Mount Push Plate.....	B16	139	Cast Door Pull.....	B21
73CL	Concealed Mount Push Plate.....	B16	147	Door Pull.....	B22
75 Series	Push Plate - .125".....	B5	147 x 76	Pull Plate.....	B26
76 Series	Decorative Push Plate - .050".....	B6	147 x 77	Pull Plate.....	B26
77 Series	Decorative Push Plate - .050".....	B6	147L	Door Pull.....	B22
80	Push Plate - .050".....	B6	148	Door Pull.....	B22
81	Push Plate - .050".....	B6	148 x 76	Pull Plate.....	B26
82	Push Plate - .050".....	B6	148 x 77	Pull Plate.....	B26
84	Push Plate - .050".....	B6	149	Door Pull.....	B22
85	Push Plate - .050".....	B7	185	Offset Door Pull.....	B32
86	Push Plate - .050".....	B7	190	90° Straight Door Pull.....	B33
87	Push Plate - .125".....	B7	193	Hand/Arm Pull.....	B34
90	Cylinder Pull.....	B8	208	Wooden Door Pull.....	B33
90B	Cylinder Pull.....	B8	215	Tapered Door Pull.....	B33
91-RKW	Combination Push Pull Plate.....	B8	215L	Tapered Door Pull.....	B33
92-RKW	Combination Push Pull Plate.....	B8	290	Corner Guard.....	C24
93-RKW	Combination Push Pull Plate.....	B8	291	Corner Guard.....	C24
94	Flush Pull.....	B9	295	Corner Guard.....	C24
94BTB	Flush Pull.....	B9	296	Corner Guard.....	C24
94C	Flush Pull.....	B9	300	Mortise Door Edge.....	C7
94DLL	Dead Lock Flush Pull.....	B9			
94DLS	Dead Lock Flush Pull.....	B9			
94L	Flush Pull.....	B10			
94P	Flush Pull.....	B10			
94P x 94L	Flush Pull Set.....	B10			
95A	Flush Pull.....	B11			

No.	Description	Page
301	Mortise Door Edge .....	C7
302	Mortise Door Edge .....	C7
302B	Mortise Door Edge .....	C7
304	Non-Mortise Door Edge .....	C8
305	Non-Mortise Door Edge .....	C8
306-RKW	Non-Mortise Door Edge .....	C8
306-AST	Non-Mortise Door Edge .....	C8
306B	Non-Mortise Door Edge .....	C8
306B-AST	Non-Mortise Door Edge .....	C8
307	Non-Mortise Door Edge .....	C8
308	Overlapping Door Edge .....	C9
309	Overlapping Door Edge .....	C9
310	Overlapping Door Edge .....	C9
310B	Overlapping Door Edge .....	C9
310BS	Overlapping Door Edge .....	C9
310S	Overlapping Door Edge .....	C9
320-RKW	Latch Protector .....	C25
320C	Latch Protector .....	C25
320CL	Latch Protector .....	C25
320CXL	Latch Protector .....	C25
321	Latch Protector .....	C25
322	Latch Protector .....	C26
325	Latch Protector .....	C26
330	Latch Protector .....	C26
350WP	Wrap Around Plate.....	C15
400	Solid Cast Wall Stop.....	D1
401	Solid Cast Wall Stop.....	D1
402	Solid Cast Wall Stop.....	D1
403	Solid Cast Wall Stop.....	D1
404	Solid Cast Wall Stop.....	D1
405	Solid Cast Wall Stop.....	D1
406	Wrought Wall Stop.....	D1
409	Wrought Wall Stop.....	D1
412	Solid Cast Wall Stop.....	D2
415	Solid Cast Wall Stop.....	D2
416	Solid Cast Wall Stop.....	D2
426	Wall Stop.....	D3
430-RKW	Solid Cast Wall Stop.....	D3
431-RKW	Wall Stop.....	D3
432W	Wall Stop.....	D3
440	Low Dome Stop.....	D4
441	Low Dome Stop.....	D4
441CU	Dome Stop Combination Unit.....	D4
441H	Cast Universal Dome Stop .....	D5
442	High Dome Stop.....	D5
443	High Dome Stop.....	D5
444	Cast Door Stop Riser.....	D5
445	Heavy Duty Dome Stop .....	D5
445H	Heavy Duty Dome Stop .....	D5
446	Door Stop.....	D6
449	Door Stop Riser.....	D6
455	Curved Roller Stop.....	D6
456-RKW	Straight Roller Stop.....	D6
456L	Straight Roller Stop.....	D7
458	Kick Down Door Stop.....	D7
459	Spring Loaded Plunger Stop.....	D7
460	Kick Down Door Stop.....	D7
461	Kick Down Door Stop.....	D8
461L	Kick Down Door Stop.....	D8
462	Heavy Duty Door Stop.....	D9
463-RKW	Heavy Duty Door Stop.....	D9
464-RKW	Heavy Duty Door Stop w/Holder.....	D9
465	Heavy Duty Door Stop.....	D9
466-RKW	Heavy Duty Door Stop.....	D10
467-RKW	Heavy Duty Door Stop.....	D10
468-RKW	Heavy Duty Door Stop .....	D10
470	Door Stop.....	D11

No.	Description	Page
471	Door Stop.....	D11
472	Door Stop w/Keeper .....	D11
473	Door Stop w/Keeper.....	D11
474	Door Stop.....	D11
475	Door Stop.....	D11
476	Door Stop w/Keeper .....	D12
477	Door Stop w/Keeper .....	D12
480	Door Stop.....	D12
480H	Door Stop.....	D12
481	Door Stop.....	D13
481H	Door Stop.....	D13
481MP	Door Stop.....	D13
482	Door Stop.....	D14
483	Door Stop.....	D14
485	Door Stop w/Keeper.....	D14
486	Angle Door Stop.....	D15
487	Heavy Duty Wall Stop.....	D15
488	Door Stop.....	D15
489	Door Stop.....	D15
490	Door Holder & Stop.....	D16
491-RKW	Automatic Door Holder & Stop.....	D16
491R	Automatic Door Holder & Stop.....	D16
491S	Automatic Door Holder & Stop.....	D16
494-RKW	Automatic Door Holder & Stop/Foot Pull ... B35, D17	D17
494R	Automatic Door Holder & Stop.....	D17
494S	Automatic Door Holder & Stop.....	D17
495	Concealed Magnetic Door Stop .....	D17
505-RKW	Door Stop.....	D18
508	Door Stop.....	D18
517	Aluminum Door Stop.....	D18
518	Door Stop.....	D18
519	Door Stop.....	D18
520	Replacement Bumper .....	D18
525	Spring Base Door Stop.....	D19
526	Spring Base Door Stop.....	D19
528	Hinge Pin Stop .....	D19
550	Lever Extension Flush Bolt .....	E1
554	Rabbit Piece .....	E1
554G	Rabbit Guide .....	E1
554S	Rabbit Guide .....	E1
555	Lever Extension Flush Bolt .....	E2
555 x 18BFB	Lever Extension Flush Bolt .....	E2
556WS	Lever Extension Flush Bolt .....	E3
557	Lever Extension Flush Bolt .....	E3
557 x 19BFB	Lever Extension Flush Bolt .....	E4
570	Dust Proof Strike.....	E4
576	Gravity Door Coordinator .....	E4
580 Series	Surface Bolts.....	E5
582 Series	Surface Bolts.....	E5
585 Series	Heavy Duty Surface Bolts.....	E5
590	Roller Latch w/Cast Strike.....	E7
590DA	Roller Latch w/Double Acting Strike .....	E7
591	Roller Latch w/ASA Strike .....	E7
592	Roller Latch w/#161 Strike.....	E8
593	Roller Latch w/Angle Strike.....	E8
594	Roller Latch w/161 Strike .....	E8
602	Secret Gate Latch .....	E9
603	Door Guard w/Shim .....	E9
604	Door Guard w/Shim .....	E9
605	Door Guard Protection Plate .....	E9
605SMS	Door Guard Protection Plate .....	E9
606-RKW	Door Guard Protection Plate .....	E10
608-RKW	Door Silencer .....	E10
608CA	Door Silencer .....	E10
609	Door Silencer.....	E10
611	Door Knocker.....	F1
614	Door Knocker .....	F1
614V	Door Knocker w/Viewer .....	F1
619	160° Door Viewer .....	F1
620	160° Door Viewer .....	F1

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

No.	Description	Page
620VC	160° Door Viewer .....	F1
621	160° Door Viewer .....	F1
622	190° Door Viewer .....	F2
622VC	190° Door Viewer .....	F2
624	160° Door Viewer .....	F1
626	190° Door Viewer .....	F2
627	190° Door Viewer w/Heavy Duty Cover .....	F2
628	190° Door Viewer w/Heavy Duty Cover .....	F2
629	190° Door Viewer w/Heavy Duty Cover .....	F2
618W	Door Viewer Washer .....	F2
630 Series	Surface Bolts.....	E6
651	Card Holder .....	F2
660	Decal.....	F3
661	Decal.....	F3
662-RKW	Decal.....	F3
670	Engraved Sign - SPECIFY COPY.....	F3
670M	Engraved Sign - MEN.....	F3
670R	Engraved Sign - RESTROOM.....	F3
670W	Engraved Sign - WOMEN .....	F3
674H	Engraved Sign - PUSH .....	F3
674L	Engraved Sign - PULL .....	F3
700	Hand Rail Bracket.....	F7
701	Hand Rail Bracket.....	F7
702	Hand Rail Bracket.....	F7
790	Small Coat Hook.....	F8
796	Small Double Coat Hook .....	F8
802	Medium Coat Hook.....	F8
806	Medium Coat Hook.....	F8
841	Ball Knob.....	F9
845	Utility Pull.....	F9
850	Solid Wire Pull.....	F9
851	Solid Wire Pull.....	F9
852	Solid Wire Pull.....	F9
853	Solid Wire Pull.....	F9
856-RKW	Heavy Wire Pull.....	F9
860	Flush Cup Pull.....	F10
870	Wrought Flush Pull.....	F10
872	Cast Flush Pull.....	F10
880	Cast Lever Edge Pull.....	F11
885	Concealed Edge Pull.....	F11
890	Pocket Door Pull .....	F11
891	Pocket Door Privacy Latch.....	F11
900	Magnetic Catch.....	F12
901	Magnetic Catch.....	F12
910	Adjustable Ball Catch.....	F13
910RC	Adjustable Ball Catch.....	F13
911	Adjustable Ball Catch.....	F13
911RC	Adjustable Ball Catch.....	F13
1100	Carry Bar .....	E12
1700	Door Coordinator.....	E12
2600	Series Door Coordinators.....	E11
2601AB	Mounting Bracket .....	E13
2601C	Mounting Bracket .....	E13
2601D	Mounting Bracket .....	E13
2805	Combination Flush Bolt .....	E14
2840	Automatic Flush Bolt.....	E14
2842	Automatic Flush Bolt Set .....	E14
2845	Combination Flush Bolt Set .....	E14
2848	Automatic Flush Bolt Set .....	E16
2849	Self Latching Flush Bolt (w/bottom fire bolt) .....	E18
2905	Combination Flush Bolt .....	E15
2940	Automatic Flush Bolt.....	E15
2942	Automatic Flush Bolt Set .....	E16
2945	Combination Flush Bolt Set .....	E16
2948	Automatic Flush Bolt Set .....	E16
2949	Self Latching Flush Bolt (w/bottom fire bolt) .....	E18
2960	Automatic Flush Bolt (w/bottom fire bolt).....	E18
2962	Automatic Flush Bolt Set .....	E18
11047	Straight Push Pull Bar Set.....	A14
11047-2	Straight Push Pull Bar Set.....	A15
11047-3	Straight Push Pull Bar Set.....	A16

No.	Description	Page
111A47	Straight Push Pull Bar Set.....	A14
111A47-2	Straight Push Pull Bar Set.....	A15
111A47-3	Straight Push Pull Bar Set.....	A16
11147	Straight Push Pull Bar Set.....	A14
11147-2	Straight Push Pull Bar Set.....	A15
11147-3	Straight Push Pull Bar Set.....	A16
11247	Straight Push Pull Bar Set.....	A14
11247-2	Straight Push Pull Bar Set.....	A15
11247-3	Straight Push Pull Bar Set.....	A16
11847	Straight Push Pull Bar Set.....	A14
19049	Straight Push Pull Bar Set.....	A23
AP1007	Arm Pull .....	B34
AP1140	Arm Pull .....	B34
AP1141	Arm Pull .....	B34
BF97	Barrier Free Flush Pull .....	B12
BF97L	Barrier Free Flush Pull .....	B12
BF150	90° Offset Door Pull.....	B28
BF151	90° Offset Door Pull.....	B28
BF152	90° Offset Door Pull.....	B28
BF156	90° Offset Door Pull.....	B28
BF15647	Offset Push Pull Bar Set .....	A17
BF15647-2	Offset Push Pull Bar Set .....	A18
BF15647-3	Offset Push Pull Bar Set .....	A19
BF157	90° Offset Door Pull.....	B28
BF157A	90° Offset Door Pull.....	B28
BF157A47	Offset Push Pull Bar Set .....	A16
BF157A47-2	Offset Push Pull Bar Set .....	A17
BF157A47-3	Offset Push Pull Bar Set .....	A18
BF15747	Offset Push Pull Bar Set .....	A16
BF15747-2	Offset Push Pull Bar Set .....	A17
BF15747-3	Offset Push Pull Bar Set .....	A18
BF158	90° Offset Door Pull.....	B28
BF15847	Offset Push Pull Bar Set .....	A17
BF15847-2	Offset Push Pull Bar Set .....	A18
BF15847-3	Offset Push Pull Bar Set .....	A19
BF159	90° Offset Door Pull.....	B28
BF15947	Offset Push Pull Bar Set .....	A17
BF19549	Offset Push Pull Bar Set .....	A23
BF160	45° Offset Door Pull.....	B31
BF161	45° Offset Door Pull.....	B31
BF162	45° Offset Door Pull.....	B31
BF166	45° Offset Door Pull.....	B31
BF167	45° Offset Door Pull.....	B31
BF167A	45° Offset Door Pull.....	B31
BF168	45° Offset Door Pull.....	B31
BF169	45° Offset Door Pull.....	B31
BF169	45° Offset Door Pull.....	B31
BF195	90° Offset Door Pull.....	B32
BF257	Heavy Duty Offset Door Pull .....	B32
BF258	Heavy Duty Offset Door Pull .....	B32
BF259	Heavy Duty Offset Door Pull .....	B32
BF260	Heavy Duty Offset Door Pull .....	B32
BF680	Engraved Sign w/Braille - SPECIFY COPY .....	F4
BF680M	Engraved Sign w/Braille - MEN.....	F4
BF680R	Engraved Sign w/Braille - RESTROOM .....	F4
BF680W	Engraved Sign w/Braille - WOMEN .....	F4
BF683	Tactile ADA Sign w/Braille .....	F5
BF684	Tactile ADA Sign w/Braille .....	F5
BF685	Tactile ADA Sign w/Braille .....	F5



Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

No.	Description	Page	No.	Description	Page
BF686	Tactile ADA Sign w/Braille .....	F5	K2125	Plastic Door Plate - .125".....	C4
BF687	Tactile ADA Sign w/Braille .....	F5	K3125	Laminate Plastic Door Plate - .125".....	C5
BF688	Tactile ADA Sign w/Braille .....	F5	K4125	Clear Plastic Door Plate - .125".....	C5
BF689	Tactile ADA Sign w/Braille .....	F5	KB1150	Angle Plate - .050".....	C6
BFLG10	Latch Guard Cover.....	C21	KB1151	Angle Plate - .050".....	C6
BFLG12	Latch Guard Cover.....	C21	KB1152	Angle Plate - .050".....	C6
BFLG16	Latch Guard Cover.....	C21	LA86	Latch Adapter Plate .....	F17
BFLG1050	Vertical Rod Latch Guard Cover .....	C21	LF161	Door Edge Filler Plate.....	F18
BFM624	All Gender Restroom Sign .....	F6	OH100 Series	Concealed Overhead Holder & Stop.....	D20
BFM625	All Gender Restroom Sign .....	F6	OH200 Series	Surface Overhead Holder & Stop.....	D22
BFM682	Tactile ADA Molded Plastic Sign w/Braille.....	F6	OH900 Series	Surface Overhead Holder & Stop.....	D23
BFM684	Tactile ADA Molded Plastic Sign w/Braille.....	F6	OH1000 Series	Surface Overhead Holder & Stop.....	D24
BFM685	Tactile ADA Molded Plastic Sign w/Braille.....	F6	PDLAA	Privacy Door Latch .....	E10
BFM686	Tactile ADA Molded Plastic Sign w/Braille.....	F6	R101LPB	Trim Protector Bar .....	C19
BFM687	Tactile ADA Molded Plastic Sign w/Braille.....	F6	R102LPB	Trim Protector Bar .....	C19
BFM688	Tactile ADA Molded Plastic Sign w/Braille.....	F6	R111LPB	Trim Protector Bar .....	C19
BFM689	Tactile ADA Molded Plastic Sign w/Braille.....	F6	R112LPB	Trim Protector Bar .....	C19
BFRC12	Vertical Rod Cover.....	C21	R115LPB	Trim Protector Bar .....	C19
BFRC24	Vertical Rod Cover.....	C21	R116EDPH	Exit Device Protector.....	C20
BH99	Behavioral Health Radius Pocket Pull .....	A1	R116EDPL	Exit Device Protector.....	C20
BH415	Behavioral Health Solid Cast Wall Stop.....	A1	SD1230	Standard Duty Trim Protector Bar .....	C18
BH420	Behavioral Health Solid Cast Wall Stop.....	A1	SD1240	Standard Duty Trim Protector Bar .....	C18
BP47 Series	Series 47 Push Bar w/Base Plate.....	A13	SD1250	Standard Duty Trim Protector Bar .....	C18
BP47-2	Series 47 Push Bar w/Base Plate.....	A13	SD1260	Standard Duty Trim Protector Bar .....	C18
BP47-3	Series 47 Push Bar w/Base Plate.....	A13	SF160	Strike Filler Plate.....	F18
CP10 Series	Standard Head Pivot .....	E20	SFASA	Strike Filler Plate .....	F18
CP40 Series	Standard Floor Pivot.....	E20	SFB160	Strike Filler Plate.....	F18
CPK1840	Cover Plate Kit.....	E17	SP47	Series 47 Push Bar .....	A12
CS Series	Custom Strikes.....	C21	T47 Series	Tubular Push Bars.....	A20
D89	Security Flush Pull .....	B8	T110 - T112	Tubular Straight Door Pulls.....	B15
D133-RKW	Security Loop Door Pull.....	B20	T118	Tubular Straight Door Pulls.....	B15
DF86	Door Edge Filler Plate.....	F14	T11047	Straight Tubular Single Bar Sets .....	A21
DFF4	Frame Hinge Filler Plate .....	F14	T111A47	Straight Tubular Single Bar Sets .....	A21
DFF5	Frame Hinge Filler Plate.....	F14	T11147	Straight Tubular Single Bar Sets .....	A21
DHF4B	Beveled Door Hinge Filler Plate .....	F14	T11247	Straight Tubular Single Bar Sets .....	A21
DHF4S	Square Door Hinge Filler Plate.....	F15	T11847	Straight Tubular Single Bar Sets .....	A21
DHF5B	Beveled Door Hinge Filler Plate .....	F15	TBF156	Tubular 90° Offset Door Pulls.....	B29
DHF5S	Square Door Hinge Filler Plate.....	F15	TBF157	Tubular 90° Offset Door Pulls.....	B29
FB-1	Filler Bar .....	E12	TBF157A	Tubular 90° Offset Door Pulls.....	B29
FB-2	Filler Bar .....	E12	TBF158	Tubular 90° Offset Door Pulls.....	B29
FBF48	Flush Bolt Filler Plate.....	F15	TBF159	Tubular 90° Offset Door Pulls.....	B29
FBS48	Flush Bolt Strike Filler Plate .....	F16	TBF15647	Offset Tubular Single Bar Sets.....	A22
FC161	Door Face Filler Plate .....	F16	TBF157A47	Offset Tubular Single Bar Sets.....	A22
FD160	Door Face Filler Plate .....	F16	TBF15747	Offset Tubular Single Bar Sets.....	A22
FP1230	Foot Pull.....	B35	TBF15847	Offset Tubular Single Bar Sets.....	A22
HD2230	Heavy Duty Trim Protector Bar .....	C17	TBF15947	Offset Tubular Single Bar Sets.....	A22
HD2230M	Heavy Duty Trim Protector Bar .....	C17	VRT12	Vandal Resistant Trim .....	B36
HD2240	Heavy Duty Trim Protector Bar .....	C17	VRT14	Vandal Resistant Trim .....	B37
HD2240M	Heavy Duty Trim Protector Bar .....	C17	VRT16	Vandal Resistant Trim .....	B37
HD2250	Heavy Duty Trim Protector Bar .....	C17	VRT22	Vandal Resistant Trim .....	B36
HD2250M	Heavy Duty Trim Protector Bar .....	C17	VRT24	Vandal Resistant Trim .....	B37
HS42	4 1/2" Hinge Shim - .028" .....	F16	VRT26	Vandal Resistant Trim .....	B37
HS44	4 1/2" Hinge Shim - .065" .....	F17	VRP30	Vandal Resistant Pull.....	B38
HS52	5" Hinge Shim - .028".....	F17	Y105 - Y112	Door Pull w/Base Plate.....	B17
HS54	5" Hinge Shim - .065".....	F17	Y118	Door Pull w/Base Plate .....	B17
K1038	Metal Door Plate - .038".....	C1	YBF150	90° Offset Door Pull w/Base Plate .....	B30
K1050	Metal Door Plate -.050" (Quick Ship) .....	C1	YBF151	90° Offset Door Pull w/Base Plate .....	B30
K1050-1-K1050-8	Shaped Door Plates - .050".....	C2	YBF152	90° Offset Door Pull w/Base Plate .....	B30
K1050F	Metal Door Plate - .050" .....	C1	YBF156	90° Offset Door Pull w/Base Plate .....	B30
K1062	Metal Door Plate - .062".....	C3	YBF157A	90° Offset Door Pull w/Base Plate .....	B30
K1125	Metal Door Plate - .125".....	C3	YBF157	90° Offset Door Pull w/Base Plate .....	B30
K2060	Plastic Door Plate - .060" .....	C4	YBF158	90° Offset Door Pull w/Base Plate .....	B30
			YBF159	90° Offset Door Pull w/Base Plate .....	B30

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



Rockwood Manufacturing Co. founders, brothers Norman and Vernon Gurzenda

## About Rockwood Manufacturing Company

Rockwood Manufacturing Company, founded in 1946 by the Gurzenda Family in rural southwestern Pennsylvania, focuses on the design and manufacture of quality builders' hardware for commercial, institutional and finer residential buildings. Now in the third generation of skilled craftsman, we continue to develop new products and processes that improve our offering. Strict attention to detail from the selection of top-grade materials to the application of the finest finishes results in a tough, yet handsome product of the highest caliber.

In 2008 Rockwood Manufacturing Company was purchased by ASSA ABLOY, the global leader in door opening solutions. This greatly expanded design and development capabilities and expanded the product offering to customers. This offering includes many coordinating products with other ASSA ABLOY Group companies through the Good Design Studio.



## Custom Designs

Design your own hardware! Whether it is a modification of a standard product or a completely unique design, we will quote your design and offer suggestions for best mounting applications. We take special pride in our custom products. For more information, please contact our sales staff.



## Rockwood Architectural Door Pulls

The alluring warmth of warm wood, smooth leather, clean and appealing lines. Just a few words to describe our beautiful architectural door pulls. With endless design options to choose from, our pulls will add contemporary beauty to any door opening.

Refer to the Rockwood Architectural Door Pulls catalog, found on our web site at [www.assaabloydooraccessories.us](http://www.assaabloydooraccessories.us)

### the good design studio

The Good Design Studio – your resource for beautiful doors, frames and hardware from ASSA ABLOY Group brands. Visit [www.thegooddesignstudio.com](http://www.thegooddesignstudio.com) to learn more.



CORBIN RUSSWIN 107 and SARGENT ME lever



McKINNEY 2 knuckle hinge with round end tips



ROCKWOOD small door pull



ASSA ABLOY is a member of the USGBC and CaGBC

U.S. Green Building Council logo is a trademark owned by the U.S. Green Building Council and is used with permission.

## LEED Certification Contribution

ASSA ABLOY can help to achieve prerequisites and accumulate points in several categories and credit areas of LEED. When you select a Rockwood stainless steel door pull for your LEED certified building project, you are using a product that is made from a minimum 75% post industrial waste and is 100% recyclable. Additionally these pulls can usually be refinished to their original appearance any time in the life of the building, eliminating the need for replacement when a renovation is conducted. For further information, please call 1-800-458-2424 or refer to our website [www.rockwoodmfg.com](http://www.rockwoodmfg.com)

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

## Sales & Support

### Sales

Rockwood Products are represented by a number of sales agencies as well as ASSA ABLOY Door Security Solutions representatives. To locate the representative for your area visit the Sales Representative map in the Contact Us area at [www.rockwoodmfg.com](http://www.rockwoodmfg.com), or call 1 800 458 2424.

### Ordering Information

Orders are accepted with the understanding that they will be billed at the prices in effect at time of shipment. Prices are subject to change without notice. We reserve the right to decline the whole or part of orders in which the price or quantity of goods is not acceptable to us.

### Easy Order Placement

By Phone: 1 800 458 2424 Monday through Friday, 8:00 am ET to 7:30 pm ET

By Fax: Orders may be faxed to 1 800 922 9212

By Email: [orders.rockwood@assaabloy.com](mailto:orders.rockwood@assaabloy.com)

By Internet: <http://extranet.assaabloydss.com/> and select Order Entry under the Customer Service Menu

Webshop: Architectural Door Accessories WebShop:  
<https://accessories.assaabloy.com/>

Canada:

By Phone: 1 800 461 3007 Monday through Friday, 8:00am ET to 4:30pm ET

By Fax: Orders may be faxed to 1 800 461 8989

By Email: [cavau-orders@assaabloy.com](mailto:cavau-orders@assaabloy.com)

By Internet: <http://extranet.assaabloydss.ca/> and select Order Entry under the Customer Service Menu

### Technical Support

Do you have a question? Let us help. Customer Service Representatives are available Monday through Friday, 8:00 am ET to 7:30 pm ET at 1 800 458 2424.

Our website is available 24/7 with current catalogs, sell sheets and the most up-to-date templates.

Visit [www.rockwoodmfg.com](http://www.rockwoodmfg.com)



## Terms & Conditions

### Terms and Conditions of Sale

Terms: 1% 15 days, net 30 days

Remit Payment To: PNC Bank/Rockwood,  
P.O. Box 644489, Pittsburgh, PA 15264-4489

For Terms & Conditions and Warranty information pertaining to product sales in Canada, please visit [www.assaabloy.ca/terms](http://www.assaabloy.ca/terms)

### Freight Policy

All prices are F.O.B. Rockwood, Pennsylvania, and/or Ventura, For freight policy terms & conditions please click [here](#) or see brand price book.

### Special Order Material

Special items made to your specifications are not returnable. These items are not subject to cancellation without consideration of expense involved at the cancellation date.

### Samples

Saleable samples will be charged at regular prices.

### Shortages

Claims for shortages must be made within 30 days of invoice date.

### Templates

Upon request we will furnish templates for any of our standard items of manufacture. Commonly used templates are available on our website at [www.rockwoodmfg.com](http://www.rockwoodmfg.com)

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

## Architectural Finishes

Most Rockwood products are available in all of the following architectural finishes. The catalog indicates exceptions. This finish list is grouped by base metal.

Base Metal	Description	Rockwood Code	BHMA Code	Base Metal	Description	Rockwood Code	BHMA Code
Aluminum	Satin	US27	627	Bronze	Polished clear coated	US9	611
Aluminum	Clear anodized	US28	628	Bronze	Satin clear coated	US10	612
Aluminum	Light bronze anodized	311	—	Bronze	Black oxidized bronze oil rubbed	US10A	722
Aluminum	Medium bronze anodized	312	—	Bronze	Satin oxidized oil rubbed	US10B*	613
Aluminum	Dark bronze anodized	313	710	Bronze	Oxidized equivalent	10BE	613E
Aluminum	Extra dark bronze anodized	314	—	Bronze	Satin oxidized clear coated	US10BL	614
Aluminum	Black anodized	315	711	Stainless Steel	Polished	US32	629
Aluminum	White powder coat	WPC	—	Stainless Steel	Satin	US32D	630
Aluminum	Red powder coat	RPC	—	Bronze	Satin dark statuary	US20A	624
Aluminum	Black powder coat	BPC	—				
Brass	Polished clear coated	US3	605				
Brass	Polished no coating	US3NL	—				
Brass	Satin clear coated	US4	606				
Brass	Satin oxidized relieved	US5	609				
Brass	Satin nickel plated clear coated	US15	619				
Brass	Satin nickel blackened relieved clear coated	US15A	620				
Brass	Flat black powder coated	US19	622				
Brass	Polished chrome plated	US26	625				
Brass	Satin chrome plated	US26D	626				

\*US10B is a living finish and will patina over time

### Special Finishes (see descriptions below)

Stainless Steel	Satin MicroShield® coated	US32DMS**	—
Stainless Steel	Polished 316 alloy	US32316**	—
Stainless Steel	Satin 316 alloy	US32D316**	—
	Black Suede Powder Coat	BSP	—
	White Suede Powder Coat	WSP	—

### US32DMS (MicroShield®):

As part of its promise to provide innovative solutions to their customers, ASSA ABLOY Group companies offer the MicroShield® technology, a silver-based antimicrobial coating designed to inhibit the spread of germs and bacteria.

### US32316 and US32D316:

Made from alloy 316 stainless steel containing molybdenum and extra nickel giving it substantially higher corrosion resistance than the standard stainless steels typically used in door hardware. This finish is ideal for use in coastal, urban, and industrial areas that have harsh environmental conditions. 32316 (polish) finishes offer the best corrosion resistance and should be used in caustic environments.



MicroShield® is a registered trademark of ASSA ABLOY.

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)

Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world



## Finish Tips

### Polished Brass

Polished brass is a beautiful finish that does not normally weather very well outdoors. Rockwood products use a very durable baked on clear powder coat on most door pulls and push bars. In indoor usage, this finish is extremely durable.

### Stainless Steel

Stainless steel is one of the most durable materials used in architecture; however there are many types with different properties and different levels of corrosion resistance. In most indoor (except chlorine and other harsh chemical exposure) and many outdoor (mildly corrosive) environments our standard stainless steel will perform exceeding well. It is best maintained by periodic water washing. If your job site has road salt, marine salt air, industrial, or urban pollution, we recommend the use of molybdenum bearing alloy 316 stainless steel. Specify US32**316** or US32D**316**. To enhance the corrosion resistance of stainless steel, use the polished finish (US32) in place of the satin finish (US32D). Minute particles of dirt and debris can lodge in the microscopic crevices of the satin finish more readily than on a smooth surface promoting corrosion. The mirror smooth surface of the polished finish has no rough surface to retain microscopic dirt or debris.

### Heat Resistant

Exterior hot sunny climates call for a finish that is resistant to heat. We recommend our white powder coat finish (WPC). This durable exterior finish reflects much of the heat rays and is substantially cooler to the touch than stainless steel or other finishes.

### Anti-Microbial Protection

MicroShield® (US32D**MS**) is the ideal finish for hospitals, schools, laboratories, assisted living facilities, public restroom areas, and anywhere there is a concern to control bacteria growth for demanding standards of cleanliness. Contact our customer service department for more detailed information.

### Finish Sample Displays

Educational and informative displays are available showing our most popular finishes.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Behavioral Health Radius Pocket Pull No. BH99

**Material:** Stainless Steel

**Finishes:** US32, US32D

**Fastener:** 5/16-18 FH MS and tamper-resistant Torx screws

- Features:**
- Simple, sleek design
  - Durable and easy to clean
  - Ideal for casework, patient room closet, and side opposite crash bar of passage-function cross-corridor doors in behavioral health applications
  - Ligature-resistant - please refer to New York State Office of Mental Health (OMH) Patient Safety Standards for current product compliance

No.	Grip Width	Grip Height	Proj.	Clearance	OA	Weight
BH99	1/2"	3/16" (4" or 6" OA)	1 1/4" (4" or 6" OA)	7/8" (4" or 6" OA)	4", 6", 12"	0.8 lbs. (4" OA)
		1/4" (12" OA)	1 3/4" (12" OA)	1 1/4" (12" OA)		1.1 lbs. (6" OA)
						2.1 lbs. (12" OA)



## Behavioral Health Solid Cast Wall Stop No. BH415

**Material:** Cast brass with nylon bumper

**Finishes:** US26, US26D

- Features:**
- Large profile with flush back plate, spreads impact of heavy/uncontrolled door contact
  - Prevents damage to door, wall
  - Universal screw pack included, suitable for all wall conditions
  - Tamper-resistant design promotes safe environment
  - For use in patient rooms - please refer to the New York State Office of Mental Health (OMH) Patient Safety Standards for current product compliance

No.	Bumper	Fastener	Size	Projection	Weight
BH415	Convex	1 - #8 - 32 x 2" RH MS and toggle bolt	4" dia.	3/4"	10 oz. each
		1 - #12 - 24 x 1 1/4" RH MS and anchor			
		3 - #8 x 1 1/4" Tamper-resistant FH SMS and plastic anchors			
		3 - #8 - 32 x 3/8" FH MS			



## Behavioral Health Solid Cast Wall Stop No. BH420

**Material:** Stainless steel with nylon bumper

**Finishes:** US32, US32D

- Features:**
- Large profile with flush back plate, spreads impact of heavy/uncontrolled door contact
  - Prevents damage to door, wall
  - Concealed, unexposed fasteners
  - Tamper-resistant design promotes safe environment
  - For use in patient rooms - please refer to the New York State Office of Mental Health (OMH) Patient Safety Standards for current product compliance

No.	Bumper	Fastener	Size	Projection	Weight
BH420	Convex	2 - 1/4-20 3/8" security set screws	2-1/2" dia.	31/32"	6.2 oz.
		1 - 1/4-20 brass conehead screws			
		1 - 1/4-20 x 1-1/2" hanger bolt			
		2 - 1/4-20 x 5/16" set screws			
		1 - #6 x 1-1/2" FH SMS			
		1 - #6 plastic wall anchor			

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

# How to Size Push Bars

## Flush Doors

Door width:

- Minus 5" for bent end bars
- Minus 5" for square end post mount bars
- Minus 7" for round end post mount bars


## Stile and Rail Doors or Doors with Lites

Door width:

- Minus width of one stile

**CAUTION:** Always confirm bars will not interfere with jamb or cause pinching hazard.

**CAUTION:** On narrow stile doors, be sure push bar base fits on the stile and bar does not interfere with the stop.




## Handing of Doors





The handing of a door is determined from the outside of the opening.

Standing outside the door:

- If the hinges are on the right, it is a right hand door
- If the hinges are on the left, it is a left hand door
- If the door opens away from you, it is a regular bevel door
- If the door opens toward you, it is a reverse bevel door



## Mounting Types for Push Bars No. 10 through No. 45 and No. 50, No. 51, No. 52



**ROCKWOOD**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Push Bar No. 10-PB

- Material:** Brass and Bronze
- Finishes:** Available in standard architectural finishes (see page 9)
- Mounting:** Metal door: type 2, surface, #8 - 32 x 3/4" OH MS  
Wood door: type 2, surface, #8 x 3/4" OH SMS
- Ordering:** Specify CTC, door type, mounting, and finish
- Features:** Can be field cut if necessary

No.	Material Size	Base	Projection	Clearance	Weight
10-PB	3/8" x 1 1/2"	1 1/2" x 2 7/8"	1 1/4"	5/8"	6.9 lbs.



## Push Bars No. 11-PB, 12-PB

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** **No. 11:**  
Metal door: type 2, surface, 1/4 - 20 x 1 1/2" MS & #8 - 32 x 3/4" OH MS  
**Wood door:** type 2, surface, #12 x 3/4" WS & #8 x 3/4" OH SMS
- No. 12:**  
Metal and wood door: type 1, 1/4 - 20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)
- Ordering:** Specify CTC, door type, mounting and finish
- Options:** Advise if door thickness is other than 1 3/4"


No.	Material Size	Base	Projection	Clearance	Weight
11-PB	3/8" x 1 1/2"	1" x 3" x 1/8"	2"	1 5/8"	6.2 lbs.
12-PB (less base plate)	3/8" x 1 1/2"	3/8" x 1 1/2"	1 7/8"	1 1/2"	6.2 lbs.



## Push Bars No. 14-PB, 15-PB

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal and wood door: type 1,  $\frac{1}{4}$  - 20 x  $2\frac{1}{4}$ " thru bolt & finish washer (standard  $1\frac{3}{4}$ " door)
- Ordering:** Specify CTC, door type, mounting, and finish
- Options:** Advise if door thickness is other than  $1\frac{3}{4}$ "

No.	Material Size	Base	Projection	Clearance	Weight
14-PB	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	$1\frac{1}{2}$ " x 2" x $\frac{1}{8}$ "	2"	$1\frac{5}{8}$ "	6.3 lbs.
15-PB (less base plate)	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	$1\frac{7}{8}$ "	$1\frac{1}{2}$ "	6.1 lbs.



## Push Bars No. 18-PB, 19-PB

- Material:** Aluminum, brass, stainless steel, bronze
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** **No. 18:**  
Metal door: type 2, surface,  $\frac{1}{4}$  - 20 x 1" and #8 - 32 x  $\frac{3}{4}$ " OH MS  
Wood door: type 2, surface, #12 x  $1\frac{1}{4}$ " FH WS and #8 x  $\frac{3}{4}$ " OH SMS
- No. 19:**  
Metal door: type 1, thru bolt,  $\frac{1}{4}$  - 20 x 1 OH MS  
Wood door: type 1, thru bolt, #12 x  $1\frac{1}{4}$ " FH WS, finish washer
- Ordering:** Specify CTC, door type, mounting, and finish
- Options:** Advise if door thickness is other than  $1\frac{3}{4}$ "

No.	Material Size	Base	Projection	Clearance	Weight
18-PB	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	1" x 3 x $\frac{1}{8}$ "	$2\frac{1}{8}$ "	$1\frac{3}{4}$ "	6.2 lbs.
19-PB (less base plate)	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	2"	$1\frac{5}{8}$ "	6.2 lbs.


**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Pull Bars No. 20-PB, 21-PB

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal and wood door: type 1,  $\frac{1}{4}$  - 20 x  $2\frac{1}{4}$ " thru bolt and finish washer (standard  $1\frac{3}{4}$ " door)
- Ordering:** Specify CTC, door type, and finish
- Options:**
- Ideal for engraving
  - Advise if door thickness is other than  $1\frac{3}{4}$ "

No.	Material Size	Base	Projection	Clearance	Space	Weight
20-PB	$\frac{3}{8}$ " x $1\frac{1}{4}$ "	$1\frac{1}{2}$ " x $1\frac{1}{4}$ "	$2\frac{1}{4}$ "	$1\frac{7}{8}$ "	8"	12.3 lbs.
21-PB	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	$1\frac{1}{2}$ " x $1\frac{1}{2}$ "	$2\frac{1}{4}$ "	$1\frac{7}{8}$ "	8"	14.7 lbs.



## Pull Bars No. 22-PB, 23-PB

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal and wood door: type 1,  $\frac{1}{4}$  - 20 x  $2\frac{1}{4}$ " thru bolt and finish washer (standard  $1\frac{3}{4}$ " door)
- Ordering:** Specify CTC, door type, and finish
- Options:** Ideal for engraving
- Other:**
- Pull length is 42" from top post to bottom post
  - Advise if door thickness is other than  $1\frac{3}{4}$ "

No.	Material Size	Base	Projection	Clearance	Space	Weight
22-PB	$\frac{3}{8}$ " x $1\frac{1}{4}$ "	$1\frac{1}{2}$ " x $1\frac{1}{4}$ "	$2\frac{1}{4}$ "	$1\frac{7}{8}$ "	8"	16.7 lbs.
23-PB	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	$1\frac{1}{2}$ " x $1\frac{1}{2}$ "	$2\frac{1}{4}$ "	$1\frac{7}{8}$ "	8"	20.0 lbs.



## Push Bars No. 25-PB, 26-PB

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal and wood door: type 1,  $\frac{1}{4}$  - 20 x  $2\frac{1}{4}$ " thru bolt and finish washer (standard  $1\frac{3}{4}$ " door)  
Metal door: type 2, surface,  $\frac{1}{4}$  - 20 MS  
Wood door: type 2, surface, #12 WS
- Ordering:** Specify CTC, door type, mounting, and finish
- Options:** Advise if door thickness is other than  $1\frac{3}{4}$ "

No.	Material Size	Base	Projection	Clearance	Space	Weight
25-PB	$\frac{3}{8}$ " x $1\frac{1}{4}$ "	$1\frac{1}{2}$ " x $1\frac{1}{4}$ "	$\frac{3}{4}$ "	$\frac{3}{8}$ "	—	4.8 lbs.
26-PB	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	$1\frac{1}{2}$ " x $1\frac{1}{2}$ "	$\frac{3}{4}$ "	$\frac{3}{8}$ "	—	5.8 lbs.

## Push & Pull Bar Sets No. 27-PB, 28-PB, 29-PB, 30-PB

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal and wood door: type 3, back to back,  $\frac{1}{4}$  - 20 MS
- Ordering:** Specify CTC, door type, and finish

No.	Material Size	Space	Weight
27-PB	Set consists of 1 #20-PB and 2 #25-PB	8"	21.9 lbs.
28-PB	Set consists of 1 #21-PB and 2 #26-PB	8"	26.3 lbs.
29-PB	Set consists of 1 #22-PB and 2 #25-PB	8"	26.3 lbs.
30-PB	Set consists of 1 #23-PB and 2 #26-PB	8"	31.6 lbs.


**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog


Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Pull Bars No. 31-PB, 32-PB

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal and wood door: type 1, thru bolt, 1/4 - 20 x 2 1/4" FH MS, finish washers (standard 1 3/4" door)
- Ordering:** Specify CTC, door type, and finish
- Options:**
- Ideal for engraving
  - Advise if door thickness is other than 1 3/4"

No.	Material Size	Base	Projection	Clearance	Space	Weight
31-PB	3/8" x 1 1/4"	2" x 12" x 1/8"	2"	1 5/8"	8"	12.8 lbs.
32-PB	3/8" x 1 1/2"	2" x 12" x 1/8"	2"	1 5/8"	8"	15.4 lbs.



## Push Bars No. 33-PB, 34-PB


- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal door: type 2, surface, #8 - 32 x 3/4" OH MS  
Wood door: type 2, surface, #8 x 3/4" OH SMS
- Ordering:** Specify CTC, door type, mounting, and finish
- Options:** Ideal for engraving

No.	Material Size	Base	Projection	Clearance	Space	Weight
33-PB	3/8" x 1 1/4"	2" x 12" x 1/8"	1 5/8"	1 1/4"	8"	10.9 lbs.
34-PB	3/8" x 1 1/2"	2" x 12" x 1/8"	1 5/8"	1 1/4"	8"	13.1 lbs.

## Push and Pull Bar Sets No. 35-PB, 36-PB

- Material:** Aluminum, brass, stainless steel, bronze
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal door: type 4, back to back, 1/4 - 20 x 2 1/4" & #8 - 32 x 3/4" OH MS  
Wood door: type 4, back to back, 1/4 - 20 x 2 1/4" & #8 x 3/4" OH SMS
- Ordering:** Specify CTC, door type, mounting, and finish


No.	Material Size	Space	Weight
35-PB	Set consists of 1 #31-PB & 1 #33-PB	8"	23.7 lbs.
36-PB	Set consists of 1 #32-PB & 1 #34-PB	8"	28.5 lbs.



## Screen Door Guard No. 40-PB

- Material:** Brass and Bronze
- Finishes:** Available in standard architectural finishes (see page 9)
- Mounting:** Metal door: type 2, surface, #8 - 32 x 3/4" OH MS  
Wood door: type 2, surface, #8 x 3/4" OH SMS
- Ordering:** Specify CTC, door type, mounting, and finish

No.	Material Size	Base	Projection	Clearance	Bar Space	Weight
40-PB	5/8" tube	5/8" x 9 5/8"	1 1/8"	3/8"	3 1/2"	4.5 lbs.



## Screen Door Guard No. 41-PB

- Material:** Brass and Bronze
- Finishes:** Available in standard architectural finishes (see page 9)
- Mounting:** Metal door: type 2, surface, #8 - 32 x 3/4" OH MS  
Wood door: type 2, surface, #8 x 3/4" OH SMS
- Ordering:** Specify CTC, door type, mounting, and finish

No.	Material Size	Base	Projection	Clearance	Bar Space	Weight
41-PB	5/8" tube	5/8" x 6 1/8"	1 1/8"	3/8"	3 1/2"	2.9 lbs.



## Screen Door Guard No. 42-PB

- Material:** Brass and Bronze
- Finishes:** Available in standard architectural finishes (see page 9)
- Mounting:** Metal door: type 2, surface, #8 - 32 x 3/4" OH MS  
Wood door: type 2, surface, #8 x 3/4" OH SMS
- Ordering:** Specify CTC, door type, mounting, and finish

No.	Material Size	Base	Projection	Clearance	Bar Space	Weight
42-PB	5/8" tube	5/8" x 2 5/8"	1 1/8"	3/8"	—	1.6 lbs.

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Push Bars No. 43-PB, 44-PB

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal and wood door: type 1, 1/4 - 20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)
- Ordering:** Specify CTC, door type, mounting, and finish
- Other:** Ideal for engraving or logos
- Options:** Advise if door thickness is other than 1 3/4"


No.	CTC	Material Size	Base	Projection	Clearance	Weight
43-PB	Specify	3/8" x 3"	1 1/2" x 4 1/2" x 1/8"	2"	1 5/8"	10.5 lbs.
44-PB (less base plate)	Specify	3/8" x 3"	—	1 7/8"	1 1/2"	10.1 lbs.



## Push Bar No. 45-PB

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US32 (see page 9)
- Mounting:** Metal and wood door: type 1, 1/4 - 20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)
- Ordering:** Specify CTC, door type, mounting, and finish
- Other:** Ideal for engraving or logos
- Options:** Advise if door thickness is other than 1 3/4"

No.	CTC	Material Size	Base	Projection	Clearance	Weight
45-PB	Specify	3/8" x 3"	1 1/2" x 3"	3/4"	3/8"	9.9 lbs.



## Pull Bar No. 50-PB

- Material:** Brass, bronze
- Finishes:** Available in standard architectural finishes (see page 9)
- Mounting:** Metal and wood door: type 1,  $\frac{1}{4}$  - 20 x  $2\frac{1}{4}$ " thru bolt & finish washer (standard  $1\frac{3}{4}$ " door)  
Wood door: type 2 surface, #8 x  $\frac{3}{4}$ " OH SMS
- Ordering:** Specify CTC, door type, and finish
- Other:** Cast slip-on end brackets
- Options:** Advise if door thickness is other than  $1\frac{3}{4}$ "

No.	Material Size	Base	Projection	Clearance	Space	Weight
50-PB	1" dia.	2" dia.	$3\frac{1}{8}$ "	$2\frac{5}{8}$ "	$7\frac{1}{2}$ "	7.6 lbs.



## Push Bar and Door Pull No. 51-PB, 53-PB

- Material:** Brass, bronze
- Finishes:** Available in standard architectural finishes (see page 9)
- Mounting:** Metal and wood door: type 1, thru bolt,  $\frac{1}{4}$  - 20 x  $2\frac{1}{4}$ " MS, finish washers (standard  $1\frac{3}{4}$ " door)  
Metal door: type 2, surface, #8 - 32 x  $\frac{3}{4}$ " OH MS  
Wood door: type 2, surface, #8 x  $\frac{3}{4}$ " OH SMS
- Ordering:** Specify CTC, door type, mounting, and finish
- Other:** Cast slip-on end brackets
- Options:** Advise if door thickness is other than  $1\frac{3}{4}$ "

No.	Material Size	CTC	Base	Projection	Clearance	Weight
51-PB	1" dia.	Specify	2" dia.	$2\frac{3}{8}$ "	$1\frac{1}{4}$ "	3.1 lbs.
53-PB	1" dia.	12"	2" dia.	$2\frac{3}{8}$ "	$1\frac{1}{4}$ "	1.5 lbs.

## Push and Pull Bar Set No. 52-PB

- Material:** Brass, bronze
- Finishes:** Available in standard architectural finishes (see page 9)
- Mounting:** Metal door: type 4, back to back,  $\frac{1}{4}$  - 20 x  $2\frac{1}{4}$ " MS and #8 - 32 x  $\frac{3}{4}$ " OH MS  
Wood door: type 4, back to back,  $\frac{1}{4}$  - 20 x  $2\frac{1}{4}$ " MS and #8 x  $\frac{3}{4}$ " OH SMS
- Ordering:** Specify CTC, door type, mounting, and finish
- Other:** Cast slip-on end brackets

No.	Material Size	Weight
52-PB	Set consists of 1 #50-PB and 2 #51-PB	30.9 lbs.

**ROCKWOOD**<sup>®</sup>


**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog


Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

# Typical Mounting



## Thru Bolt


Wood or Metal Door - Type 1



Type	Bolt Size	Drill Size	
		Wood	Metal
1	1/4 - 20	9/32	9/32
1HD	5/16 - 18	11/32	11/32
1XHD	3/8 - 16	13/32	13/32


## Free End Details

Wood or Metal Door - Type 12



Type	Bolt Size	Drill Size	
		Wood	Metal
12	1/4 - 20	9/32	9/32
12HD	5/16 - 18	11/32	11/32
12XHD	3/8 - 16	13/32	13/32


Glass Door - Type 15



Type	Bolt Size	Drill Size - Glass
15	1/4 - 20	5/8
15HD	5/16 - 18	5/8
15XHD	3/8 - 16	5/8


## Surface Concealed

Metal Door - Type 6




Type	Bolt Size	Drill Size - Metal
6	1/4 - 20	1/4 - 20 tap
6HD	5/16 - 18	5/16 - 18 tap

Wood Door - Type 8



Type	Bolt Size	Drill Size - Wood
8	1/4 - 20	23/64 x 9/16 dp
8HD	5/16 - 18	7/16 x 9/16 dp


Metal Door - Type 17



Type	Bolt Size	Drill Size - Metal
17	1/4 - 20	1/4 - 20 tap
17HD	5/16 - 18	5/16 - 18 tap


## Common End Details

Wood or Metal Door - Type 5



Type	Bolt Size	Drill Size	
		Wood	Metal
5	1/4 - 20	9/32	9/32
5HD	5/16 - 18	11/32	11/32

Glass Door - Type 13



Type	Bolt Size	Drill Size - Glass
13	1/4 - 20	5/8
13HD	5/16 - 18	5/8

*NOTE: Heavy Duty (HD/XHD) mounting features hex drive for positive tightening and large overall size for superior strength. Recommended for high frequency and rough service openings.*



## Series 47 Push Bar No. SP47

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes; US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)
- Mounting:** Metal and wood door: type 1, 1/4" - 20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)  
*NOTE: See page A10 for detailed mounting drawings*
- Ordering:** Specify CTC, handing, door type, and finish
- Options:**
- Engraving "PUSH" or "PULL"
  - Advise if door thickness is other than 1 3/4"


No.	CTC	Material Size	Base	Projection	Clearance	Weight
SP47	Specify	1" dia.	1" dia.	2 3/4"	1 1/2"	8.5 lbs.



## Series 47 Push Bar No. 47-PB, 47-2-PB, 47-3-PB, 48-PB



- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)
- Mounting:**
- No. 47, 47-2, 47-3:**  
Metal and wood door: type 1, 1/4" - 20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)  
Metal door: type 6, concealed, 1/4" - 20 CH MS
- No. 48 (not shown):**  
Metal and wood door: type 1, 1/4" - 20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)  
*NOTE: See page A10 for detailed mounting drawings*
- Ordering:** Specify CTC, door type, mounting, and finish
- Options:**
- Engraving "PUSH" or "PULL". Specify handing
  - Heavy duty versions of most fastening types available – use suffix HD to fastening type number (47 Type 6HD)
  - Advise if door thickness is other than 1 3/4"



No.	CTC	Material Size	Base	Projection	Clearance	Weight
47-PB	Specify	1" dia.	1" dia.	2 3/4"	1 3/4"	8.5 lbs.
47-2-PB	Specify	1" dia.	1" dia.	2 3/4"	1 3/4"	17.0 lbs.
47-3-PB	Specify	1" dia.	1" dia.	2 3/4"	1 3/4"	25.5 lbs.
48-PB	Specify	3/4" dia.	3/4" dia.	2 3/4"	1 3/4"	4.5 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



49-PB


## Series 49 Push Bar No. 49-PB with Santoprene grip

- Material:** Aluminum
- Finishes:** Available in US28, 313, 314, 315, 10BE, BSP (Black Suede), WSP (White Suede), stock powder coat finishes (see page 9)
- Mounting:**
- Metal and wood door: type 1, 1/4"-20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)
  - Metal and wood door: type 5 back-to-back, 1/4"-20 x 2 1/4" cone head machine screws
  - Metal door: type 6, concealed, 1/4"-20 Cone Head Machine Screws
  - Glass door: type 13, back-to-back, 1/4"-20 x 1 1/8" conehead machine screws and finish washer
- Features:** Santoprene™ durable, weather resistant grip - available in black (standard), red, and brown
- Options:** Heavy duty versions of most fastening types available - use suffix HD to fastening type number (49 Type 6HD)  
Advise if door thickness is other than 1 3/4"  
See page B13 for mounting selection (standard duty 1/4" - 20)


No.	CTC	Material Size	Base	Projection	Clearance	Weight
49-PB	Specify	1" dia.	1" dia.	2 3/4"	1 3/4"	9.5 lbs.



No. BP47




No. BP47-2



No. BP47-3

## Series 47 Push Bar No. BP47, BP47-2, BP47-3

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)
- Mounting:**
- No. BP47:**  
Metal and wood door: type 1, 1/4 - 20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)  
Metal door: type 6, concealed, 1/4 - 20 CH MS x 1/2" thread
- No. BP47-2, BP47-3:**  
Metal and wood door: type 1, 1/4 - 20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)  
Metal door: type 2, surface, #8 - 32 x 3/4" OH MS  
Wood door: type 2, surface, #8 x 3/4" OH SMS  
Metal door: type 6, concealed, 1/4 - 20 CH MS x 1/2" thread  
*NOTE: See page A10 for detailed mounting drawings*
- Ordering:** Specify CTC, door type, mounting and finish.
- Options:**
- Engraving "PUSH" or "PULL". Specify handing
  - Heavy duty versions of most fastening types available - use suffix HD to fastening type number (BP47 Type 6HD)
  - Advise if door thickness is other than 1 3/4"




Engraved

No.	CTC	Material Size	Base	Projection	Clearance	Weight
BP47	Specify	1" dia.	1 1/4" dia.	2 7/8"	1 7/8"	9.0 lbs.
BP47-2	Specify	1" dia.	2" x 6"	2 7/8"	1 7/8"	18.0 lbs.
BP47-3	Specify	1" dia.	2" x 10"	2 7/8"	1 7/8"	27.5 lbs.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world



## Series 47 Straight Single Bar Sets

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32D**MS**, US32D**316**, US32**316**, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9).

Mounting:	Door	Pull Free End	Push Free End	Common End	Description	Mounting Spec. No.
	Metal & wood	1	1	5	Back to back & thru bolt	T3**
	Metal	6	6	5	Back to back & concealed	T4
	Wood	8	8	5	Back to back & concealed	T5
	Metal & wood	12	12	5	Back to back & decorative bolt	T1
	Glass	15	15	13	Back to back & thru bolt	T2

\*\* T3 is the standard mounting method for metal and wood doors.

*NOTE: See page A10 for detailed mounting drawings*

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (11247 T3, wood door, 33" CTC, US32D**316**)

**Other:** See page A1 on "How To" size push bars

**Options:**

- Engraving "PUSH" or "PULL". Specify handing
- Base plates available similar to those shown on page A12 — use BP prefix (BP11047) when ordering
- Heavy duty versions of most fastening types available — use suffix HD to fastening type number (11047 T3HD)

*NOTE: Pull bar Projection : 3-1/2" for Stainless Steel and 3" for Aluminum, Brass and Bronze.*



No.	Material Size	Pull			Push		Weight
		CTC	Projection	Clearance	Projection	Clearance	
11047	1" dia.	8"	3 1/2"	2"	2 3/4"	1 3/4"	11.5 lbs.
111A47	1" dia.	9"	3 1/2"	2"	2 3/4"	1 3/4"	11.7 lbs.
11147	1" dia.	10"	3 1/2"	2"	2 3/4"	1 3/4"	12.0 lbs.
11247	1" dia.	12"	3 1/2"	2"	2 3/4"	1 3/4"	12.5 lbs.
11847	1" dia.	18"	3 1/2"	2"	2 3/4"	1 3/4"	14.0 lbs.

*Pull projection is 3 1/2" for stainless steel and 3" for aluminum, brass and bronze.*


**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Series 47 Straight Double Bar Sets

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32D**MS**, US32D**316**, US32**316**, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9).

Mounting:	Door	Push Free End	Common End	Description	Mounting Spec. No.
	Metal & wood	1	5	Back to back & thru bolt	T3**
	Metal	6	5	Back to back & concealed	T4
	Wood	8	5	Back to back & concealed	T5
	Metal & wood	12	5	Back to back & decorative bolt	T1
	Glass	15	13	Back to back & thru bolt	T2

\*\* T3 is the standard mounting method for metal and wood doors.

*NOTE: See page A10 for detailed mounting drawings.*

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (11247-2 T3, wood door, 33" CTC, US32D**316**)

**Other:** See page A1 on "How To" size push bars

**Options:**

- Engraving "PUSH" or "PULL". Specify handing
- Base plates available similar to those shown on page A12 – use BP prefix (BP11047-2) when ordering
- Heavy duty versions of most fastening types available – use suffix HD to fastening type number (11047-2 T3HD)

*NOTE: Pull bar Projection : 3-1/2" for Stainless Steel and 3" for Aluminum, Brass and Bronze.*


No.	Material Size	Pull			Push		Weight
		CTC	Projection	Clearance	Projection	Clearance	
11047-2	1" dia.	8"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	20.0 lbs.
111A47-2	1" dia.	9"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	20.2 lbs.
11147-2	1" dia.	10"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	20.5 lbs.
11247-2	1" dia.	12"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	21.0 lbs.

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world



## Series 47 Straight Triple Bar Sets

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9).

Mounting:	Door	Push Free End	Common End	Description	Mounting Spec. No.
	Metal & wood	1	5	Back to back & thru bolt	T3**
	Metal	6	5	Back to back & concealed	T4
	Wood	8	5	Back to back & concealed	T5
	Metal & wood	12	5	Back to back & decorative bolt	T1
	Glass	15	13	Back to back & thru bolt	T2

\*\* T3 is the standard mounting method for metal and wood doors.

NOTE: See page A10 for detailed mounting drawings

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (11247-3 T3, wood door, 33" CTC, US32D316)

**Other:** See page A1 on "How To" size push bars

**Options:**

- Engraving "PUSH" or "PULL". Specify handing
- Base plates available similar to those shown on page A12 – use BP prefix (BP11047-3) when ordering
- Heavy duty versions of most fastening types available – use suffix HD to fastening type number (11047-3 T3HD)

NOTE: Pull bar Projection : 3-1/2" for Stainless Steel and 3" for Aluminum, Brass and Bronze.

No.	Material Size	Pull			Push		Weight
		CTC	Projection	Clearance	Projection	Clearance	
11047-3	1" dia.	8"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	28.5 lbs.
111A47-3	1" dia.	9"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	28.7 lbs.
11147-3	1" dia.	10"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	29.0 lbs.
11247-3	1" dia.	12"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	29.5 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Series 47 Offset Single Bar Sets

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32D**MS**, US32D**316**, US32**316**, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9).

Mounting:	Door	Pull Free End	Push Free End	Common End	Description	Mounting Spec. No.
	Metal & wood	1	1	5	Back to back & thru bolt	T3**
	Metal	17	17	16	Back to back & concealed	T4
	Wood	8	8	5	Back to back & concealed	T5
	Metal & wood	12	12	5	Back to back & decorative bolt	T1
	Glass	15	15	13	Back to back & thru bolt	T2

\*\* T3 is the standard mounting method for metal and wood doors.

*NOTE: See page A10 for detailed mounting drawings*

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (BF15747 T3, wood door, 33" CTC, US32D**316**)

**Other:** See page A1 on "How To" size push bars

**Options:**

- Engraving "PUSH" or "PULL". Specify handing
- Base plates available similar to those shown on page A12 – use BP prefix (BPBF15747) when ordering
- Heavy duty versions of most fastening types available – use suffix HD to fastening type number (BF15647 T3HD)

No.	Material Size	Pull			Push		Weight
		CTC	Projection	Clearance	Projection	Clearance	
BF15647	1" dia.	8"	3½"	2½"	2¾"	1¾"	12.4 lbs.
BF157A47	1" dia.	9"	3½"	2½"	2¾"	1¾"	12.6 lbs.
BF15747	1" dia.	10"	3½"	2½"	2¾"	1¾"	12.8 lbs.
BF15847	1" dia.	12"	3½"	2½"	2¾"	1¾"	13.3 lbs.
BF15947	1" dia.	18"	3½"	2½"	2¾"	1¾"	15.0 lbs.


**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Series 47 Offset Double Bar Sets

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32D**MS**, US32D**316**, US32**316**, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9).

Mounting:	Door	Push Free End	Common End	Description	Mounting Spec. No.
	Metal & wood	1	5	Back to back & thru bolt	T3**
	Metal	17	16	Back to back & concealed	T4
	Wood	8	5	Back to back & concealed	T5
	Metal & wood	12	5	Back to back & decorative bolt	T1
	Glass	15	13	Back to back & thru bolt	T2

\*\* T3 is the standard mounting method for metal and wood doors.

*NOTE: See page A10 for detailed mounting drawings*

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (BF15747-2 T3, wood door, 33" CTC, US32D**316**)

**Other:** See page A1 on "How To" size push bars

**Options:**

- Engraving "PUSH" or "PULL". Specify handing
- Base plates available similar to those shown on page A12 – use BP prefix (BPBF15747-2) when ordering
- Heavy duty versions of most fastening types available – use suffix HD to fastening type number (BF15647-2 T3HD)

No.	Material Size	Pull			Push		Weight
		CTC	Projection	Clearance	Projection	Clearance	
BF15647-2	1" dia.	8"	3½"	2½"	2¾"	1¾"	20.9 lbs.
BF157A47-2	1" dia.	9"	3½"	2½"	2¾"	1¾"	21.1 lbs.
BF15747-2	1" dia.	10"	3½"	2½"	2¾"	1¾"	21.3 lbs.
BF15847-2	1" dia.	12"	3½"	2½"	2¾"	1¾"	21.8 lbs.


**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Series 47 Offset Triple Bar Sets

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9).

Mounting:	Door	Push Free End	Common End	Description	Mounting Spec. No.
	Metal & wood	1	5	Back to back & thru bolt	T3**
	Metal	17	16	Back to back & concealed	T4
	Wood	8	5	Back to back & concealed	T5
	Metal & wood	12	5	Back to back & decorative bolt	T1
	Glass	15	13	Back to back & thru bolt	T2

\*\* T3 is the standard mounting method for metal and wood doors.

NOTE: See page A10 for detailed mounting drawings

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (BF15747-3 T3, wood door, 33" CTC, US32D316)

**Other:** See page A1 on "How To" size push bars

**Options:**

- Engraving "PUSH" or "PULL". Specify handing
- Base plates available similar to those shown on page A12 – use BP prefix (BPBF15747-3) when ordering
- Heavy duty versions of most fastening types available – use suffix HD to fastening type number (BF15647-3 T3HD)

No.	Material Size	Pull			Push		Weight
		CTC	Projection	Clearance	Projection	Clearance	
BF15647-3	1" dia.	8"	3 <sup>1</sup> / <sub>2</sub> "	2 <sup>1</sup> / <sub>2</sub> "	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	29.4 lbs.
BF157A47-3	1" dia.	9"	3 <sup>1</sup> / <sub>2</sub> "	2 <sup>1</sup> / <sub>2</sub> "	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	29.6 lbs.
BF15747-3	1" dia.	10"	3 <sup>1</sup> / <sub>2</sub> "	2 <sup>1</sup> / <sub>2</sub> "	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	29.8 lbs.
BF15847-3	1" dia.	12"	3 <sup>1</sup> / <sub>2</sub> "	2 <sup>1</sup> / <sub>2</sub> "	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	30.3 lbs.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world

## T Series 1" Tubular Push Bars and Push & Pull Bar Sets

The Rockwood T Series 1" diameter tubular push and pull bar sets are made from sturdy .065" thick wall tubing. Solid brass or stainless steel inserts are brazed into the ends to provide a solid area for our guaranteed mounting systems.

Benefits of specifying the T Series push and pulls include:

- Tubular pulls weigh 25% less than their solid counterparts; this 75% weight reduction greatly reduces the environmental impact of harvesting material for their manufacture – a LEED certified building goal
- The lighter weight minimizes the risk of damage in shipping and handling
- The cost of most tubular pulls represents a significant savings over the equivalent solid model

Considering all the benefits, the T Series pulls offer an improved value without any quality sacrifice.

T Series is also available in straight pulls (see page B15) and offset pulls (see page B29).



No. T47



No. T47-2



No. T47-3

### T47 Series Tubular Push Bars No. T47, T47-2, T47-3

**Material:** Brass, bronze, stainless steel


**Finishes:** Available in standard architectural finishes (see page 9)

**Mounting:** Metal and wood door: type 1, 1/4" - 20 x 2 1/4" thru bolt and finish washer (standard 1 3/4" door)  
Metal door: type 6, concealed, 1/4" - 20 CH MS  
*NOTE: See page A10 for detailed mounting drawings*

**Ordering:** Specify CTC, door type, mounting, and finish (Specify Handing)

**Options:**

- Engraving "PUSH" or "PULL"
- Advise if door thickness is other than 1 3/4"



Engraved

No.	CTC	Material Size	Base	Projection	Clearance	Weight
T47	Specify	1" dia.	1" dia.	2 3/4"	1 3/4"	2.9 lbs.
T47-2	Specify	1" dia.	1" dia.	2 3/4"	1 3/4"	5.8 lbs.
T47-3	Specify	1" dia.	1" dia.	2 3/4"	1 3/4"	8.7 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## T47 Series Straight Tubular Single Bar Sets

**Material:** Brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes (see page 9)

Mounting:	Door	Pull Free End	Push Free End	Common End	Description	Mounting Spec. No.
	Metal & wood	1	1	5	Back to back & thru bolt	T3**
	Metal	6	6	5	Back to back & concealed	T4
	Wood	8	8	5	Back to back & concealed	T5
	Metal & wood	12	12	5	Back to back & decorative bolt	T1
	Glass	15	15	13	Back to back & thru bolt	T2

\*\*T3 is the standard mounting method for metal and wood doors.

*NOTE: See page A10 for detailed mounting drawings*

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (T11247 T3, wood door, 33" CTC, US32D)

**Other:** See page A1 on "How To" size push bars

**Options:**

- Engraving "PUSH" or "PULL". Specify handing
- Base plates available similar to those shown on page A12 – use BP prefix (TBP11047) when ordering



No.	Material Size	Pull			Push		Weight
		CTC	Projection	Clearance	Projection	Clearance	
T11047	1" dia.	8"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	3.9 lbs.
T111A47	1" dia.	9"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	4.0 lbs.
T11147	1" dia.	10"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	4.0 lbs.
T11247	1" dia.	12"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	4.1 lbs.
T11847	1" dia.	18"	3"	2"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	4.6 lbs.



## TBF47 Series Offset Tubular Single Bar Sets

**Material:** Brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes (see page 9)

**Mounting:**

Door	Pull Free End	Push Free End	Common End	Description	Mounting Spec. No.
Metal & wood	1	1	5	Back to back & thru bolt	T3**
Metal	17	17	16	Back to back & concealed	T4
Wood	8	8	5	Back to back & concealed	T5
Metal & wood	12	12	5	Back to back & decorative bolt	T1
Glass	15	15	13	Back to back & thru bolt	T2

\*\*T3 is the standard mounting method for metal and wood doors.

*NOTE: See page A10 for detailed mounting drawings*

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (TBF15747 T3, wood door, 33" CTC, US32D)

**Other:** See page A1 on "How To" size push bars

**Options:**

- Engraving "PUSH" or "PULL". Specify handing
- Base plates available similar to those shown on page A12 – use BP prefix (TBF15747) when ordering

No.	Material Size	Pull			Push		Weight
		CTC	Projection	Clearance	Projection	Clearance	
TBF15647	1" dia.	8"	3½"	2½"	2¾"	1¾"	4.2 lbs.
TBF157A47	1" dia.	9"	3½"	2½"	2¾"	1¾"	4.3 lbs.
TBF15747	1" dia.	10"	3½"	2½"	2¾"	1¾"	4.3 lbs.
TBF15847	1" dia.	12"	3½"	2½"	2¾"	1¾"	4.4 lbs.
TBF15947	1" dia.	18"	3½"	2½"	2¾"	1¾"	4.9 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Straight Single Bar Set with Santoprene Grip No. 19049

- Material:** Aluminum
- Finishes:** Available in US28, 313, 314, 315, 10BE, BSP (Black Suede), WSP (White Suede), stock powder coat finishes (see page 9)
- Features:** Santoprene™ durable, weather resistant grip - available in black (standard), red, and brown
- Mounting:**

Door	Pull Free End	Push Free End	Common End	Description	Mounting Spec. No.
Metal & wood	1	1	5	Back to back & thru bolt	T3**
Metal & wood	6	6	5	Back to back & concealed	T4
Wood	8	8	5	Back to back & concealed	T5
Metal & wood	12	12	5	Back to back & decorative bolt	T1
Glass	15	15	13	Back to back & thru bolt	T2

\*\*T3 is the standard mounting method for Metal and Wood Doors  
(See mounting selections at rockwoodmfg.com)

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (i.e., 19049 T3, wood door, 33" CTC, US28)

**Options:** Base plates available — use BP prefix (BP19049) when ordering  
Advise if door thickness is other than 1<sup>3</sup>/<sub>4</sub>"

No.	Material Size	Pull CTC	Pull Projection	Pull Clearance	Push CTC	Push Projection	Push Clearance	Weight
19049	1" dia.	12"	3 <sup>1</sup> / <sub>2</sub> "	2"	36"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	11.7 lbs.



## Offset Single Bar Set with Santoprene Grip No. BF19549

- Material:** Aluminum
- Finishes:** Available in US28, 313, 314, 315, 10BE, BSP (Black Suede), WSP (White Suede), stock powder coat finishes (see page 9)
- Features:** Santoprene™ durable, weather resistant grip - available in black (standard), red, and brown
- Mounting:**

Door	Pull Free End	Push Free End	Common End	Description	Mounting Spec. No.
Metal & wood	1	1	5	Back to back & thru bolt	T3**
Metal & wood	17	17	16	Back to back & concealed	T4
Wood	8	8	5	Back to back & concealed	T5
Metal & wood	12	12	5	Back to back & decorative bolt	T1
Glass	15	15	13	Back to back & thru bolt	T2

\*\*T3 is the standard mounting method for Metal and Wood Doors  
(See mounting selections at rockwoodmfg.com)

**Ordering:** Specify product number, mounting, door type, push bar CTC, and finish (i.e., BF19549 T3, wood door, 33" CTC, US28)

**Options:** Base plates available — use BP prefix (BPBF19049) when ordering  
Advise if door thickness is other than 1<sup>3</sup>/<sub>4</sub>"

No.	Material Size	Pull CTC	Pull Projection	Pull Clearance	Push CTC	Push Projection	Push Clearance	Weight
BF19549	1" dia.	18"	3 <sup>1</sup> / <sub>2</sub> "	2 <sup>1</sup> / <sub>2</sub> "	36"	2 <sup>3</sup> / <sub>4</sub> "	1 <sup>3</sup> / <sub>4</sub> "	15.2 lbs.

# Notes

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

# Location Standards

## Positioning Applications:

- Door pulls to plates
- Cutouts on plates
- Engraving on plates
- Cutout and engraving on plates

## Sizing:

- 1 1/4" standard cylinder hole cutout size
- 3/8" diameter standard turn knob hole
- Other cutout sizes and styles are readily available

## Engraving:

- 1" high condensed block letters with black enamel fill
- Other letter sizes and styles are readily available


*NOTE: Be sure the pull you choose will fit on the plate, allowing for cutouts and/or engraving*

# ADA Accessibility Guidelines for Buildings and Facilities (ADAAG)


As amended through 2004

**4.13.9 Door Hardware.** Handles, pulls, latches, locks, and other operating devices on accessible doors shall have a shape that is easy to grasp with one hand and does not require tight grasping, tight pinching, or twisting of the wrist to operate. Lever-operated mechanisms, push-type mechanisms, and U-shaped handles are acceptable designs. When sliding doors are fully open, operating hardware shall be exposed and usable from both sides. Hardware required for accessible door passage shall be mounted no higher than 48" (1220 mm) above finished floor.


## Pull Positioning on Plates 4" or Less in Width



## Pull Positioning on Plates Wider than 4" (Handing Required)



## Recommended Locations on Door



800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world

## Push Plates – .050" Thick

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, and US32D316 (see page 9)

**Fastener:** #6 x 5/8" OH SMS

**Features:** Four beveled edges

**Ordering:** Specify plate number followed by size designation and finish (70B US32D) or for non-standard size 70. Specify width x height and finish. Specify any additional options

- Options:**
- Custom sizes available upon request
  - TEK – self-drilling screws
  - TORX – security Torx screws
  - SA – self-adhesive mounting: 1/16" double face foam tape (no screw holes on plate)
  - Engraving on plates 4" wide or wider. Specify copy. See page B1 for standard engraving locations
  - Cylinder cutouts (CFC) and turn knob cutouts (CFTT). See page B1 for standard locations and sizes
  - Heavy bevel available on 70A to 70G, specify HVBEV
  - Optional UL listed for 3 hours for use on hollow-metal, steel-covered Composite fire doors (70C-RKW, 70E, 70F, 70G only)\*
  - Optional UL listed for 90 minutes for use on plastic-covered Composite, wood-covered Composite fire doors (70C-RKW, 70E, 70F, 70G only)\*



### No. 70

No.	Standard Size	Weight
70A	3" x 12"	0.7 lbs.
70B	3 1/2" x 15"	0.9 lbs.
70C-RKW*	4" x 16"	1.0 lbs.
70E*	6" x 16"	1.5 lbs.
70F*	8" x 16"	2.0 lbs.
70G*	4" x 20"	1.3 lbs.



### No. 70RC

No.	Standard Size	Weight
70RCA	3" x 12"	0.7 lbs.
70RCB	3 1/2" x 15"	0.9 lbs.
70RCC	4" x 16"	1.0 lbs.
70RCE	6" x 16"	1.5 lbs.
70RCF	8" x 16"	2.0 lbs.
70RCG	4" x 20"	1.3 lbs.



### No. 70RE

No.	Standard Size	Weight
70REA	3" x 12"	0.7 lbs.
70REB	3 1/2" x 15"	0.9 lbs.
70REC	4" x 16"	1.0 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

## Push Plates – .062" Thick

**Material:** Stainless steel

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** #6 x 5/8" OH SMS

**Features:** Four beveled edges

**Ordering:** Specify plate number followed by size designation and finish (71B US32D) or for non-standard size 71. Specify width x height and finish. Specify any additional options

- Options:**
- Custom sizes available upon request
  - TEK – self-drilling screws
  - TORX – security Torx screws
  - SA – self-adhesive mounting: .008" double face tape (no screw holes on plate)
  - Engraving on plates 4" wide or wider. Specify copy. See page B1 for standard engraving locations
  - Cylinder cutouts (CFC) and turn knob cutouts (CFTT). See page B1 for standard locations and sizes



### No. 71

No.	Standard Size	Weight
71A	3" x 12"	0.9 lbs.
71B	3½" x 15"	1.1 lbs.
71C	4" x 16"	1.2 lbs.
71E	6" x 16"	1.8 lbs.
71F	8" x 16"	2.4 lbs.
71G	4" x 20"	1.5 lbs.



### No. 71RC

No.	Standard Size	Weight
71RCA	3" x 12"	0.9 lbs.
71RCB	3½" x 15"	1.1 lbs.
71RCC	4" x 16"	1.2 lbs.
71RCE	6" x 16"	1.8 lbs.
71RCF	8" x 16"	2.4 lbs.
71RCG	4" x 20"	1.5 lbs.



### No. 71RE

No.	Standard Size	Weight
71REA	3" x 12"	0.9 lbs.
71REB	3½" x 15"	1.1 lbs.
71REC	4" x 16"	1.2 lbs.

## Push Plates – .125" Thick

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, and US32D316 (see page 9)

**Fastener:** #6 x 5/8" OH SMS

**Features:** Four beveled edges

**Ordering:** Specify plate number followed by size designation and finish (73B US32D) or for non-standard size 73. Specify width x height and finish. Specify any additional options

- Options:**
- Custom sizes available upon request
  - TEK – self-drilling screws
  - TORX – security Torx screws
  - SA – self-adhesive mounting: .008" double face tape (no screw holes on plate)
  - Engraving on plates 4" wide or wider. Specify copy. See page B1 for standard engraving locations
  - Cylinder cutouts (CFC) and turn knob cutouts (CFTT). See page B1 for standard locations and sizes



### No. 73

No.	Standard Size	Weight
73A	3" x 12"	1.7 lbs.
73B	3½" x 15"	2.1 lbs.
73C	4" x 16"	2.5 lbs.
73E	6" x 16"	3.8 lbs.
73F	8" x 16"	5.0 lbs.
73G	4" x 20"	3.2 lbs.



### No. 73RC

No.	Standard Size	Weight
73RCA	3" x 12"	1.7 lbs.
73RCB	3½" x 15"	2.1 lbs.
73RCC	4" x 16"	2.5 lbs.
73RCE	6" x 16"	3.8 lbs.
73RCF	8" x 16"	5.0 lbs.
73RCG	4" x 20"	3.2 lbs.



### No. 73RE

No.	Standard Size	Weight
73REA	3" x 12"	1.7 lbs.
73REB	3½" x 15"	2.1 lbs.
73REC	4" x 16"	2.5 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

## Push Plates – .125" Thick No. 75

**Material:** Plastic laminate, clear plastic, Kydex®

**Colors:** Black, brown, gray, beige, white, and clear

**Fastener:** #6 x 5/8 OH SMS

**Features:** Four beveled edges


**Ordering:** Specify color and any other options

- Options:**
- Custom sizes available upon request
  - SA – Self-adhesive mounting: 1/16" double face foam tape (no screw holes on plate). Not available on clear plastic
  - Engraving on plates 4" wide or wider. Specify copy. See page B1 for standard engraving locations
  - Cylinder cutouts (CFC) and turn knob cutouts (CFTT). See page B1 for standard locations and sizes



No.	Standard Size	Weight
75A	3" x 12"	0.3 lbs.
75B	3½" x 15"	0.4 lbs.
75C	4" x 16"	0.5 lbs.
75E	6" x 16"	0.7 lbs.
75F	8" x 16"	0.9 lbs.
75G	4" x 20"	0.6 lbs.

® Kydex is a registered trademark of Kleerdex Company.



No. 76

No. 77

## Decorative Push Plates – .050" Thick No. 76, 77

**Material:** Brass, bronze


**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** #6 x <sup>5</sup>/<sub>8</sub>" OH SMS

**Ordering:** Specify finish

**Options:** These plates look great when combined with the No. 147 or 148 pulls as shown on page B22

No.	Standard Size	Weight
76B	3½" x 15"	0.9 lbs.
76C	4" x 16"	1.0 lbs.
77B	3½" x 15"	0.9 lbs.
77C	4" x 16"	1.0 lbs.



## Push Plates – .050" Thick No. 80, 81, 82

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, and US32D316 (see page 9)


**Fastener:** #6 x <sup>5</sup>/<sub>8</sub>" OH SMS

**Ordering:** Specify finish

**Options:**

- Plates may be mated with most any door pull of your choice
- Custom sizes available upon request

No.	Standard Size	Weight
80	6" x 12"	1.4 lbs.
81	7½" x 15"	1.6 lbs.
82	8" x 16"	1.8 lbs.



## Push Plate – .050" Thick No. 84

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, and US32D316 (see page 9)

**Fastener:** #6 x <sup>5</sup>/<sub>8</sub>" OH SMS

**Ordering:** Specify finish and handing (right handing shown)

**Options:**

- Variations of design can be created to fit your requests
- Plate may be mated with most any door pull of your choice

No.	Standard Size	Weight
84	10" x 20"	2.1 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Push Plates – .050" Thick No. 85, 86

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, and US32DMS (see page 9)
- Fastener:** #6 x <sup>5</sup>/<sub>8</sub>" OH SMS
- Features:** Cold forged to <sup>7</sup>/<sub>32</sub>" thick
- Ordering:** Specify finish
- Options:** Plates may be mated with most any door pull of your choice

No.	Standard Size	Weight
85	3½" x 15"	0.9 lbs.
86	4" x 16"	1.0 lbs.



## Push Plate – .125" Thick No. 87

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** #6 x <sup>5</sup>/<sub>8</sub>" OH SMS
- Ordering:** Specify finish
- Options:**
- Variations of design can be created to fit your requests
  - Plate may be mated with most any door pull of your choice


No.	Standard Size	Weight
87	2 <sup>5</sup> / <sub>8</sub> " x 16"	2.0 lbs.



## Heavy Duty Security Flush Pull No. D89

- Material:** Cast brass
- Finishes:** Available in US4, 10BE and US26D (see page 9)
- Fastener:** 1/4 - 20 x 1/2" OH Security Torx MS  
#14 x 1" OH Security Torx SMS

No.	Size	Grip Opening	Depth	Weight
D89	4" x 5"	1 3/4" x 3 1/2"	7/8"	1.3 lbs.



## Cylinder Pulls No. 90, 90B

- Material:** .125" aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, and **US32DMS** (see page 9)
- Fastener:** 90: SA - Self Adhesive Mounting, 90B: #8 x 3/4" OH SMS
- Options:** No cylinder hole - screw mounted, order No. 90B

No.	Size	Opening	Projection	Weight
90	2" x 3 3/4"	1 1/4" dia.	1"	0.3 lbs.
90B	2" x 3 3/4"	—	1"	0.3 lbs.



## Combination Push Pull Plates No. 91-RKW, 92-RKW, 93-RKW

- Material:** .125" aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, and **US32DMS** (see page 9)
- Fastener:** #8 x 7/8" SMS
- Options:**
- TORX - security Torx screws
  - Cylinder cutouts (CFC) and turn knob cutouts (CFTT). See page B1 for standard locations and sizes

No.	Size	Projection	Weight
91-RKW	3 1/2" x 15 3/4"	1"	1.9 lbs.
92-RKW	4" x 15 3/4"	1"	2.2 lbs.
93-RKW	8" x 15 3/4"	1"	4.4 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Flush Pulls No. 94, 94BTB

**Material:** .125" brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, and US32316 (see page 9)

*NOTE: Cups are painted black on all finishes except stainless steel.*

**Fastener:** No. 94: #8 x 3/4" SMS

No. 94BTB: #8 - 32 x 3/4" OH MS with sleeves Type 10

**Options:** TORX – security Torx screws

No.	Size	Grip Opening	Depth	Weight
94	3 1/2" x 5"	1 3/4" x 3 1/8"	7/8"	0.6 lbs.
94BTB (pair)	3 1/2" x 5"	1 3/4" x 3 1/8"	1 3/4"	1.2 lbs.



## Flush Pull No. 94C

**Material:** .125" brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, and US32316 (see page 9)


*NOTE: Cups are painted black on all finishes except stainless steel*

**Fastener:** #6 x 1" TH SMS.

**Features:**

- Fasteners concealed in cup.
- Accepted by the New York State Office of Mental Health (OMH) for use in high risk areas

No.	Size	Grip Opening	Depth	Weight
94C	3 1/2" x 5"	1 3/4" x 3 1/8"	7/8"	0.6 lbs.



## Dead Lock Flush Pulls No. 94DLL, 94DLS

**Material:** .125" brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, and US32316 (see page 9)

*NOTE: Cups are painted black on all finishes except stainless steel*

**Fastener:** #8 x 3/4" OH SMS.

**Features:**

- Used with dead bolt lock. 1 1/4" cylinder hole is standard
- Vandal resistant.
- Use where projecting trim is an operational problem or an aesthetic objection
- Ideal for use on "exit only" doors where occasional entrance is required (warehouse exits), night latch function exit device openings (classroom exit only doors), mechanical closet doors and anywhere dead locking is approved

**Options:**

- TORX – security Torx screws
- Custom sizes

No.	Size	Grip Opening	Depth	Weight
94DLL	6 1/8" x 8"	1 3/4" x 6 1/8"	7/8"	1.0 lbs.
94DLS	6 1/8" x 5"	1 3/4" x 3 1/8"	7/8"	0.8 lbs.



## Flush Pull No. 94L

- Material:** .125" brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, and US32316 (see page 9)  
*NOTE: Cups are painted black on all finishes except stainless steel*
- Fastener:** 1/4 - 20 x 1 1/2" thru bolt & finish washer (standard 1 3/4" door)
- Features:** Includes lugs for thru bolt. No fasteners on pull side
- Options:**
- TORX – security Torx screws
  - Advise if door thickness other than 1 3/4"


No.	Size	Grip Opening	Depth	Weight
94L	3 1/2" x 5"	1 3/4" x 3 1/8"	7/8"	0.6 lbs.



## Flush Pull No. 94P

- Material:** .125" brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, and US32316 (see page 9)  
*NOTE: Cups are painted black on all finishes except stainless steel*
- Fastener:** 1/4 - 20 x 1 1/2" MS
- Features:** Usually used with the 94L as a set (see below)
- Options:** TORX – security Torx screws

No.	Size	Grip Opening	Depth	Weight
94P	3 1/2" x 5"	1 3/4" x 3 1/8"	7/8"	0.6 lbs.



## Flush Pull Set No. 94P x 94L

- Material:** .125" brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, and US32316 (see page 9)  
*NOTE: Cups are painted black on all finishes except stainless steel*
- Fastener:** 1/4 - 20 x 1 1/2" thru bolt (standard 1 3/4" door)
- Options:**
- TORX – security Torx screws
  - Advise if door thickness other than 1 3/4"

No.	Size	Weight
94P x 94L	Set consists of 1 94L and 1 94P	1.3 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



95A



95B

## Flush Pull No. 95A, 95B

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** #6 x 5/8" SMS (95A), #8 x 7/8" SMS (95B)

**Features:** Fasteners concealed in cup

No.	Size	Grip Opening	Depth	Weight
95A	2 <sup>3</sup> / <sub>16</sub> " x 3 <sup>1</sup> / <sub>4</sub> "	7/8" x 2 <sup>7</sup> / <sub>16</sub> "	3/4"	0.6 lbs.
95B	2 <sup>11</sup> / <sub>16</sub> " x 4 <sup>3</sup> / <sub>16</sub> "	1 <sup>7</sup> / <sub>16</sub> " x 3 <sup>1</sup> / <sub>2</sub> "	3/4"	0.8 lbs.



## Flush Pull No. 95R

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** #8 x 7/8" SMS

**Features:** Fasteners concealed in cup

No.	Size	Grip Opening	Depth	Weight
95R	3 <sup>1</sup> / <sub>2</sub> " dia.	2 <sup>3</sup> / <sub>4</sub> " x 1 <sup>11</sup> / <sub>16</sub> "	7/8"	0.6 lbs.



## Flush Pull No. 96

**Material:** .125" aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** #8 x 3/4" FH SMS

**Options:**

- TORX – security Torx screws
- Special sizes
- Cylinder cutouts (CFC) and turn knob cutouts (CTFF). See page B1 for standard locations and sizes

No.	Size	Grip Opening	Depth	Weight
96	4" x 16"	1 <sup>3</sup> / <sub>4</sub> " x 3 <sup>1</sup> / <sub>8</sub> "	7/8"	2.2 lbs.



No. BF97



No. BF97L

## Barrier Free Flush Pulls No. BF97, BF97L

**Material:** .125" brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, and US32DMS (see page 9).

**Fastener:** No. BF97: #8 x 3/4" FH SMS

No. BF97L: #8 - 32 stud welded lugs and #8 - 32 FH MS

**Options:** TORX – security Torx screws

**Features:** ADA flush pull

No.	Size	Grip Opening	Depth	Weight
BF97	5" x 5"	2 1/2" x 3 1/2"	7/8"	1.0 lbs.
BF97L	5" x 5"	2 1/2" x 3 1/2"	7/8"	1.0 lbs.



## Flat Pocket Pull No. 98

**Material:** Stainless Steel

**Finishes:** US32, US32D, US32MS, US32DMS, 10BE, 314E, 315E, BPC, WPC, RPC, FBPC, BSP, WSP

*Mounting Note: 1HD, 12HD*

**Fastener:** 5/16-18 Flat Head Machine Screws

**Features:**

- Simple, sleek design
- Durable and easy to clean

No.	Grip Width	Grip Height	Proj.	Clearance	OA	Weight
98	1/2"	1/4"	1 1/4" (4" or 6" OA)	1" (4" or 6" OA)	4", 6", 12"	0.8 lbs. (4" OA)
			1 3/4" (12" OA)	1 1/2" (12" OA)		1.1 lbs. (6" OA)
						2.1 lbs. (12" OA)



## Radius Pocket Pull No. 99-RKW

**Material:** Stainless Steel

**Finishes:** US32, US32D, US32MS, US32DMS, 10BE, 314E, 315E, BPC, WPC, RPC, FBPC, BSP, WSP

*Mounting Note: 1HD, 12HD*

**Fastener:** 5/16-18 Flat Head Machine Screws

**Features:**

- Simple, sleek design
- Durable and easy to clean

No.	Grip Width	Grip Height	Proj.	Clearance	OA	Weight
99-RKW	1/2"	3/16" (4" or 6" OA)	1 1/4" (4" or 6" OA)	7/8" (4" or 6" OA)	4", 6", 12"	0.8 lbs. (4" OA)
		1/4" (12" OA)	1 3/4" (12" OA)	1 1/4" (12" OA)		1.1 lbs. (6" OA)
						2.1 lbs. (12" OA)

**ROCKWOOD**

**ASSA ABLOY**


Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.


## Thru Bolt

Wood or Metal Door – Type 1




Type	Bolt Size	Drill Size	
		Wood	Metal
1	1/4 - 20	9/32	9/32
1HD	5/16 - 18	11/32	11/32
1XHD	3/8 - 16	13/32	13/32

Wood or Metal Door – Type 12



Type	Bolt Size	Drill Size	
		Wood	Metal
12	1/4 - 20	9/32	9/32
12HD	5/16 - 18	11/32	11/32
12XHD	3/8 - 16	13/32	13/32

Glass Door – Type 15




Type	Bolt Size	Drill Size
		Glass
15	1/4 - 20	5/8
15HD	5/16 - 18	5/8
15XHD	3/8 - 16	5/8

*NOTE: Heavy Duty (HD/XHD) mounting features hex drive for positive tightening and large overall size for superior strength. Recommended for high frequency and rough service openings.*


## Back to Back

Wood or Metal Door – Type 5




Type	Bolt Size	Drill Size	
		Wood	Metal
5	1/4 - 20	9/32	9/32
5HD	5/16 - 18	11/32	11/32

Any Door Type – Type 9



Type	Bolt Size	Drill Size
		Metal
9	1/4 - 20	N/A


Glass Door – Type 13



Type	Bolt Size	Drill Size
		Glass
13	1/4 - 20	5/8
13HD	5/16 - 18	5/8


## Surface Concealed

Metal Door – Type 6




Type	Bolt Size	Drill Size
		Metal
6	1/4 - 20	1/4 - 20 tap
6HD	5/16 - 18	5/16 - 18 tap

Metal Door – Type 6R



Type	Bolt Size	Drill Size
		Metal
6R	1/4 - 20	N/A


Wood Door – Type 8



Type	Bolt Size	Drill Size
		Wood
8	1/4 - 20	23/64 x 9/16 dp
8HD	5/16 - 18	7/16 x 9/16 dp

## Flush Pull Mounting

Wood or Metal Door – Type 10




Type	Bolt Size	Drill Size	
		Wood	Metal
10	8 - 32	9/32	9/32

*Type 10 Mounting applies to the 94 Series Flush Pulls*

## Wire or Small PostMount Pull Mounting


Wood or Metal Door – Type 5S



Type	Bolt Size	Drill Size	
		Wood	Metal
5S	8 - 32	13/64	13/64

*NOTE: This mounting should only be used on pulls with mounting points that are 1/2 inch in diameter.*

Surface Concealed Wood or Metal Door – Type 6S



Type	Bolt Size	Drill Size
		Wood Metal
6S	8 - 32	8 - 32 Tap



## Door Pulls No. 102-RKW, 105, 106-RKW, 107, 108, 109

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

**Fastener:** 1/4-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

- Options:**
- Back to back mounting in pairs – use BTB suffix and mounting type number (107BTB5)
  - Concealed mounting single pulls – use C suffix and mounting type number (107C6)
  - Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)
  - 2 1/2" Barrier Free clearance – use BF prefix (BF107)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Weight
102-RKW	5/8" dia.	5 1/2"	6 1/8"	5/8"	2 1/8"	1 1/2"	0.6 lbs.
105	3/4" dia.	5 1/2"	6 1/4"	3/4"	2 5/8"	1 7/8"	1.2 lbs.
106-RKW	3/4" dia.	6"	6 3/4"	3/4"	2 5/8"	1 7/8"	1.3 lbs.
107	3/4" dia.	8"	8 3/4"	3/4"	2 5/8"	1 7/8"	1.6 lbs.
108	3/4" dia.	10"	10 3/4"	3/4"	2 5/8"	1 7/8"	1.8 lbs.
109	3/4" dia.	12"	12 3/4"	3/4"	2 5/8"	1 7/8"	2.1 lbs.

## Door Pulls No. 110-RKW, 111A, 111, 112, 118



**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

- Options:**
- Back to back mounting in pairs – use BTB suffix and mounting type number (112BTB5)
  - Concealed mounting single pulls – use C suffix and mounting type number (112C6)
  - Advise if door thickness is other than 1 3/4"
  - Heavy duty versions of most fastening types available – use suffix HD to fastening type number (112BTB5HD)
  - See page B13 for mounting selection (standard duty 1/4 - 20)
  - 2 1/2" Barrier Free clearance – use BF prefix (BF110)

No.	Material Size	CTC	Overall	Base	Pull Projection (Stainless)	Pull Projection (Brass, Bronze)	Clearance (Stainless)	Clearance (Brass Bronze)	Weight
110-RKW	1" dia.	8"	9"	1"	3 1/2"	3"	2 1/2"	2"	3.0 lbs.
111A	1" dia.	9"	10"	1"	3 1/2"	3"	2 1/2"	2"	3.3 lbs.
111	1" dia.	10"	11"	1"	3 1/2"	3"	2 1/2"	2"	3.5 lbs.
112	1" dia.	12"	13"	1"	3 1/2"	3"	2 1/2"	2"	4.0 lbs.
118	1" dia.	18"	19"	1"	3 1/2"	3"	2 1/2"	2"	5.4 lbs.

*Pull projection is 3 1/2" for stainless steel and 3" for aluminum, brass and bronze.*

**ROCKWOOD**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

## T Series 1" Tubular Pulls

Rockwood T Series 1" diameter straight tubular pulls are made from sturdy .065" thick wall tubing. Solid brass or stainless steel inserts are brazed into the ends to provide a solid area for our guaranteed mounting systems.

Benefits of specifying the T Series push and pulls include:

- Tubular pulls weigh 25% less than their solid counterparts; this 75% weight reduction greatly reduces the environmental impact of harvesting material for their manufacture – a LEED certified building goal
- The lighter weight minimizes the risk of damage in shipping and handling
- The cost of most tubular pulls represents a significant savings over the equivalent solid model

Considering all the benefits, the T Series pulls offer an improved value without any quality sacrifice.

T Series is also available in offset pulls (see page B29) and in both Series 47 push bars and push & pull bar sets (see pages A19–A21).



### Tubular Door Pulls No. T110, T111A, T111, T112, T118

**Material:** Brass, bronze, stainless steel


**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

- Options:**
- Back to back mounting in pairs – use BTB suffix and mounting type number (T112BTB5)
  - Concealed mounting single pulls – use C suffix and mounting type number (T112C6)
  - Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)
  - 2 1/2" Barrier Free clearance – use BF prefix (TBF110)

No.	Material Size	CTC	Overall	Base	Pull Projection (Stainless)	Pull Projection (Brass, Bronze)	Clearance (Stainless)	Clearance (Brass Bronze)	Weight
T110	1" dia.	8"	9"	1"	3 1/2"	3"	2 1/2"	2"	1.0 lbs.
T111A	1" dia.	9"	10"	1"	3 1/2"	3"	2 1/2"	2"	1.1 lbs.
T111	1" dia.	10"	11"	1"	3 1/2"	3"	2 1/2"	2"	1.1 lbs.
T112	1" dia.	12"	13"	1"	3 1/2"	3"	2 1/2"	2"	1.2 lbs.
T118	1" dia.	18"	19"	1"	3 1/2"	3"	2 1/2"	2"	1.7 lbs.

Pull projection is 3 1/2" for stainless steel and 3" for aluminum, brass and bronze.



## Concealed Mount Pull Plate Sets

### No. 107 x 73B/73BL, 110 x 73C/73CL, 111 x 73C/73CL

**Material:** Stainless steel

**Finishes:** US32D


**Fastener:** Type 9. Stud welded lugs on the back of the push plate are permanently attached to the 1/8" thick push plate. Cone head MS attached to selected door pull

**Features:**

- This set has no perimeter screw holes in either plate
- Concealed mounting system. Any of the rod type door pulls from No. 105 to No. 118 are appropriate for this application

**Options:**

- Engraving on plates 4" wide or wider. Specify copy. See page B1 for standard engraving locations
- Cylinder cutouts (CFC) and turn knob cutouts (CFTT). See page B1 for standard locations and sizes
- \*Other overall sizes available upon request



No.	Pull	Pull Size	Pull CTC	Pull Plate	Push Plate	Overall*	Weight
107 x 73B/73BL	107	3/4" dia.	8"	73B	73BL	3 1/2" x 15"	5.8 lbs.
110 x 73C/73CL	110	1" dia.	8"	73C	73CL	4" x 16"	8.0 lbs.
111 x 73C/73CL	111	1" dia.	10"	73C	73CL	4" x 16"	8.5 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Door Pulls with Base Plates No. Y102, Y105, Y106, Y107, Y108, Y109

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)
- Fastener:** 1/4 - 20 x 2 1/2" thru bolt & finish washer (standard 1 3/4" door)
- Features:** 1/8" base plates improve stability on the door. Recommended for glass and wood doors
- Options:**
- Back to back mounting in pairs – use BTB suffix and mounting type number (Y107BTB5)
  - Concealed mounting single pulls – use C suffix and mounting type number (Y107C6)
  - Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Weight
Y102	5/8" dia.	5 1/2"	6 1/8"	7/8"	2 1/8"	1 1/2"	0.6 lbs.
Y105	3/4" dia.	5 1/2"	6 7/16"	1 1/16"	2 3/8"	1 5/8"	1.2 lbs.
Y106	3/4" dia.	6"	7 1/16"	1 1/16"	2 3/8"	1 5/8"	1.3 lbs.
Y107	3/4" dia.	8"	9 1/16"	1 1/16"	2 3/8"	1 5/8"	1.6 lbs.
Y108	3/4" dia.	10"	11 1/16"	1 1/16"	2 3/8"	1 5/8"	1.8 lbs.
Y109	3/4" dia.	12"	13 1/16"	1 1/16"	2 3/8"	1 5/8"	2.1 lbs.



## Door Pulls with Base Plates No. Y110, Y111A, Y111, Y112, Y118

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)
- Fastener:** 1/4 - 20 x 2 1/2" thru bolt & finish washer (standard 1 3/4" door)
- Features:** 1/8" base plates improve stability on the door. Recommended for glass and wood doors.
- Options:**
- Back to back mounting in pairs – use BTB suffix and mounting type number (Y112BTB5)
  - Concealed mounting single pulls – use C suffix and mounting type number (Y112C6)
  - Advise if door thickness is other than 1 3/4"
  - Heavy duty versions of most fastening types available – use suffix HD to fastening type number (Y112BTB5HD)
  - See page B13 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Weight
Y110	1" dia.	8"	9 1/4"	1 1/4"	3 1/8"	2 1/8"	3.1 lbs.
Y111A	1" dia.	9"	10 1/4"	1 1/4"	3 1/8"	2 1/8"	3.4 lbs.
Y111	1" dia.	10"	11 1/4"	1 1/4"	3 1/8"	2 1/8"	3.6 lbs.
Y112	1" dia.	12"	13 1/4"	1 1/4"	3 1/8"	2 1/8"	4.1 lbs.
Y118	1" dia.	18"	19 1/4"	1 1/4"	3 1/8"	2 1/8"	5.5 lbs.



## Door Pull No. 120

- Material:** Aluminum, brass, stainless steel
- Finishes:** Available in most standard architectural finishes (see page 9)
- Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Engraving available vertically
  - Back to back mounting
  - Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Weight
120	3/8" x 1 1/4"	8"	14"	1" dia.	1 7/8"	1 3/8"	2.6 lbs.



## Door Pull No. 121

- Material:** Aluminum, brass, stainless steel
- Finishes:** Available in most standard architectural finishes (see page 9)
- Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Engraving available vertically
  - Back to back mounting
  - Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Weight
121	3/8" x 1 1/4"	8"	14"	1" dia.	1 7/8"	1 3/8"	2.6 lbs.



## Door Pulls No. 122-RKW, 123

- Material:** Aluminum, brass, stainless steel
- Finishes:** Available in most standard architectural finishes (see page 9)
- Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Projection	Clearance	Weight
122-RKW	3/8" x 1 1/4"	6"	6 3/8"	2"	1 5/8"	1.1 lbs.
123	3/8" x 1 1/4"	8"	8 3/8"	2"	1 5/8"	1.4 lbs.

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Door Pulls No. 125-RKW, 126-RKW

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in most standard architectural finishes (see page 9)
- Fastener:** 1/4-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1 1/4-20)

No.	Material Size	CTC	Overall	Projection	Clearance	Weight
125-RKW	1" half round	6"	6 1/2"	2"	1 1/2"	1.1 lbs.
126-RKW	1" half round	8"	8 1/2"	2"	1 1/2"	1.4 lbs.



## Cast Door Pull No. 130-RKW

- Material:** Cast aluminum, brass, stainless steel
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** 1/4-20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4-20)

No.	CTC	Overall	Base	Projection	Clearance	Weight
130-RKW	5 1/2"	7 1/2"	2"	2 1/4"	1 1/2"	1.1 lbs.



## Cast Door Pull No. 131-RKW

- Material:** Cast aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** #8 x 3/4" OH SMS

No.	CTC	Overall	Base	Projection	Clearance	Weight
131-RKW	—	7 1/2"	2"	2 1/4"	1 1/2"	1.1 lbs.



## Cast Door Pull No. 132-RKW

- Material:** Cast aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, and US32DMS (see page 9)
- Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)

No.	CTC	Overall	Base	Projection	Clearance	Weight
132-RKW	5 1/2"	6 3/8"	7/8"	1 7/8"	1 3/8"	0.8 lbs.



## Security Loop Door Pull No. D133-RKW

- Material:** Brass, stainless steel
- Finishes:** US4, 10BE, US32D, and US32DMS
- Fastener:** 2 ea. 3/8 - 16 x 5/8" OH Security Torx MS

No.	CTC	Overall	Base	Projection	Clearance	Weight
D133-RKW	7 3/4"	8 3/4"	1 3/4" x 1 7/8"	2 1/4"	1 11/16"	1.1 lbs.



## Cast Door Pull No. 134-RKW

- Material:** Cast brass
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)

No.	CTC	Overall	Base	Projection	Clearance	Weight
134-RKW	7 1/2"	8 1/2"	1"	1 7/8"	1 3/8"	1.0 lbs.

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Cast Door Pull No. 137

**Material:** Cast brass, stainless steel

**Finishes:** Available in standard architectural finishes, and US32DMS (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Advise if door thickness is other than 1 3/4"
- See page B13 for mounting selection (standard duty 1/4 - 20)

No.	CTC	Overall	Base	Projection	Clearance	Weight
137	5 1/2"	6"	5/8" x 1 1/4"	2"	1 1/2"	0.9 lbs.



## Cast Door Pull No. 137L

**Material:** Cast brass, bronze

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Advise if door thickness is other than 1 3/4"
- See page B13 for mounting selection (standard duty 1/4 - 20)

No.	CTC	Overall	Base	Projection	Clearance	Weight
137L	10"	10 3/4"	5/8" x 1 1/4"	2 1/2"	1 3/4"	1.1 lbs.



## Cast Door Pull No. 138

**Material:** Cast aluminum, brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Advise if door thickness is other than 1 3/4"
- See page B13 for mounting selection (standard duty 1/4 - 20)

No.	CTC	Overall	Base	Projection	Clearance	Weight
138	7 1/2"	9 1/2"	2"	2"	1 1/2"	1.5 lbs.



## Cast Door Pull No. 139

**Material:** Cast aluminum, brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** #8 x 3/4" OH SMS

No.	CTC	Overall	Base	Projection	Clearance	Weight
139	—	9 1/2"	2"	2"	1 1/2"	1.5 lbs.



## Door Pulls No. 147, 147L

**Material:** Cast brass.

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:** Elliptical base plates

- Options:**
- Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)

No.	CTC	Overall	Base	Projection	Clearance	Weight
147	6"	7 1/2"	1 1/8" dia.	2 1/2"	1 3/4"	1.2 lbs.
147L	12"	13 3/4"	1 7/8" dia.	2 5/8"	1 7/8"	1.7 lbs.



## Door Pull No. 148

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

- Options:**
- Type 5 back to back mounting.
  - Advise if door thickness is other than 1 3/4".
  - See page B13 for mounting selection (standard duty 1/4 - 20).

No.	CTC	Overall	Base	Projection	Clearance	Weight
148	8"	8 7/8"	1 5/16"	2 1/4"	1 1/4"	1.5 lbs.



## Door Pull No. 149

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 3/4" thru bolt & finish washer (standard 1 3/4" door)

- Options:**
- Type 5 back to back mounting
  - Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)

No.	CTC	Overall	Base	Projection	Clearance	Weight
149	8"	9 1/4"	1 3/4"	2 5/8"	1 5/8"	1.8 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Pull Plates No. 102 x 70, 105 x 70, 106 x 70, 107 x 70

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Stocked in standard architectural finishes but available in any finish, US32DMS and US32D316 (see page 9)

**Fastener:** #6 x 5/8" OH SMS; 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Barrier Free available in 2 1/2" clearance — use BF prefix when ordering (BF102 x 70C)
- Advise if door thickness is other than 1 3/4"
- See page B13 for mounting selection (standard duty 1/4 - 20)

No.	Pull	CTC	Plate	Size	Weight
102 x 70B	5/8" dia.	5 1/2"	70	3 1/2" x 15"	1.8 lbs.
102 x 70C	5/8" dia.	5 1/2"	70	4" x 16"	1.9 lbs.
105 x 70B	3/4" dia.	5 1/2"	70	3 1/2" x 15"	2.1 lbs.
105 x 70C	3/4" dia.	5 1/2"	70	4" x 16"	2.2 lbs.
106 x 70B	3/4" dia.	6"	70	3 1/2" x 15"	2.2 lbs.
106 x 70C	3/4" dia.	6"	70	4" x 16"	2.3 lbs.
107 x 70B	3/4" dia.	8"	70	3 1/2" x 15"	2.4 lbs.
107 x 70C	3/4" dia.	8"	70	4" x 16"	2.5 lbs.



## Pull Plates No. 110 x 70, 111 x 70

**Material:** Aluminum, brass, bronze, stainless steel


**Finishes:** Stocked in standard architectural finishes but available in any finish, US32DMS and US32D316 (see page 9)

**Fastener:** #6 x 5/8" OH SMS; 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Barrier Free available in 2 1/2" clearance — use BF prefix when ordering (BF110 x 70C)
- Advise if door thickness is other than 1 3/4"
- See page B13 for mounting selection (standard duty 1/4 - 20)
- Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight
110 x 70B	1" dia.	8"	70	3 1/2" x 15"	3.8 lbs.
110 x 70C	1" dia.	8"	70	4" x 16"	3.9 lbs.
111 x 70B	1" dia.	10"	70	3 1/2" x 15"	4.3 lbs.
111 x 70C	1" dia.	10"	70	4" x 16"	4.4 lbs.



## Pull Plates No. 122 x 70, 123 x 70

- Material:** Aluminum, brass, stainless steel
- Finishes:** Stocked in standard architectural finishes but available in most finishes (see page 9)
- Fastener:** #6 x 5/8" OH SMS; 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)
  - Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight
122 x 70B	3/8" x 1 1/4"	6"	70	3 1/2" x 15"	2.2 lbs.
122 x 70C	3/8" x 1 1/4"	6"	70	4" x 16"	2.3 lbs.
123 x 70B	3/8" x 1 1/4"	8"	70	3 1/2" x 15"	2.5 lbs.
123 x 70C	3/8" x 1 1/4"	8"	70	4" x 16"	2.6 lbs.



## Pull Plates No. 125 x 70, 126 x 70

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Stocked in standard architectural finishes but available in most finishes (see page 9)
- Fastener:** #6 x 5/8" OH SMS; 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4 - 20)
  - Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight
125 x 70B	1" half round	6"	70	3 1/2" x 15"	2.0 lbs.
125 x 70C	1" half round	6"	70	4" x 16"	2.1 lbs.
126 x 70B	1" half round	8"	70	3 1/2" x 15"	2.3 lbs.
126 x 70C	1" half round	8"	70	4" x 16"	2.4 lbs.


**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Pull Plates No. 132 x 70

**Material:** Aluminum, brass, bronze, stainless steel


**Finishes:** Stocked in standard architectural finishes but available in any finish, and US32DMS (see page 9)

**Fastener:** #6 x 5/8" OH SMS; 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Advise if door thickness is other than 1 3/4"
- See page B13 for mounting selection (standard duty 1/4 - 20)
- Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight
132 x 70B	Cast	5 1/2"	70	3 1/2" x 15"	1.7 lbs.
132 x 70C	Cast	5 1/2"	70	4" x 16"	1.8 lbs.



## Pull Plates No. 137 x 70

**Material:** Brass, stainless steel


**Finishes:** Stocked in standard architectural finishes but available in any finish (see page 9)

**Fastener:** #6 x 5/8" OH SMS; 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Advise if door thickness is other than 1 3/4"
- See page B13 for mounting selection (standard duty 1/4 - 20)
- Heavy bevel available, specify HVBEV

No.	Pull	CTC	Plate	Size	Weight
137 x 70B	Cast	5 1/2"	70	3 1/2" x 15"	1.7 lbs.
137 x 70C	Cast	5 1/2"	70	4" x 16"	1.8 lbs.



No. 147 x 76B

No. 147 x 77B

## Pull Plates No. 147 x 76, 147 x 77

**Material:** Cast brass.


**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** #6 x 5/8" OH SMS; 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Advise if door thickness is other than 1 3/4"
- See page B13 for mounting selection (standard duty 1/4 - 20)

No.	Pull	CTC	Plate	Size	Weight
147 x 76B	Cast	6"	76	3 1/2" x 15"	2.1 lbs.
147 x 76C	Cast	6"	76	4" x 16"	2.2 lbs.
147 x 77B	Cast	6"	77	3 1/2" x 15"	2.1 lbs.
147 x 77C	Cast	6"	77	4" x 16"	2.2 lbs.



No. 148 x 76B

No. 148 x 77B

## Pull Plates No. 148 x 76, 148 x 77

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** #6 x 5/8" OH SMS; 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Advise if door thickness is other than 1 3/4"
- See page B13 for mounting selection (standard duty 1/4 - 20)

No.	Pull	CTC	Plate	Size	Weight
148 x 76B	Cast	8"	76	3 1/2" x 15"	2.7 lbs.
148 x 76C	Cast	8"	76	4" x 16"	2.8 lbs.
148 x 77B	Cast	8"	77	3 1/2" x 15"	2.7 lbs.
148 x 77C	Cast	8"	77	4" x 16"	2.8 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world


800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

NOTE: Y base plates are recommended on wood or glass doors to make a stable and durable mounting.  
 NOTE: Heavy Duty (HD/XHD) mounting features hex drive for positive tightening and large overall size for superior strength. Recommended for high frequency and rough service openings.


## Thru Bolt

Wood or Metal Door - Type 1




Type	Bolt Size	Drill Size	
		Wood	Metal
1	1/4 - 20	9/32	9/32
1HD	5/16 - 18	11/32	11/32
1XHD	3/8 - 16	13/32	13/32

Wood or Metal Door - Type 12



Type	Bolt Size	Drill Size	
		Wood	Metal
12	1/4 - 20	9/32	9/32
12HD	5/16 - 18	11/32	11/32
12XHD	3/8 - 16	13/32	13/32


Glass Door - Type 15



Type	Bolt Size	Drill Size
		Glass
15	1/4 - 20	5/8
15HD	5/16 - 18	5/8
15XHD	3/8 - 16	5/8


## Back to Back

Wood or Metal Door - Type 16



Type	Bolt Size	Drill Size	
		Wood	Metal
16	1/4 - 20	9/32	9/32
16HD	5/16 - 18	11/32	11/32


Glass Door - Type 18



Type	Bolt Size	Drill Size
		Glass
18	1/4 - 20	5/8
18HD	5/16 - 18	5/8


## Concealed

Metal Door - Type 17



Type	Bolt Size	Drill Size
		Metal
17	1/4 - 20	1/4 - 20 tap
17HD	5/16 - 18	5/16 - 18 tap

Metal Door - Type 17R




Type	Bolt Size	Drill Size
		Metal
17R	1/4 - 20	N/A

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
 Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
 and more open world



## 90° Offset Door Pulls No. BF150, BF151, BF152



**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

- Options:**
- Back to back mounting in pairs – use BTB suffix and mounting type number (BF150BTB16)
  - Concealed mounting single pulls – use C suffix and mounting type number (BF150C17)
  - Advise if door thickness is other than 1 3/4"
  - See page B27 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight
BF150	3/4" dia.	8"	8 3/4"	3/4"	3 1/4"	2 1/2"	3"	2.3 lbs.
BF151	3/4" dia.	10"	10 3/4"	3/4"	3 1/4"	2 1/2"	3"	2.5 lbs.
BF152	3/4" dia.	12"	12 3/4"	3/4"	3 1/4"	2 1/2"	3"	2.7 lbs



## 90° Offset Door Pulls No. BF156, BF157A, BF157, BF158, BF159

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Features:** Recommended for ADA openings

- Options:**
- Back to back mounting in pairs – use BTB suffix and mounting type number (BF156BTB16)
  - Concealed mounting single pulls – use C suffix and mounting type number (BF156C17)
  - Advise if door thickness is other than 1 3/4"
  - Heavy duty versions of most fastening types available – use suffix HD to fastening type number (BF156BTB16HD)
  - See page B27 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight
BF156	1" dia.	8"	9"	1"	3 1/2"	2 1/2"	4"	3.9 lbs.
BF157A	1" dia.	9"	10"	1"	3 1/2"	2 1/2"	4"	4.1 lbs.
BF157	1" dia.	10"	11"	1"	3 1/2"	2 1/2"	4"	4.3 lbs.
BF158	1" dia.	12"	13"	1"	3 1/2"	2 1/2"	4"	4.8 lbs.
BF159	1" dia.	18"	19"	1"	3 1/2"	2 1/2"	4"	6.5 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

## T Series 1" Tubular Pulls


The Rockwood T Series diameter offset tubular pulls are made from sturdy .065" thick wall tubing. Solid brass or stainless steel inserts are brazed into the ends to provide a solid area for our guaranteed mounting systems.

Benefits of specifying the T Series push and pulls include:

- Tubular pulls weigh 25% less than their solid counterparts; this 75% weight reduction greatly reduces the environmental impact of harvesting material for their manufacture – a LEED certified building goal
- The lighter weight minimizes the risk of damage in shipping and handling
- The cost of most tubular pulls represents a significant savings over the equivalent solid model

Considering all the benefits, the T Series pulls offer an improved value without any quality sacrifice

T Series is also available in straight pulls (see page B15) and in both Series 47 push bars and push & pull bar sets (see pages A19–A21).



### 90° Offset Tubular Door Pulls

No. TBF156, TBF157A, TBF157, TBF158, TBF159

**Material:** Brass, bronze, stainless steel


**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Features:** Recommended for ADA openings

- Options:**
- Back to back mounting in pairs – use BTB suffix and mounting type number (TBF156BTB16)
  - Concealed mounting single pulls – use C suffix and mounting type number (TBF156C17)
  - Advise if door thickness is other than 1 3/4"
  - See page B27 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight
TBF156	1" dia.	8"	9"	1"	3 1/2"	2 1/2"	4"	1.3 lbs.
TBF157A	1" dia.	9"	10"	1"	3 1/2"	2 1/2"	4"	1.4 lbs.
TBF157	1" dia.	10"	11"	1"	3 1/2"	2 1/2"	4"	1.4 lbs.
TBF158	1" dia.	12"	13"	1"	3 1/2"	2 1/2"	4"	1.5 lbs.
TBF159	1" dia.	18"	19"	1"	3 1/2"	2 1/2"	4"	1.5 lbs.



## 90° Offset Door Pulls with Base Plates

### No. YBF150, YBF151, YBF152

**Material:** Aluminum, brass, bronze, stainless steel


**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/2" thru bolt & finish washer (standard 1 3/4" door)

**Features:** Base plates improve stability on all doors and are especially recommended for use on wood and glass doors

- Options:**
- Back to back mounting in pairs — use BTB suffix and mounting type number (YBF150BTB16)
  - Concealed mounting single pulls — use C suffix and mounting type number (YBF150C17)
  - Advise if door thickness is other than 1 3/4"
  - See page B27 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight
YBF150	3/4" dia.	8"	9 1/16"	1 1/16"	3 3/4"	2 5/8"	3"	2.4 lbs.
YBF151	3/4" dia.	10"	11 1/16"	1 1/16"	3 3/4"	2 5/8"	3"	2.6 lbs.
YBF152	3/4" dia.	12"	13 1/16"	1 1/16"	3 3/4"	2 5/8"	3"	2.8 lbs



## 90° Offset Door Pulls with Base Plates

### No. YBF156, YBF157A, YBF157, YBF158, YBF159

**Material:** Aluminum, brass, bronze, stainless steel.

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

**Fastener:** 1/4 - 20 x 2 1/2" thru bolt & finish washer (standard 1 3/4" door)

**Features:**

- Recommended for ADA openings
- Base plates improve stability on all doors and are especially recommended for use on wood and glass doors

- Options:**
- Back to back mounting in pairs — use BTB suffix and mounting type number (YBF156BTB16)
  - Concealed mounting single pulls — use C suffix and mounting type number (YBF156C17)
  - Advise if door thickness is other than 1 3/4"
  - Heavy duty versions of most fastening types available — use suffix HD to fastening type number (YBF156BTB16HD)
  - See page B27 for mounting selection (standard duty 1/4 - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight
YBF156	1" dia.	8"	9 1/4"	1 1/4"	3 5/8"	2 5/8"	4"	4.0 lbs.
YBF157A	1" dia.	9"	10 1/4"	1 1/4"	3 5/8"	2 5/8"	4"	4.2 lbs.
YBF157	1" dia.	10"	11 1/4"	1 1/4"	3 5/8"	2 5/8"	4"	4.4 lbs.
YBF158	1" dia.	12"	13 1/4"	1 1/4"	3 5/8"	2 5/8"	4"	4.9 lbs.
YBF159	1" dia.	18"	19 1/4"	1 1/4"	3 5/8"	2 5/8"	4"	6.6 lbs.


**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | www.rockwoodmfg.com  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## 45° Offset Door Pulls No. BF160, BF161, BF162

**Material:** Aluminum, brass, bronze, stainless steel


**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

**Fastener:** 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Back to back mounting in pairs – use BTB suffix and mounting type number (BF160BTB16)
- Concealed mounting single pulls – use C suffix and mounting type number (BF160C17)
- Advise if door thickness is other than 1 3/4"
- See page B27 for mounting selection (standard duty 1/4" - 20).
- Use Y prefix (YBF160) when ordering pulls with base plates, Y plate diameter is 1 1/16"; recommended for use on wood and glass doors

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight
BF160	3/4" dia.	8"	8 3/4"	3/4"	3 1/4"	2 1/2"	2 1/4"	1.8 lbs.
BF161	3/4" dia.	10"	10 3/4"	3/4"	3 1/4"	2 1/2"	2 1/4"	2.0 lbs.
BF162	3/4" dia.	12"	12 3/4"	3/4"	3 1/4"	2 1/2"	2 1/4"	2.2 lbs.



## 45° Offset Door Pulls No. BF166, BF167A, BF167, BF168, BF169

**Material:** Aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 9)

**Fastener:** 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)

**Options:**

- Back to back mounting in pairs – use BTB suffix and mounting type number (BF166BTB16)
- Concealed mounting single pulls – use C suffix and mounting type number (BF166C17)
- Advise if door thickness is other than 1 3/4"
- Heavy duty versions of most fastening types available – use suffix HD to fastening type number (BF166BTB16HD)
- See page B27 for mounting selection (standard duty 1/4" - 20)
- Use Y prefix (YBF16) when ordering pulls with base plates, Y plate diameter is 1 1/4"; recommended for use on wood and glass doors

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight
BF166	1" dia.	8"	9"	1"	3 1/2"	2 1/2"	2 3/4"	2.8 lbs.
BF167A	1" dia.	9"	10"	1"	3 1/2"	2 1/2"	2 3/4"	3.0 lbs.
BF167	1" dia.	10"	11"	1"	3 1/2"	2 1/2"	2 3/4"	3.2 lbs.
BF168	1" dia.	12"	13"	1"	3 1/2"	2 1/2"	2 3/4"	3.6 lbs.
BF169	1" dia.	18"	19"	1"	3 1/2"	2 1/2"	2 3/4"	5.0 lbs.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world



## Offset Door Pull No. 185

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, except US26 and US26D (see page 9)
- Fastener:** 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Engraving "PUSH" or "PULL" or a corporate logo. Email artwork file for quicker service
  - Advise if door thickness is other than 1 3/4"
  - See page B27 for mounting selection (standard duty 1/2" - 20)


No.	Material Size	CTC	Base	Projection	Clearance	Weight
185	5" x 12"	10"	1" x 12"	2 3/8"	1 1/8"	12.5 lbs.



## 90° Offset Door Pull with Santoprene Grip No. BF195

- Material:** Aluminum
- Finishes:** Available in US28, 313, 314, 315, 10BE, BSP (Black Suede), WSP (White Suede), stock powder coat finishes (see page 9)
- Fastener:** 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Features:** Santoprene™ durable, weather resistant grip - available in black (standard), red, and brown  
Recommended for ADA openings
- Options:**
- Back to back mounting in pairs — use BTB suffix and mounting type number (BF195BTB16)
  - Concealed mounting single pulls— use C suffix and mounting type number (BF195C17)
  - Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4" - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight
BF195	1" dia	18"	19"	1"	3 1/2"	2 1/2"	4"	6.7 lbs.



## Heavy Duty Offset Door Pulls No. BF257, BF258, BF259, BF260

- Material:** Aluminum, brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes, US32DMS, US32D316, US32316, white (WPC), red (RPC), and black (BPC) powder coat finishes (see page 6)
- Fastener:** 3/8" - 16 x 2 1/2" thru bolt & finish washer (standard 1 3/4" door)
- Features:**
- Heavy duty pull and mounting for rough service areas
  - Large footprint on door provides stable mounting
- Options:**
- Advise if door thickness is other than 1 3/4"

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Offset	Weight
BF257	1 1/4" dia.	10"	11 1/4"	1 1/4" x 1 7/16"	3 3/4"	2 1/2"	2 15/16"	8.3 lbs.
BF258	1 1/4" dia.	12"	13 1/4"	1 1/4" x 1 7/16"	3 3/4"	2 1/2"	2 15/16"	9.0 lbs.
BF259	1 1/4" dia.	18"	19 1/4"	1 1/4" x 1 7/16"	3 3/4"	2 1/2"	2 15/16"	11.1 lbs.
BF260	1 1/4" dia.	24"	25 1/4"	1 1/4" x 1 7/16"	3 3/4"	2 1/2"	2 15/16"	13.3 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## 90° Straight Door Pull with Santoprene Grip No. 190

- Material:** Aluminum
- Finishes:** Available in US28, 313, 314, 315, 10BE, BSP (Black Suede), WSP (White Suede), stock powder coat finishes (see page 9)
- Fastener:** 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Features:** Santoprene™ durable, weather resistant grip - available in black (standard), red, and brown
- Options:**
- Back to back mounting in pairs — use BTB suffix and mounting types
  - Concealed mounting single pulls— use C suffix and mounting type number (190C6)
  - Advise if door thickness is other than 1 3/4"
  - See page B13 for mounting selection (standard duty 1/4" - 20)

No.	Material Size	CTC	Overall	Base	Projection	Clearance	Weight
190	1" dia	12"	13"	1"	3 1/2"	2"	3.2 lbs.



## Wooden Door Pull No. 208

- Material:** Maple, oak, walnut, cherry (other woods available upon request)
- Finishes:** Brackets available in standard architectural finishes (see page 9)  
Wood available in oiled or clear finish
- Fastener:** 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Ordering:** Specify type of material, finish of wood, and finish of metal brackets
- Options:**
- Use Y prefix (Y208) when ordering pulls with base plates, Y plate diameter is 1 1/16"; recommended for use on glass or wood doors
  - Back to back mounting — use BTB suffix (208BTB) when ordering two pulls back to back. See page B27 for mounting details
  - Other sizes and shapes available; contact factory
  - Advise if door thickness is other than 1 3/4"

No.	Grip	CTC	Overall	Base	Projection	Clearance	Weight
208	1"	8"	15"	3/4" dia.	2 1/2"	1 3/4"	1.9 lbs.



## Tapered Door Pulls No. 215, 215L

- Material:** Aluminum, brass, bronze, stainless steel.
- Finishes:** Available in standard architectural finishes, and US32DMS (see page 9)
- Fastener:** 1/4" - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door)
- Options:**
- Use Y prefix (Y215) when ordering pulls with base plates, Y plate diameter is 1 1/16"; recommended for use on glass or wood doors
  - Back to back mounting — use BTB suffix (215BTB) when ordering two pulls back to back. See page B27 for mounting details
  - Advise if door thickness is other than 1 3/4"


No.	Material Size	CTC	Overall	Base	Projection	Clearance	Weight
215	1" dia.	8"	16"	3/4" dia.	2 1/2"	1 1/2"	3.5 lbs.
215L	1 1/4" dia.	12"	28"	3/4" dia.	2 3/4"	1 1/2"	9.4 lbs.

**ROCKWOOD®**  
**ASSA ABLOY**



## Arm Pull with Plate No. AP1007

- Material:** Stainless steel
- Finishes:** US32D, US32DMS, 10BE, BSP, WSP
- Fastener:** #8 x 3/4" OH SMS, 3/8"-16 x 2 1/2" thru bolt & finish washer
- Features:** Groove on backside of pull to comfortably accept forearm.  
Plate features rounded corners




No.	Pull	Projection	Clearance	Plate Size	Weight
AP1007	3/4" dia.	4"	2 <sup>25</sup> / <sub>32</sub> " at center of groove	4" x 16"	4 lbs. 5.7 oz.



## Arm Pulls No. AP1140, AP1141

- Material:** 1/8" Thick stainless steel
- Finishes:** US32DMS, 10BE, BSP, WSP
- Fasteners:** #10 x 1 1/4" FH SMS
- Options:** Apply above existing door pull or as new application



No.	Pull Width	Base Plate Width	Projection	Clearance	Weight
AP1140	1 1/2"	2"	4 1/2"	4 3/8"	6.4 oz.
AP1141	1 1/2" to 3/4"	2"	4 1/2"	4 3/8"	5 oz.



## Hand/Arm Pull No. 193

- Material:** Cast brass, stainless steel
- Finishes:** US32D, US32DMS, US3, US4, US10, US10B, 10BE, BSP, WSP, US26, US26D
- Fasteners:** #8 x 3/4" OH SMS
- Options:** Use top portion as hand pull, use bottom portion as arm pull



No.	CTC	Overall	Projection	Clearance	Weight
193	5 <sup>15</sup> / <sub>16</sub> "	9 1/4"	3 3/4"	1 <sup>5</sup> / <sub>8</sub> "	0.9 lbs.

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Foot Pull No. FP1230

- Material:**  $\frac{3}{16}$ " Thick stainless steel
- Finishes:** US32D, US32DMS, 10BE, BSP, WSP
- Fastener:**  $\frac{1}{4}$ -20 x 1" FH MS
- Features:** Grip on top of pull for ease of use.
- Options:** Place your foot on top grip and pull the door open or put your toe underneath and pull the door towards you.



No.	CTC	Projection	Clearance	Weight
FP1230	6"	$3\frac{1}{4}$ "	$3\frac{1}{16}$ "	1 lbs. 1.3 oz.



## Door Holder/Foot Pull No. 494-RKW

- Material:** Cast brass
- Finishes:** Available in standard architectural finishes (see page 9)
- Other:** Holder base: 3"w x  $3\frac{3}{8}$ "h
- Holder Projection:**  $2\frac{1}{8}$ "
- Strike Base** 2"w x 3"h
- Strike Projection:**  $3\frac{1}{4}$ "
- Options:** Install strike on the bottom of the door to use as a foot pull. Mount the holder to the wall adjacent to the strike and utilize as a door holder.



No.	Fastener	Strike	Weight
494-RKW	Strike: 3 ea. #12 x $1\frac{1}{4}$ " FH WS, 3 ea. Plastic anchors Body: 4 ea. #10 x $1\frac{1}{4}$ " FH WS	Door	1.7 lbs.

*NOTE: 494-RKW can be used as an Automatic Door Holder with Stop, see page D17.*



No. VRT12



No. VRT22

## Vandal Resistant Trim No. VRT12, VRT22

**Material:** Stainless steel

**Finishes:** VRT12 - US32D,US32DMS 10BE, Stock Powder Coats  
VRT22 - US32D

**Fastener:** 1/4 - 20 thru bolt. Other sizes to match locks and exit devices as required

**Features:** VRT22 — soft black textured grip

**Options:**

- Cut for cylinder — use C suffix (VRT22C) when ordering
- Specify make and model number of exit device when mounting with exit device fastening systems

No.	Material Size	Weight
VRT12	5 <sup>7</sup> / <sub>8</sub> " x 12"	2.3 lbs.
VRT22	5 <sup>7</sup> / <sub>8</sub> " x 12"	2.3 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



No. VRT14



No. VRT16



No. VRT24



No. VRT26

# Vandal Resistant Trim

## No. VRT14, VRT16, VRT24, VRT26

**Material:** Stainless Steel

**Finishes:** VRT14 & VRT16 - US32D, US32DMS, 10BE,  
Stock Powder Coats VRT24 & VRT26 - US32D

**Fastener:** 1/4 -20 Thru Bolt. Other sizes to match locks and exit devices as required

- Features:**
- Ideal pull for the exterior doors on schools and other public buildings, as well as the rear exit doors of commercial and industrial buildings
  - Vandal Resistant design minimizes opportunity for tampering
  - No exposed fasteners
  - Supplied with thru bolts for non-integrated mounting
  - US Patent No.: D659,507S

- Options:**
- Cut for cylinder use C suffix (VRT24C) when ordering
  - Specify make and model number of exit device when mounting with exit device fastening systems

No.	Integral Latch Guard	Textured Black Grip	Overall	Weight
VRT14	Yes	No	1/8" x 7" x 12"	3.2 lbs.
VRT16	No	No	1/8" x 5 1/2" x 12"	2.5 lbs.
VRT24	Yes	Yes	1/8" x 7" x 12"	3.2 lbs.
VRT26	No	Yes	1/8" x 5 1/2" x 12"	2.5 lbs.

Required Order Information (Please supply all required templates - mating parts and cylinders).

Quantity	Product #	Mating Manufacturer	Mating Part #	Device Template #	Template # for Cylinder Hole Location	Cylinder Diameter	Door Handing	Finish

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world

## Vandal Resistant Pull No. VRP 30



**Material:** 4" x 16" High Strength Steel

**Weight:** 3.25 lbs.

**Finishes:** 10BE, Stock Powder Coats, US32D, US32DMS

**Fastener:** #8 x 3/4" Oval Head Sheet Metal Screws

- Features:**
- Narrow, sloping handle for easy grip and reducing binding opportunities between handles.
  - High strength steel designed for durability and resisting vandalism.
  - Non handed design, reduces risk of installing incorrectly.
  - Backing plate included, removes necessity to repaint opening in retrofit applications.
  - Patented

- Options:**
- Engraving
  - Custom Powder Coat Available
  - Cylinder Option
  - For Mounting with Exit Device: Specify make and model number of exit device and send template when ordering.

Required Order Information (Please supply all required templates - mating parts and cylinders).

Quantity	Product #	Mating Manufacturer	Mating Part #	Device Template #	Template # for Cylinder Hole Location	Cylinder Diameter	Finish

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

# Rockwood Vandal Resistant Order Form

Complete this form and email to: orders.rockwood@assaabloy.com / or fax to: 800.922.9212


## Customer Information

Company Name: \_\_\_\_\_ Date: \_\_\_\_\_

Account #: \_\_\_\_\_ Phone/Fax: \_\_\_\_\_ / \_\_\_\_\_

Email: \_\_\_\_\_ PO #: \_\_\_\_\_ Line #: \_\_\_\_\_

\* Cylinder Prep optional - Use C suffix (ex: VRT12C) when ordering.



Vandal Resistant Products can be ordered to mount with an exit device, or in conjunction with a mortise lock. Include exit device and mortise lock templates when ordering. (If not being paired with either, please advise.) Stud locations shown above are an indication that an exit device can be mated to these pulls. This is not indicating a standard pattern of these studs, we can custom manufacture the pull to the exit device required.

No.	Integral Latch Guard	Textured Black Grip	Size	Weight
<b>VRT12</b>	No	No	5 7/8" x 12"	2.3 lbs
<b>VRT22</b>	No	Yes	5 7/8" x 12"	2.3 lbs
<b>VRT14</b>	Yes	No	6 3/4" x 12"	3.2 lbs
<b>VRT24</b>	Yes	Yes	6 3/4" x 12"	3.2 lbs
<b>VRT16</b>	No	No	5 3/8" x 12"	2.5 lbs
<b>VRT26</b>	No	Yes	5 3/8" x 12"	2.5 lbs
<b>VRP30</b>	N/A	No	4" x 16" - 2 11/16" Proj.	3.25 lbs

## Required Order Information (Please supply all required templates)

Qty	Rockwood Product #	Mating Device Manufacturer	Mating Device Product #	Device Template #	Template # for Cylinder Hole Loc.	Cylinder Dia.	Door Handing	Finish

### Finish Options:

VRT22, VRT24, VRT26: US32D/630

VRT12, VRT14, VRT16, VRT30:  US32D/630  US32DMS  10BE  Stock Powder Coats (specify): \_\_\_\_\_

**NOTE:** Orders will not be processed until all Templates have been received.

**NOTE:** Mounting hardware is not provided for VRT to attach with exit device.

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

\_\_\_\_\_  
(customer signature)

\_\_\_\_\_  
(date)

**ROCKWOOD®**  
**ASSA ABLOY**

800 458 2424 | www.rockwoodmfg.com  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

Experience a safer  
and more open world **B39**


# Notes



Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



**Mop Plate** Up to 6" h x 48" w  
**Kick Plate** 6" to 12" h x 48" w  
**Stretcher Plate** 6" to 12" h and up to 48" w  
**Armor Plate** Up to 48" h x 48" w and available in most finishes

Width of Plates:  
 Push Side: 2" less than door width.  
 Pull Side: 1½" less than door width.  
**NFPA 80 STANDARDS – 2-4.5 Protection Plates:** Factory-installed protection plates shall be installed in accordance with the listing of the door. Field-installed protection plates shall be labeled and installed in accordance with their listing.  
 Exception: Labeling is not required where the top of the protection plate is not more than 16" (406 mm) above the bottom of the door.

**OPTIONAL Self-Drilling TEK Screws:** Cuts door plate installation time in half.

## Metal Door Plate – Economy Duty No. K1038

- Material:** .038" stainless steel  
**Finishes:** US32D  
**Fastener:** #6 x 5/8" OH SMS  
**Ordering:** Specify height x width x finish code. Add any options  
**Weight:** 8" x 34" = 3.2 lbs  
**Features:**
  - All edges come beveled**Options:**
  - SA – self-adhesive mounting
  - TORX – security Torx screws
  - TEK – self-drilling screws
  - Cutouts for locks, louvers, or windows (see worksheets on pages C14-C15 for details on how to order)

## Metal Door Plate – Standard Duty No. K1050

- Material:** .050" Stainless Steel  
**Finishes:** US32D  
**Fastener:** #6 x 5/8" OH SMS  
**Features:**
  - All edges come beveled**Options:**
  - One day shipping available
  - Door markings are not available on quick ship

## Metal Door Plate – Standard Duty No. K1050, K1050F

- Material:** .050" aluminum, brass, bronze, stainless steel  
**Finishes:** 10BE, US32D, US32DMS  
**Fastener:** #6 x 5/8" OH SMS  
**Ordering:** Specify height x width x finish code. Add any options  
**Weight:** 8" x 34" = 4.0 lbs  
**Features:**
  - All edges come beveled**Options:**
  - SA – self-adhesive mounting
  - TEK – self-drilling screws
  - Cutouts for locks, louvers, or windows (see worksheets on pages C14-C15 for details on how to order)
  - UL listed TEK – self-drilling screws for use on 90-minute label wood doors and 3-hour label metal doors
  - Heavy bevel available, specify HVBEV
  - Screw mounting (K1050F) and UL listed for use on 90-minute label wood doors and 3-hour label metal doors
  - CSK – countersunk holes
  - TORX – security Torx screws



## Windstorm Plate – K1050WS

- Material:** .050" Aluminium, Brass, Bronze, Stainless Steel  
**Finishes:** Standard Architectural Finishes  
**Fastener:** #10x5/8" Pan Head Tek Screws  
**Ordering:** Part # when ordering is K1050WS  
 All plates are UL and Windstorm rated  
**Features:**
  - All edges come beveled**Options:**
  - Cutouts for locks, louvers or windows
  - Rounded Corners
  - Heavy Bevel
  - Screw Mount only
- UL** Certified to the below standards:  
 - ICC-500 (2014)  
 - FEMA Guideline 320 (2014)  
 - FEMA Guideline 361 (2015)
- Part of windstorm assembly cards:  
 ZHLA.45, ZHLA.46, ZHLA.47, ZHLA.51,  
 ZHLA.53, ZHLA.54

800 458 2424 | www.rockwoodmfg.com  
 Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



Experience a safer and more open world

# Shaped Metal Door Plates – Standard Duty No. K1050-1 thru K1050-8

**Material:** .050" stainless steel

**Finishes:** US3, US4, US9, US10, US32D, US32DMS, 10BE, BSP, WSP, Stock Powder Coats, OptiCoat™

**Fastener:** #6 x 5/8" OH SMS

**Ordering:** Specify height x width x finish code. Add any options


**Weight:** 8" x 34" = 4.0 lbs

**Features:** • All edges come beveled


**Options:**

- TEK – self-drilling screws
- CSK – countersunk holes
- Cutouts for locks, louvers, or windows (see worksheets on pages C14–C15 for details on how to order)
- TORX – security Torx screws
- Screw mounting (K1050F) and UL listed for use on 90-minute label wood doors and 3-hour label metal doors
- Any design is possible. Submit your drawings for a custom quote


No. K1050-1




No. K1050-2




No. K1050-3




No. K1050-4




No. K1050-5




No. K1050-6



No. K1050-7



No. K1050-8




**ROCKWOOD®**

**ASSA ABLOY**


Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog


Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.




**Mop Plate**  
Up to 6" h x 48" w



**Kick Plate**  
6" to 12" h x 48" w



**Stretcher Plate**  
6" to 12" h and up to 48" w



**Armor Plate**  
Up to 48" h x 48" w and  
available in most finishes

**Width of Plates:**

Push side: 2" less than door width. Pull side: 1½" less than door width.

## Metal Door Plate – Heavy Duty No. K1062

**Material:** .062" stainless steel

**Finishes:** 10BE,US32D,US32DMS, BSP, WSP

**Fastener:** #6 x 5/8" OH SMS

**Ordering:** Specify height x width x finish code. Add any options

**Weight:** 8" x 34" = 5.0 lbs

**Features**

- All edges come beveled

**Options:**

- TEK – self-drilling screws
- CSK – countersunk holes
- Cutouts for locks, louvers, or windows (see worksheets on pages C14–C15 for details on how to order)
- TORX – security Torx screws
- Heavy bevel available, specify HVBEV

## Metal Door Plate – Extra Heavy Duty No. K1125

**Material:** .125" aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32D**316** (see page 9)

**Fastener:** #6 x 5/8" OH SMS

**Ordering:** Specify height x width x finish code. Add any options

**Weight:** 8" x 34" = 10.0 lbs

**Features**

- All edges come beveled (not applicable on Aluminum Diamond Plate)

**Options:**

- TEK – self-drilling screws
- Cutouts for locks, louvers, or windows (see worksheets on pages C14–C15 for details on how to order)
- TORX – security Torx screws

## Metal Door Plate – Extra Heavy Duty Diamond Plate No. K1125 DIA

**Material:** .125" aluminum

**Finishes:** Polished aluminum diamond plate (ALM DIA)

**Fastener:** #6 x 5/8" OH SMS

**Ordering:** Specify height x width x finish code. Add any options

**Weight:** 8" x 34" = 10.0 lbs


**Options:**

- TEK – self-drilling screws
- Cutouts for locks, louvers, or windows (see worksheets on pages C14–C15 for details on how to order)
- TORX – security Torx screws



ALM DIA  
Polished Aluminum  
Diamond Plate

## Plastic Door Plate – Heavy Duty No. K2060

- Material:** .060" Kydex® 160 PVC acrylic alloy plastic\*
- Finishes:** Beige #72005, calcutta black #52000, chocolate brown #72010, pewter gray #52001
- Fastener:** #6 x 3/4" TH SMS
- Ordering:** Specify height x width x color. Add any options
- Weight:** 8" x 34" = 1.0 lbs
- Options:**
- Cutouts for locks, louvers, or windows (see worksheets on pages C14–C15 for details on how to order)
  - SA – self-adhesive mounting (K2060SA)
  - SA-F – self-adhesive mounting (K2060SA-F) and UL approved for use of 90-minute wood doors and 3-hour metal doors 

---

## Plastic Door Plate – Extra Heavy Duty No. K2125

- Material:** .125" Kydex® 160 PVC acrylic alloy plastic\*
- Finishes:** Beige #72005, calcutta black #52000, chocolate brown #72010, pewter gray #52001
- Fastener:** #6 x 3/4" TH SMS
- Ordering:** Specify height x width x color. Add any options
- Weight:** 8" x 34" = 1.8 lbs
- Options:**
- Cutouts for locks, louvers, or windows (see worksheets on pages C14–C15 for details on how to order)
  - CSK – countersunk holes

\* Kydex 160 meets Class 1A building code ratings up to .060" thick.


**ROCKWOOD®**

**ASSA ABLOY**


Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog


Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**Mop Plate**


Up to 6" h x 48" w

**Kick Plate**

6" to 12" h x 48" w

**Stretcher Plate**

6" to 12" h and up to 48" w

**Armor Plate**

Up to 48" h x 48" w

Width of Plates:

Push side: 2" less than door width. Pull side: 1½" less than door width.

## Laminate Plastic Door Plate No. K3125


**Material:** .125" laminate plastic**Finishes:** Beige, black, brown, pewter gray, white**Fastener:** #6 x ¾" TH SMS**Ordering:** Specify height x width x finish code x color. Add any options**Weight:** 8" x 34" = 1.8 lbs

- Options:**
- SA – self-adhesive mounting (K3125SA)
  - Cutouts for locks, louvers, or windows (see worksheets on pages C14–C15 for details on how to order)
  - CSK – countersunk holes

## Clear Plastic Door Plate No. K4125

**Material:** .125" clear plastic**Finishes:** Clear**Fastener:** #6 x ¾" TH SMS**Features:** Break and scratch resistant**Ordering:** Specify height x width. Add any options**Weight:** 8" x 34" = 1.5 lbs

- Options:**
- Cutouts for locks, louvers, or windows (see worksheets on pages C14–C15 for details on how to order)
  - CSK – countersunk holes



## One-Sided Angle Plate No. KB1150

**Material:** .050" aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes (see page 9)


**Fastener:** #6 x  $\frac{5}{8}$ " FH/OH SMS

**Ordering:** Provide drawing specifying size, and square or bevel edge door

- 87 degrees – Pull side of beveled door
- 90 degrees – Push/Pull side of square door
- 93 degrees – Push side of beveled door

**Options:**

- Beveling, TORX – security Torx screws
- TEK – self-drilling screws
- Cutouts for hinges, flush bolts, and locks
- UL Listed (screw applied)



## Two-Sided Angle Plate No. KB1151

**Material:** .050" aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes (see page 9)


**Fastener:** #6 x  $\frac{5}{8}$ " FH/OH SMS

**Ordering:** Provide drawing specifying size, and square or bevel edge door

- Both 90 degree bends on push or pull side of square door
- Both 93 degree bends on push side of beveled door
- One 90 degree bend and One 93 degree bend on push side of beveled/ square door
- Both 87 degree bends on pull side beveled door
- One 90 degree bend and One 87 degree bend on pull side of beveled/ square door

**Options:**

- Beveling, TORX – security Torx screws
- TEK – self-drilling screws
- Cutouts for hinges, flush bolts, and locks
- UL Listed (screw applied)



## Bottom Angle Plate No. KB1152

**Material:** .050" aluminum, brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** #6 x  $\frac{5}{8}$ " FH/OH SMS

**Ordering:** Provide drawing specifying size, and square or bevel edge door

- Always 90 degree bends

**Options:**

- Beveling, TORX – security Torx screws
- TEK – self-drilling screws
- UL Listed (screw applied)

**ROCKWOOD**<sup>®</sup>


**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

# Mortise Door Edges No. 300, 301, 302, 302B



**Material:** .050" brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32D**MS**, US32D**316**, prime painted steel (see page 9)

**Fastener:** #6 x 5/8" FH SMS


**Ordering:** Specify any length up to 96" (standard lengths are 42", 84", 96")  
*NOTE: 84" and 96" are made to match net door height – specify.*

**Features:** Door edges are sized to be mortised into the surface of 1 3/4" thick wood doors. Advise if your door is another thickness  
*NOTE: Some wood doors that are nominally 1 3/4" vary significantly.*


- Options:**
- UL fire rated listed for stainless steel, brass and bronze. For use on wood or plastic faced fire doors rated up to and including 1 1/2 hours or hollow metal, steel covered, composite type fire doors rated up to and including 3 hours. Specify UL when ordering (300-UL)
  - Cutouts for flush bolts, lock strikes, locks, and hinges (see worksheets on pages C10-C11 or C13-C15 for details on how to order)

*NOTE: Your door thickness is a nominal dimension. Doors can vary + or - 1/16" from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.*


No. 300




No. 301



No. 302



No. 302B



\* Modified leg lengths available.

**ROCKWOOD®**  
**ASSA ABLOY**



# Non-Mortise Door Edges

## No. 304, 305, 306-RKW, 306-AST, 306B, 306B-AST, 307

**Material:** .050" brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32D**MS**, US32D**316**, prime painted steel (see page 9)

**Fastener:** #6 x 5/8" FH SMS

**Features:** • Door edges are sized for 1 3/4" thick wood or metal doors. Advise if your door is another thickness

*NOTE: Some wood doors that are nominally 1 3/4" vary significantly.*

• 306-AST and 306B-AST include an astragal, providing additional protection against vandalism

**Ordering:** Specify any length up to 96" (standard lengths are 42", 84", 96")

*NOTE: 84" and 96" are made to match net door height – specify.*


Specify wood or metal door

**Options:** • UL fire rated listed for stainless steel, brass and bronze. For use on wood or plastic faced fire doors rated up to and including 1 1/2 hours or hollow metal, steel covered, composite type fire doors rated up to and including 3 hours. Specify UL when ordering (306-UL)


• Cutouts for flush bolts, lock strikes, locks, and hinges (see worksheets on pages C10-C11 or C13-C15 for details on how to order)

*NOTE: Your door thickness is a nominal dimension. Doors can vary + or - 1/16" from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.*


No. 304




No. 305




No. 306-RKW




No. 306-AST  
(with Astragal)




No. 306B



No. 306B-AST  
(with Astragal)



No. 307



\* Modified leg lengths available.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

# Overlapping Door Edges

## No. 308, 309, 310, 310S, 310B, 310BS



**Material:** .050" brass, bronze, stainless steel

**Finishes:** Available in standard architectural finishes, US32DMS, US32D316, prime painted steel (see page 9)


**Fastener:** #6 x 5/8" FH SMS

**Ordering:** Specify any length (standard length is 42"). Specify wood or metal door


- Options:**
- UL fire rated listed for stainless steel, brass and bronze. For use on wood or plastic faced fire doors rated up to and including 1 1/2 hours or hollow metal, steel covered, composite type fire doors rated up to and including 3 hours. Specify UL when ordering (310-UL)
  - Cutouts for flush bolts, lock strikes, locks, and hinges (see worksheets on pages C10-C11 or C13-C15 for details on how to order)

*NOTE: Your door thickness is a nominal dimension. Doors can vary + or - 1/16" from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.*


No. 308




No. 309




No. 310




No. 310S  
(single side)



No. 310B



No. 310BS  
(single side)



## Ordering Instructions


The use of door edges and armor plates not only offers superior protection to expensive doors, it also adds an attractive and functional finishing touch. Armor plates and door edges are available in all architectural finishes. The following two pages are intended to help you determine the cutout locations required on armor plates and door edges. Follow the steps listed to assure complete consideration of all factors concerning cutout locations.

- Determine the armor plate height. We recommend 48" high. If you cut holes for lock, make the armor plate high enough to provide at least  $\frac{1}{2}$ " from edge of the top cutout to the top edge of the plate, or  $\frac{1}{2}$ " above the top of the lock front when mortise lock is used. This prevents a cutout running out of the top edge of the plate.
- Determine the armor plate width. Armor plates are usually mounted on the stop or push side of the door. Measure the net width of the door face and subtract the following depending on the type of door edges you specify:
  - non-mortise door edges =  $2\frac{5}{8}$ " (for  $\frac{1}{8}$ " gap)
  - overlapping door edges = 2" (for  $\frac{3}{16}$ " overlap)
  - no door edges – single door =  $1\frac{1}{4}$ "
  - no door edges – pairs of doors = 1" (without mullions)
- List all hardware that will be mounted on the door. Identify those items that will require armor plate and/or door edge cutouts; i.e., lock spindle, cylinder, thumb piece, lock front and strike, flush bolts, hinges, louvers, lites.
- Determine door undercut and location of armor plate and door edge to bottom of the door. We recommend mounting plates flush with the bottom of the door.
- Determine location of all hardware cutout centerlines from the bottom of the armor plate.
- Determine the backset of lock cutouts on the armor plate.

		Square Edge	Bevel Edge
a) with non-mortise door edges	lock backset minus	$1\frac{5}{16}$ "	$1\frac{3}{8}$ "
b) with overlapping door edges	lock backset minus	1"	$1\frac{1}{16}$ "
c) without door edges – single doors	lock backset minus	$\frac{5}{8}$ "	$1\frac{1}{16}$ "
d) without door edges – pair of doors (without mullions)	lock backset minus	$\frac{3}{8}$ "	$\frac{7}{16}$ "

- Specify the size of cutouts.
- Determine the hand of the door. Armor plates are typically mounted on the stop or push side of the door. Function holes must be given special attention as they may not be required on reverse bevel doors.

*NOTE: Your door thickness is a nominal dimension. Doors can vary + or -  $\frac{1}{16}$ " from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.*



**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog


Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

# Cutouts


This drawing shows typical location of cutouts on armor plates and door edges. It also illustrates non-mortise door edges, but this can be used as a guide for armor plates with overlapping door edges or no door edges. Use this as a worksheet to make your own drawings or photocopy and fill in your dimensions.

**For Hinge Cutouts:** Be sure to allow for door undercut and location of edge on door if other than flush with bottom.

**For Lock Trim Protection:** Consider using a trim protector bar.



*NOTE: Your door thickness is a nominal dimension. Doors can vary + or - 1/16\"*




# Cutouts

This drawing shows typical location of cutouts on armor plates and door edges. It also illustrates non-mortise door edges, but this can be used as a guide for armor plates with overlapping door edges or no door edges. Use this as a worksheet to make your own drawings or photocopy and fill in your dimensions.


**For Hinge Cutouts:** Be sure to allow for door undercut and location of edge on door if other than flush with bottom.

**For Lock Trim Protection:** Consider using a trim protector bar.




*NOTE: Your door thickness is a nominal dimension. Doors can vary + or - 1/16" from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.*

**SQUARE EDGE BACKSET**



**BEVEL EDGE BACKSET**



**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

Fill out this form and email/fax form to orders.rockwood@assaabloy.com / or fax to: 800-922-9212.

**Customer Information**

Company Name: \_\_\_\_\_ Date: \_\_\_\_\_

Account#: \_\_\_\_\_ Phone #/Fax #: \_\_\_\_\_

Email: \_\_\_\_\_ PO#: \_\_\_\_\_

**Select a Door Edge**

- Mortised:  300  301  302  302B
- Non-Mortised:  304  305  306-RKW  306-AST  306B  306B-AST
- 308  309  310  310B  310BS
- Other \_\_\_\_\_

Order Line #: \_\_\_\_\_ Quantity: \_\_\_\_\_ Handing: \_\_\_\_\_ Tag. Nos.: \_\_\_\_\_

Finish: \_\_\_\_\_

**Select Hinge Size, Door Type and Fill in Dimensions**

UL Rated

\*Door Edge Height if different from net door height  
\_\_\_\_\_



Specify Mounting (if not standard)

- Torx Screws  
 Tek Screws


\*Standard Door Thickness is 1<sup>3</sup>/<sub>4</sub>" if not please advise:  
\_\_\_\_\_

\*Standard Leg Length for non mortised edge is 1<sup>1</sup>/<sub>4</sub>" if not please advise:  
\_\_\_\_\_


\*Standard Leg Length for mortised edge is 7/<sub>8</sub>" if not please advise:  
\_\_\_\_\_



Door with 3 Hinges



Door with 4 Hinges



*NOTE: Your door thickness is a nominal dimension. Doors can vary + or - 1/16" from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.*

Fill out this form and email/fax form to orders.rockwood@assaabloy.com / or fax to: 800-922-9212.

**Customer Information**

Company Name: \_\_\_\_\_ Date: \_\_\_\_\_

Account#: \_\_\_\_\_ Phone #/Fax #: \_\_\_\_\_

Email: \_\_\_\_\_ PO#: \_\_\_\_\_

**Select a Door Edge**

- Mortised:  300  301  302  302B
- Non-Mortised:  304  305  306-RKW  306-AST  306B  306B-AST
- 308  309  310  310B  310BS
- Other \_\_\_\_\_

Order Line #: \_\_\_\_\_ Quantity: \_\_\_\_\_

Finish: \_\_\_\_\_ Handing: \_\_\_\_\_ Tag. Nos.: \_\_\_\_\_

**Select Cutout, Door Type and Fill in Dimensions**

**UL Rated**

\*Door Edge Height if different from net door height  
\_\_\_\_\_

**Astragal Side**

(306-AST, 306B-AST ONLY)

- Active Door  
 Inactive Door

**Specify Mounting**


(if not standard)

- Torx Screws  
 Tek Screws

\*Standard Door Thickness is 1 3/4" if not please advise:  
\_\_\_\_\_

\*Standard Leg Length for non mortised edge is 1 1/4" if not please advise:  
\_\_\_\_\_

\*Standard Leg Length for mortised edge is 7/8" if not please advise:  
\_\_\_\_\_



\*Above is a representation of a prep location on the edge of the door.

**NOTE:** Your door thickness is a nominal dimension. Doors can vary + or - 1/16" from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer and more open world

800 458 2424 | www.rockwoodmfg.com  
Check the web site for the up-to-date catalog



## Wrap Around Plate No. 350WP

**Material:** Stainless Steel, Brass, Bronze

**Finishes:** US3/605, US4/606, US10/612, US10B/613, US32MS, US32DMS, US32/629, US32D/630, 10BE/613E, BSP, WSP, BPC, WPC, FBPC, RPC, Stock Powder Coats

**Fastener:** #6 x 5/8" Oval Head Sheet Metal Screws

**Features:**

- For both wood and metal doors
- Reinforces area around door lock
- Conceals door damage
- Added protection against forced entry
- Custom latch and lock preps available

**Options:**

- Latch Preps Available:
  - Single Flat Front
  - Double Flat Front
  - Indent Clip Prep
- Lock Preps Available:
  - Universal Cylindrical
  - Mortise

No.	Max Height	Max Leg Length
350WP	18"	6-1/2"

## Solutions to Door and Trim Damage

Damage to doors and door trim (exit devices, knobs, levers, etc.) from hallway traffic such as carts and gurneys cost hospitals, schools and other institutions tens of thousands of dollars every year. The following four pages are Rockwood Product's line of Unique, Patented Protection Products designed to prevent this damage. Made from solid stainless steel the line is engineered to deflect traffic safely away from the door or trim.

Our line of trim protector bars is designed to safely deflect traffic away from exit devices, door knobs/levers, or other trim. These bars are made from solid stainless steel and are available in both standard duty ( $\frac{3}{16}$ "") and heavy duty ( $\frac{3}{8}$ "") versions. The bars are mounted either directly below, over, or in front of the trim depending on the application. They are available in a variety of projections and center to centers to fit your needs. If you require custom designs our engineering department can work with you to meet your needs.


Choosing the correct protection bar:

1. **Determine traffic** – light to moderate use = SD Series, heavy use = HD Series.
2. **Measure projection** – of exit device, door knob, etc.
3. **Review product dimension** – to match bar to your specific needs.




**Warning:** Do not locate protection bars where they can impede operation of exit devices.

### How They Work



Without Bar – Costly Damage



With Bar – Safely Deflected Away

**ROCKWOOD**<sup>®</sup>


**ASSA ABLOY**

Experience a safer  
and more open world


800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

## Heavy Duty Application




Application shown for product HD2230, HD2240, HD2250.  
\* Advise if door thickness is other than 1 3/4".




patent no.  
5,934,023

### Heavy Duty Protector Bars HD2230, HD2230M

- Material:** Stainless steel
- Finishes:** US32D, US32DMS, 10BE
- Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door\*)
- Other:** Made to order sizes available




No.	CTC	Material Size	Projection	Weight
HD2230	8"	3/8" x 1 1/2"	3 1/4"	2.3 lbs.
HD2230M	Specify	3/8" x 1 1/2"	3 1/4"	—




patent no.  
5,934,023

### Heavy Duty Protector Bars HD2240, HD2240M

- Material:** Stainless steel
- Finishes:** US32D, US32DMS, 10BE
- Fastener:** 1/4 -20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door\*)
- Other:** Made to order sizes available




No.	CTC	Material Size	Projection	Weight
HD2240	8"	3/8" x 1 1/2"	3 3/4"	2.5 lbs.
HD2240M	Specify	3/8" x 1 1/2"	3 3/4"	—



patent no.  
5,934,023


### Heavy Duty Protector Bars HD2250, HD2250M

- Material:** Stainless steel
- Finishes:** US32D, US32DMS, 10BE
- Fastener:** 1/4 - 20 x 2 1/4" thru bolt & finish washer (standard 1 3/4" door\*)
- Other:** Made to order sizes available




No.	CTC	Material Size	Projection	Weight
HD2250	8"	3/8" x 1 1/2"	4 1/4"	2.7 lbs.
HD2250M	Specify	3/8" x 1 1/2"	4 1/4"	—


## Standard Duty Applications



Application shown for product SD1230, SD1240, SD1250.




Application shown for product SD1260.




patent no.  
5,934,023

### Standard Duty Protector Bar No. SD1230

- Material:** Stainless steel
- Finishes:** US32D, US32DMS, 10BE
- Fastener:** #10-24 x 1 FH MS and sex bolt




No.	CTC	Material Size	Projection	Weight
SD1230	8"	3/16" x 2"	3 1/4"	1.4 lbs.




patent no.  
5,934,023

### Standard Duty Protector Bar No. SD1240

- Material:** Stainless steel
- Finishes:** US32D, US32DMS, 10BE
- Fastener:** #10 - 24 x 1 FH MS and sex bolt




No.	CTC	Material Size	Projection	Weight
SD1240	8"	3/16" x 2"	3 3/4"	1.6 lbs.



patent no.  
5,934,023

### Standard Duty Protector Bar No. SD1250

- Material:** Stainless steel
- Finishes:** US32D, US32DMS, 10BE
- Fastener:** #10 - 24 x 1 FH MS and sex bolt




No.	CTC	Material Size	Projection	Weight
SD1250	8"	3/16" x 2"	4 1/4"	1.7 lbs.



### Standard Duty Protector Bar No. SD1260

- Material:** Stainless steel
- Finishes:** US32D, US32DMS, 10BE
- Fastener:** #10 - 24 x 1 FH MS and sex bolt



No.	CTC	Material Size	Projection	Weight
SD1260	8"	3/16" x 2"	3 1/4"	1.6 lbs.

**ROCKWOOD®**


**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

## Applications



Application shown for product R101LPB thru R115LPB.

\* Advise if door thickness is other than 1<sup>3</sup>/<sub>4</sub>".




### Trim Protector Bars No. R101LPB, R102LPB

**Material:** Stainless steel

**Finishes:** US32D, US32DMS, 10BE/BSP, BPC, FBPC, WPC, WSP, Stock Powder Coats

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt, 1/4 - 20 x 2" thru bolt, finish washers (standard 1 3/4" door\*)

**Other:** Made to order sizes available



No.	CTC	Material Size	Weight
R101LPB	12"	3/8" x 1 1/2"	2.6 lbs.
R102LPB (with reinforcing bar)	12"	3/8" x 1 1/2"	4.6 lbs.




### Trim Protector Bars – Lever Handle No. R111LPB, R112LPB

**Material:** Stainless steel

**Finishes:** US32D, US32DMS, 10BE/BSP, BPC, FBPC, WPC, WSP, Stock Powder Coats

**Fastener:** 1/4 - 20 x 2 1/4" thru bolt, 1/4 - 20 x 2" thru bolt, finish washers (standard 1 3/4" door\*)

**Other:** Made to order sizes available



No.	CTC	Material Size	Weight
R111LPB	12"	3/8" x 1 1/2"	2.6 lbs.
R112LPB (with reinforcing bar)	12"	3/8" x 1 1/2"	4.6 lbs.




### Trim Protector Bar - Long Lever Handle No. R115LPB

**Material:** Stainless steel

**Finishes:** US32D, US32DMS, 10BE/BSP


**Fastener:** 1/4 - 20 x 2 1/4" thru bolt, 1/4 - 20 x 2" thru bolt, finish washers (standard 1 3/4" door\*)

**Other:** Made to order sizes available





No.	CTC	Material Size	Weight
R115LPB	14"	3/8" x 1 1/2"	3.0 lbs.

# EDP Application



Application shown for product R116EDPL and R116EDPH.  
Field cutting hinge end of exit device is required.

\* Advise if door thickness is other than 1<sup>3</sup>/<sub>4</sub>".



## Exit Device Protector No. R116EDPL

**Material:** Stainless steel

**Finishes:** US32D, US32DMS, 10BE

**Fastener:** 2 ea. 1/4 - 20 x 2 1/4" thru bolts, 1 ea. 1/4 - 20 x 2" thru bolt, finish washers (standard 1 3/4" door\*)



**Features:** Suitable for use with exit devices that project less than 2 3/8" from door face (i.e., SARGENT® 80 series, Monarch® 17 series, and Precision® Apex series)

No.	CTC	Material Size	Projection	Weight
R116EDPL	7 1/2"	3/8" x 1 1/2"	3/4"	3.5 lbs.

® SARGENT 80 series is a registered trademark of Sargent Manufacturing Company.

® Monarch 17 series is a registered trademark of Ingersoll-Rand Company.

® Precision Apex series is a registered trademark of Apex Machine Tool Company.



## Exit Device Protector No. R116EDPH

**Material:** Stainless steel

**Finishes:** US32D, US32DMS, 10BE

**Fastener:** 2 ea. 1/4 - 20 x 2 1/4" thru bolts, 1 ea. 1/4 - 20 x 2" thru bolt, finish washers (standard 1 3/4" door\*)

**Features:** Suitable for use with exit devices that project less than 3 5/8" from door face (i.e., Von Duprin® 33, 98 and 99 series, ASSA ABLOY ACCENTRA™ 7000 series, Corbin Russwin® ED500 series)

No.	CTC	Material Size	Projection	Weight
R116EDPH	8 1/2"	3/8" x 1 1/2"	4 1/2"	3.7 lbs.

® VonDuprin 33, 98, and 99 series is a registered trademark of Ingersoll-Rand Company.

® ASSA ABLOY ACCENTRA™ 7000 series is a registered trademark of ASSA ABLOY.

® Corbin Russwin ED500 series is a registered trademark of Corbin Russwin, Inc.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.


## Vertical Rod Cover

The vertical rod cover (BFRC) is a sturdy channel made of .050" stainless steel (other finishes available) designed to fit over the vertical rod, protecting it from damage caused by carts, gurneys, etc. It is available in 12" and 24" lengths.

## Latch Guard Cover

The latch guard cover (BFLG) is made of .050" material and is designed with a 45° ramp, which when placed over the latch at the base of the door, deflects traffic safely away. It meets ADA requirements for a "smooth bottom door surface". The BFLG is available in 10", 12", and 16" lengths and most architectural finishes.

## Application




Application shown for products BFRC and BFLG. Protects vertical rod and latch of exit device. Meets ADA "smooth surface" requirements.



## Vertical Rod Covers No. BFRC12, BFRC24

**Material:** .050" brass, bronze, stainless steel  
**Finishes:** Available in standard architectural finishes (see page 9)  
**Fastener:** #6 x 5/8" OH SMS  
**Other:** Made to order sizes available

No.	Height	Width	Projection	Weight
BFRC12	12"	3 1/4"	1 5/8"	0.9 lbs.
BFRC24	24"	3 1/4"	1 5/8"	1.8 lbs.



## Latch Guard Covers No. BFLG10, BFLG12, BFLG16

**Material:** .050" stainless steel  
**Finishes:** Available in standard architectural finishes (see page 9)  
**Fastener:** #8 - 32 x 3/8" Pan Head MS; WS available on request  
**Ordering:** Specify handing  
**Other:** Made to order sizes available

No.	Height	Width	Projection	Weight
BFLG10	10"	6"	2 3/8"	1.6 lbs.
BFLG12	12"	6"	2 3/8"	1.9 lbs.
BFLG16	16"	6"	2 3/8"	2.5 lbs.



## Vertical Rod Latch Guard Cover No. BFLG1050

**Material:** .050" Stainless Steel  
**Finishes:** US32D and Stock PC's  
**Height:** 10"  
**Fastener:** #10x5/8" Self-Drilling Tek Screws  
**Backset:** Standard 2-3/4"  
**Ordering:** Please specify handing and width of door (push side)

Certified to the below Standards:

- ICC-500 (2020)
- FEMA Guideline 320 (2014)
- FEMA Guideline 361 (2021)

Part of windstorm assembly cards: ZHLA.47 and ZHLA.51

No.	Height	Width	Projection
BFLG1050	10"	Specify	2 3/8"

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

Rockwood custom strikes are manufactured to your specifications in almost any size, shape and finish. The drawings below represent standard ASA and T strikes. For easy and efficient ordering, please use the order form on the next page and fill in your requirements on drawing(s) and chart then fax or email us the form.

*NOTE: Any dimensions are possible. Contact us with your requirements.*

**Material:** .090" brass, bronze, stainless steel

**Finishes:** US3, US4, US10, US10B, US32D, US32


**Fastener:** CS-ASA: #12 WS or #12 - 24 MS.  
 CS-OM: #12 WS or #12 - 24 MS.  
 CS-T: #8 WS or #8 - 24 MS  
 590DA: #8 WS or #8 - 24 MS

**Bolt Hole:** Common sizes are:  $\frac{1}{16}$ " x  $\frac{1}{4}$ " and  $\frac{3}{4}$ " x  $\frac{1}{4}$ "; any size available


**Options:**

- .050", .062", or .125" thickness
- TORX - security Torx screws
- Finish on both sides
- Custom filler plates available
- Full lip


CS-ASA1




CS-ASA2




CS-OM



CS-T



590DA



**ROCKWOOD®**


**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
 Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.






## Corner Guards No. 290, 291

- Material:** .050" brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes (see page 9)
- Mounting:** Self-adhesive mounting
- Ordering:** Specify size
- Other:** Other lengths available up to 96", leg widths up to 6"

No.	Standard Sizes	Top Corners	Weight
290	2" x 2" x 40"	Square	2.4 lbs.
	2" x 2" x 48"		2.8 lbs.
	3" x 3" x 40"		3.5 lbs.
	3" x 3" x 48"		4.2 lbs.
291	2" x 2" x 40"	Rounded	2.4 lbs.
	2" x 2" x 48"		2.8 lbs.
	3" x 3" x 40"		3.5 lbs.
	3" x 3" x 48"		4.2 lbs.



## Corner Guards No. 295, 296

- Material:** .050" brass, bronze, stainless steel
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** #6 x 5/8" OH SMS
- Ordering:** Specify size
- Other:** Other lengths available up to 96", leg widths up to 6"

No.	Standard Sizes	Top Corners	Weight
295	2" x 2" x 40"	Square	2.4 lbs.
	2" x 2" x 48"		2.8 lbs.
	3" x 3" x 40"		3.5 lbs.
	3" x 3" x 48"		4.2 lbs.
296	2" x 2" x 40"	Rounded	2.4 lbs.
	2" x 2" x 48"		2.8 lbs.
	3" x 3" x 40"		3.5 lbs.
	3" x 3" x 48"		4.2 lbs.


**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog


Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Latch Protector No. 320-RKW

- Material:** .105" steel, stainless steel
- Finishes:** US2C (cadmium plated), US32D, and 10BE
- Fastener:**  $\frac{5}{16}$  - 18 carriage bolts and hex drive sex nuts
- Ordering:** Specify product number and finish
- Features:** Jamb pin prevents prying of door. Non-handed


No.	Material Size	Lock Type	Weight
320-RKW	3" x 11"	Cylindrical or mortise	1.2 lbs.



320C      320CL      320CXL

## Latch Protectors No. 320C, 320CL, 320CXL

- Material:** .090" steel, stainless steel
- Finishes:** US2C (cadmium plated), US32D, and 10BE
- Fastener:**  $\frac{5}{16}$  - 18 carriage bolts and hex drive sex nuts
- Ordering:** Specify product number and finish
- Features:** Jamb pin prevents prying of door. Non-handed
- No. 320C: Notched for  $2\frac{1}{8}$ " or less diameter rose on cylindrical lockset
- No. 320CL: Notched for  $2\frac{1}{4}$ " -  $3\frac{1}{4}$ " diameter rose on cylindrical lockset
- No. 320CXL: Notched for  $2\frac{1}{4}$ " -  $3\frac{3}{4}$ " diameter rose on cylindrical lockset



No.	Material Size	Lock Type	Weight
320C	3" x 11"	Cylindrical	1.2 lbs.
320CL	3" x 11"	Cylindrical	1.2 lbs.
320CXL	3" x 11"	Cylindrical	1.2 lbs.



## Latch Protector No. 321

- Material:** .105" steel, stainless steel
- Finishes:** US2C (cadmium plated), US32D, and 10BE
- Fastener:**  $\frac{5}{16}$  - 18 carriage bolts and hex drive sex nuts
- Ordering:** Specify product number and finish


No.	Material Size	Lock Type	Weight
321	$1\frac{1}{2}$ " x 10"	Mortise	0.7 lbs.



## Latch Protector No. 322

- Material:** .100" steel, stainless steel
- Finishes:** US2C (cadmium plated), US32D, and 10BE
- Fastener:**  $\frac{5}{16}$ " - 18 carriage bolts and hex drive sex nuts
- Ordering:** Specify product number and finish
- Features:** Compact size. Non-handed


No.	Material Size	Lock Type	Weight
322	$1\frac{5}{8}$ " x 6"	Cylindrical	5.6 oz.



## Cast Latch Protector No. 325

- Material:** .375" solid cast brass
- Finishes:** US26D
- Fastener:**  $\frac{1}{4}$ " - 20 thru bolts & finish washer
- Ordering:** Specify product number and finish
- Features:** Clean aesthetic design with no exposed fasteners

No.	Material Size	Lock Type	Weight
325	$1\frac{7}{8}$ " x $9\frac{1}{2}$ "	Mortise or cylindrical	1.1 lbs.



## Anti-Vandal Latch Protector No. 330

- Material:** .090" stainless steel
- Finishes:** US32D
- Fastener:** #8 x  $\frac{3}{4}$ " FH stainless steel combo screws
- Ordering:** Specify product number and finish
- Features:**
- Protects cylindrical locks from forced entry and vandalism
  - Fast and simple installation
  - Non-handed
  - Attractive appearance

No.	Material Size	Lock Type	Weight
330	$5\frac{3}{8}$ " x 6"	Cylindrical	1.8 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Solid Cast Wall Stops No. 400, 401, 402

**Material:** Cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:** Concealed mounting, convex bumper.

No.	Bumper	Fastener	Size	Projection	Weight
400	Convex	#6 x 1½" FH SMS, plastic toggle	2 <sup>7</sup> / <sub>16</sub> " dia.	1"	2 lbs./10
401	Convex	#8 x 1" RH WS, plastic anchor	2 <sup>7</sup> / <sub>16</sub> " dia.	1"	2 lbs./10
402	Convex	#8 - 32 x 1" TH MS, anchor	2 <sup>7</sup> / <sub>16</sub> " dia.	1"	2 lbs./10



## Solid Cast Wall Stops No. 403, 404, 405

**Material:** Cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:** Concealed mounting, concave bumper.

No.	Bumper	Fastener	Size	Projection	Weight
403	Concave	#6 - 1½" FH SMS, plastic toggle	2 <sup>7</sup> / <sub>16</sub> " dia.	1"	2 lbs./10
404	Concave	#8 x 1" RH WS, plastic anchor	2 <sup>7</sup> / <sub>16</sub> " dia.	1"	2 lbs./10
405	Concave	#8 - 32 x 1" TH MS, anchor	2 <sup>7</sup> / <sub>16</sub> " dia.	1"	2 lbs./10



## Wrought Wall Stops No. 406

**Material:** Wrought brass, bronze, and stainless steel with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- Concealed mounting, convex bumper. Back plate prevents damage to wall
- Accepted by the New York State Office of Mental Health (OMH) for use in high risk areas

No.	Bumper	Fastener	Size	Projection	Weight
406	Convex	#8 x 1¼" TH SMS, plastic toggle	2½" dia.	1"	1¼ lbs./10



## Wrought Wall Stops No. 409

**Material:** Wrought brass, bronze, and stainless steel with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- Concealed mounting, concave bumper. Back plate prevents damage to wall
- Accepted by the New York State Office of Mental Health (OMH) for use in high risk area

No.	Bumper	Fastener	Size	Projection	Weight
409	Concave	#8 x 1¼" TH SMS, plastic toggle	2½" dia.	1"	1¼ lbs./10



## Solid Cast Wall Stop No. 412

- Material:** Cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Features:** For where concealed mounting is not desired. School version
- Options:** Tamperproof Torx screws

No.	Bumper	Fastener	Size	Projection	Weight
412	Convex	#8 x 1 <sup>3</sup> / <sub>4</sub> " FH SMS	2 <sup>7</sup> / <sub>16</sub> " dia.	1"	3.5 lbs./10



## Solid Cast Wall Stop No. 415

- Material:** Cast brass with nylon bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Features:** Large size with flush back plate spreads impact of heavy or uncontrolled door contact – avoiding damage to wall. Universal screw pack is included for all wall conditions

No.	Bumper	Fastener	Size	Projection	Weight
415	Convex	1 - #8 - 32 x 2" RH MS and toggle bolt	4" dia.	<sup>3</sup> / <sub>4</sub> "	10 oz. each
		1 - #12 - 24 x 1 <sup>1</sup> / <sub>4</sub> " RH MS and anchor			
		3 - #8 x 1 <sup>1</sup> / <sub>4</sub> " FH SMS and plastic anchors			
		3 - #8 - 32 x 1 <sup>1</sup> / <sub>4</sub> " FH MS			



## Solid Cast Wall Stop No. 416

- Material:** Cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Features:** For use where concealed mounting is not desired. School version
- Options:** Tamperproof Torx screws

No.	Bumper	Fastener	Size	Projection	Weight
416	Concave	#8 x 1 <sup>3</sup> / <sub>4</sub> " FH SMS	2 <sup>7</sup> / <sub>16</sub> " dia.	1"	3.5 lbs./10

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Wrought Wall Stop No. 426

**Material:** Wrought brass and stainless steel with rubber bumper

**Finishes:** US32D, 10BE, Stock Powder Coats

**Other:** Concealed mounting

No.	Bumper	Fastener	Size	Projection	Weight
426	Concave	#8 x 1 <sup>1</sup> / <sub>4</sub> " TH SMS, plastic toggle and plastic anchor	1 <sup>7</sup> / <sub>8</sub> " dia.	1"	1 lbs./10



## Solid Cast Wall Stop No. 430-RKW

**Material:** Solid brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- Compact design for use on hotel bathroom doors swinging into the tub area, or where an inconspicuous bumper is desired.
- Concealed mounting

No.	Bumper	Fastener	Size	Projection	Weight
430-RKW	Convex	#6 x <sup>3</sup> / <sub>4</sub> " OH SMS, plastic anchor	1" dia	<sup>7</sup> / <sub>16</sub> "	0.5 lbs./10



## Wall Stop No. 431-RKW

**Material:** Gray rubber bumper

**Finishes:** Gray

**Features:** Economical bumper for applications where a completely concealed mounting is not required

No.	Bumper	Fastener	Size	Projection	Weight
431-RKW	Concave	#8 x 1 <sup>1</sup> / <sub>4</sub> " TH SMS, #8 flat washer, plastic toggle	1 <sup>9</sup> / <sub>16</sub> " dia.	<sup>15</sup> / <sub>16</sub> "	1.0 lbs./10



## Wall Stop No. 432W

**Material:** White rubber bumper

**Finishes:** White

**Features:**

- Economical
- Self-adhesive mounting

No.	Bumper	Fastener	Size	Projection	Weight
432W	Concave	Self-adhesive tape	1 <sup>9</sup> / <sub>16</sub> " dia.	<sup>3</sup> / <sub>4</sub> "	5 oz./10



## Low Dome Stops No. 440, 441

- Material:** Solid cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Other:** No. 441 is packed with both WS and MS fasteners
- Features:** For doors without thresholds (not undercut).
- Options:** Exterior pack screw packs, stainless steel plated to match — use EXP suffix (440 x EXP) when ordering.

No.	Fastener	Base	Height	Weight
440	#12 x 1 <sup>1</sup> / <sub>4</sub> " FH WS, plastic anchor	1 <sup>1</sup> / <sub>4</sub> " h x 1 <sup>7</sup> / <sub>8</sub> " dia.	1 <sup>1</sup> / <sub>8</sub> "	1.5 lbs./10
441	#12 x 1 <sup>1</sup> / <sub>2</sub> " FH WS, plastic anchor; #12 - 24 x 1 <sup>1</sup> / <sub>2</sub> " FH MS, anchor	1 <sup>1</sup> / <sub>4</sub> " h x 1 <sup>7</sup> / <sub>8</sub> " dia.	1 <sup>1</sup> / <sub>8</sub> "	2.1 lbs./10



## Dome Stop Combination Unit No. 441CU

- Material:** Solid cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Other:** Set consists of 1 each No. 441 and 1 each No. 444. For use at doors with or without a threshold
- Features:** Convertible for undercut or not undercut doors
- Options:** Exterior pack screw packs, stainless steel plated to match — use EXP suffix (441CU x EXP) when ordering

No.	Fastener	Base	Height	Weight
441CU	#12 x 1 <sup>1</sup> / <sub>2</sub> " FH WS, plastic anchor; #12 - 24 x 1 <sup>1</sup> / <sub>2</sub> " FH MS, anchor	Dome stop: 1 <sup>1</sup> / <sub>4</sub> " h x 1 <sup>7</sup> / <sub>8</sub> " dia. Riser: 3 <sup>3</sup> / <sub>8</sub> " h x 2" dia.	1 <sup>1</sup> / <sub>8</sub> " or 1 <sup>1</sup> / <sub>2</sub> "	1.85 lbs./10
444	Cast riser only	3 <sup>3</sup> / <sub>8</sub> " h x 1 <sup>3</sup> / <sub>4</sub> " dia.	3 <sup>3</sup> / <sub>8</sub> "	10 oz. /10

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Cast Universal Dome Stop No. 441H

- Material:** Solid cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Features:** Low lip dome stop with height of high dome stop, eliminates the need to determine requirement for traditional low or high dome stop – one stop for all applications. Integral cast pin for added strength. Universal screw pack included for all floor conditions
- Options:** Exterior pack screw packs, stainless steel plated to match – use EXP suffix (441H x EXP) when ordering.

No.	Fastener	Base	Height	Weight
441H	#12 x 1 <sup>1</sup> / <sub>4</sub> " FH WS, plastic anchor	<sup>7</sup> / <sub>32</sub> " h x 1 <sup>7</sup> / <sub>8</sub> " dia.	1 <sup>11</sup> / <sub>16</sub> "	3.2 lbs./10
	#12 - 24 x 1" FH MS, anchor			



## High Dome Stops No. 442, 443

- Material:** Solid cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Other:** No. 443 is packed with both WS and MS fasteners
- Features:** For doors with thresholds or undercut doors
- Options:** Exterior pack screw packs, stainless steel plated to match – use EXP suffix (442 x EXP) when ordering.

No.	Fastener	Base	Height	Weight
442	#12 x 1 <sup>1</sup> / <sub>2</sub> " FH WS, plastic anchor	<sup>1</sup> / <sub>2</sub> " h x 1 <sup>7</sup> / <sub>8</sub> " dia.	1 <sup>1</sup> / <sub>2</sub> "	2.8 lbs./10
443	#12 x 1 <sup>1</sup> / <sub>2</sub> " FH WS, plastic anchor; #12 - 24 x 1" FH MS, anchor	<sup>1</sup> / <sub>2</sub> " h x 1 <sup>7</sup> / <sub>8</sub> " dia.	1 <sup>5</sup> / <sub>16</sub> "	3.2 lbs./10



No. 445



No. 445H

## Heavy Duty Dome Stop No. 445, 445H

- Material:** Solid cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Features:** Extra heavy duty dome type stop for heavy and high frequency doors
- Options:** Exterior pack screw packs, stainless steel plated to match – use EXP suffix (445 x EXP) when ordering.

No.	Fastener	Base	Height	Weight
445	2 ea. #12 x 1 <sup>1</sup> / <sub>2</sub> " FH SMS, plastic anchor; #12 - 24 x 1" FH MS, anchor	2" x 4"	1 <sup>1</sup> / <sub>8</sub> "	4.6 lbs./10
445H	2 ea. #12 x 1 <sup>1</sup> / <sub>2</sub> " FH SMS, plastic anchor; #12 - 24 x 1" FH MS, anchor	2" x 4"	1 <sup>11</sup> / <sub>16</sub> "	6 lbs./10

**ROCKWOOD®**  
**ASSA ABLOY**



## Door Stop No. 446

- Material:** Brass with rubber bumper.
- Finishes:** Available in standard architectural finishes (see page 9).
- Features:** Modern style universal stop.
- Options:** Rubber bumper available in standard gray or optional black.


No.	Fastener	Base	Height	Weight
446	#12 x 1 1/2" WS, plastic anchor; #12 - 24 x 1" FH MS, anchor	1 1/4"	1 1/2"	0.5 lbs.



## Door Stop Riser No. 449

- Material:** Aluminum
- Finishes:** Mill aluminum or painted to match
- Ordering:** Specify finish and thickness; 1/4", 3/8", 1/2", 5/8", 3/4", 1"
- Other:** Full size carpet riser provides sturdy base for mounting the No. 440 or No. 442 dome stop


No.	Fastener	Base	Height	Weight
449	#12 WS, plastic anchor	1 7/8" dia.	As specified	1.6 lbs./10



## Curved Roller Stop No. 455

- Material:** Solid cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Features:** For use where doors swing into each other at odd angles

No.	Fastener	Base	Projection	Weight
455	3 ea. #8 x 3/4" OH SMS	1 5/8" x 2 1/4"	2 3/4"	5 lbs./10



## Straight Roller Stop No. 456-RKW

- Material:** Solid cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Features:** For use where doors swing into each other at right angles

No.	Fastener	Base	Projection	Weight
456-RKW	3 ea. #8 x 3/4" OH SMS	2" dia.	4 9/16"	4.1 lbs./10


**ROCKWOOD**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Straight Roller Stop No. 456L

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:** For use where doors swing into each other at right angles

No.	Fastener	Base	Projection	Weight
456L	3 ea. #8 x 3/4" OH SMS	2" dia.	6 1/4"	4.8 lbs./10



## Kick Down Door Stop No. 458

**Material:** Cast zinc with rubber bumper

**Finishes:** Available in bright brass (BRS), dull bronze (BRZ), and bright chrome plate (CRM)

**Features:**

- Uses replacement bumper No. 461B
- Rubber bumper provides reliable grip on floor.

No.	Fastener	Base	Projection	Weight
458	3 ea. #8 x 1" OH SMS	1 5/8" x 1 7/8"	4"	3.3 lbs./10



## Spring Loaded Plunger Stop No. 459

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- Uses replacement bumper No. 461B
- Foot operated, spring loaded
- Rubber bumper provides reliable grip on floor

No.	Fastener	Base	Projection	Weight
459	3 ea. #8 x 3/4" OH SMS	1 3/8" x 5 3/8"	1 7/8"	4.7 lbs./10



## Kick Down Door Stop No. 460

**Material:** Solid cast aluminum with rubber bumper

**Finishes:** Spray painted silver (ALM), brass (BRS), bronze (BRZ) or brown to match US10B (ORB)

**Features:**

- Uses replacement bumper No. 461B
- Rubber bumper provides reliable grip on floor.

No.	Fastener	Base	Projection	Weight
460	4 ea. #8 x 1" FH SMS	2 1/16" x 1 3/8"	4"	2.7 lbs./10



## Kick Down Door Stop No. 461

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)  
Rubber bumper available in gray or black

**Features:**

- Uses replacement bumper No. 461B
- Rubber bumper provides reliable grip on floor
- A unique assembly design that conceals the axle in the base

No.	Fastener	Base	Projection	Weight
461	4 ea. #8 x 3/4" OH SMS	2 1/4" x 1 1/4"	3 5/8"	5.1 lbs./10



## Kick Down Door Stop No. 461L

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9).  
Rubber bumper available in gray or black

**Features:**

- Uses replacement bumper No. 461B
- Rubber bumper provides reliable grip on floor
- A unique assembly design that conceals the axle in the base
- For use with doors up to 3" door-to-floor clearance

No.	Fastener	Base	Projection	Weight
461L	4 ea. #8 x 3/4" OH SMS	2 1/4" x 1 1/4"	5"	5.7 lbs./10

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Heavy Duty Door Stop No. 462

**Material:** Flame resistant high impact bumper  
**Finishes:** US2C  
**Mounting:** Drill 1" dia. x 2½" deep hole, fill with anchoring grout

No.	Diameter	Height	Mounting Bolt	Weight
462	2" dia.	x 1½" h	5⁄8" x 2½"	0.6 lbs.



## Heavy Duty Door Stop No. 463-RKW

**Material:** Flame resistant high impact bumper  
**Finishes:** US32D  
**Mounting:** Drill 1" dia. x 2½" deep hole, fill with anchoring grout  
**Other:** Replaceable bumper retained by security Torx MS

No.	Diameter	Height	Mounting Bolt	Weight
463-RKW	2" dia.	x 1¾" h	1⁄2" x 2½"	0.5 lbs.



## Heavy Duty Door Stop with Holder No. 464-RKW

**Material:** Cast brass and black rubber bumper  
**Finishes:** US26D  
**Mounting:** Body: 1 ea. ½ x 4½" lag bolt; 1 ea. shield;  
 2 ea. #8 x 1¼" FH SMS.  
 Cap: 1 ea. #8 - 32 x 3⁄8" RH MS  
**Features:** Offers maximum protection needed for heavily used doors.  
 Supplied with holder and catch

No.	Diameter	Height	Weight
464-RKW	3¼" dia.	x 3" h	1.8 lbs.



## Heavy Duty Door Stop No. 465

**Material:** Wrought brass and black rubber bumper  
**Finishes:** US26D  
**Mounting:** Body: 1 ea. ½ x 4½" lag bolt; 1 ea. shield.  
 Cap: 1 ea. #8 - 32 x 3⁄8" RH MS  
**Features:** Offers maximum protection needed for heavily used doors

No.	Diameter	Height	Weight
465	3¼" dia.	x 2⁵⁄8" h	1.3 lbs.



## Heavy Duty Door Stop No. 466-RKW

**Material:** Flame resistant molded rubber bumper

**Finishes:** Black

**Mounting:** Drill 1" dia. x 2½" deep hole, fill with anchoring grout

**Features:**

- Ideal for use in high vandalism or security areas
- No exposed fasteners

No.	Diameter	Height	Mounting Bolt	Weight
466-RKW	2" dia.	x 1½" h	5/8" x 2½"	0.6 lbs.



## Heavy Duty Door Stop No. 467-RKW

**Material:** Flame resistant molded rubber bumper

**Finishes:** Black

**Mounting:** Drill 1" dia. x 2½" deep hole, fill with anchoring grout

**Features:**

- Suitable for concrete floor or wall mounting
- Ideal for use in high vandalism or security areas
- No exposed fasteners
- Accepted by the New York State Office of Mental Health (OMH) for use in high risk areas

No.	Diameter	Height	Mounting Bolt	Weight
467-RKW	2" dia.	x 3½" h	5/8" x 2½"	0.9 lbs.



## Heavy Duty Door Stop No. 468-RKW

**Material:** Wrought stainless steel and black rubber bumper

**Finishes:** US32D

**Mounting:** Drill 1½" dia. x 7" deep hole, fill with anchoring grout

**Features:**

- Ideal for use in high vandalism or security area
- No exposed fasteners
- Accepted by the New York State Office of Mental Health (OMH) for use in high risk areas

No.	Diameter	Height	Mounting Bolt	Weight
468-RKW	2" dia.	x 3" h	1" x 7"	2.6 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



No. 471

## Door Stops No. 470, 471

**Material:** Cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Options:** Exterior pack screw packs, stainless steel plated to match – use EXP suffix (470 x EXP) when ordering

*Note: 470 features three fastener holes, 471 features one*

No.	Fastener	Base	Height	Weight
470	3 ea. #12 x 1 1/4" FH WS; 3 ea. plastic anchors	2 1/2" dia.	3"	0.7 lbs.
471	1 ea. 5/16 - 18 x 1 3/4" stud, anchor; #8 x 3/4" OH SMS, plastic anchor	2 1/2" dia.	3"	0.7 lbs.



No. 473

## Door Stops with Keepers No. 472, 473

**Material:** Cast brass with rubber bumper


**Finishes:** Available in standard architectural finishes (see page 9)

**Other:** Keeper size 1" w x 1 3/4" h

**Options:** Exterior pack screw packs, stainless steel plated to match – use EXP suffix (472 x EXP) when ordering

*Note: 472 features three fastener holes, 473 features one*

No.	Fastener	Base	Height	Weight
472	3 ea. #12 x 1 1/4" FH WS; 3 ea. plastic anchors Keeper: 2 ea. #12 x 1 1/4" FH WS; 2 ea. plastic anchors	2 1/2" dia.	3 3/4"	0.9 lbs.
473	5/16 - 18 x 1 3/4" stud, anchor; #8 x 3/4" OH SMS, plastic anchor Keeper: 2 ea. #12 x 1 1/4" FH WS; 2 ea. plastic anchors	2 1/2" dia.	3 3/4"	0.9 lbs.



No. 474


## Door Stops No. 474, 475

**Material:** Cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

*Note: 474 features three fastener holes, 475 features one*

No.	Fastener	Base	Projection	Weight
474	3 ea. #12 x 1 1/4" FH WS, 3 ea. plastic anchors	2 1/4" dia.	3 3/4"	0.6 lbs.
475	1 ea. 5/16 - 18 x 1 3/4" stud, anchor; #8 x 3/4" OH SMS, plastic anchor	2 1/4" dia.	3 3/4"	0.6 lbs.



No. 476

## Door Stops with Keepers No. 476, 477

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Other:** Keeper size 1" w x 1<sup>3</sup>/<sub>4</sub>" h

*Note: 476 features three fastener holes, 477 features one*

No.	Fastener	Base	Projection	Weight
476	3 ea. #12 x 1 <sup>1</sup> / <sub>4</sub> " FH WS, 3 ea. plastic anchors Keeper: 2 ea. #12 x 1 <sup>1</sup> / <sub>4</sub> " FH WS; 2 ea. plastic anchors	2 <sup>1</sup> / <sub>4</sub> " dia.	3 <sup>3</sup> / <sub>4</sub> "	0.8 lbs.
477	1 <sup>5</sup> / <sub>16</sub> " - 18 x 1 <sup>3</sup> / <sub>4</sub> " stud, anchor; #8 x 3 <sup>3</sup> / <sub>4</sub> " OH SMS, plastic anchor Keeper: 2 ea. #12 x 1 <sup>1</sup> / <sub>4</sub> " FH WS; 2 ea. plastic anchors	2 <sup>1</sup> / <sub>4</sub> " dia.	3 <sup>3</sup> / <sub>4</sub> "	0.8 lbs.



## Door Stops No. 480

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- Uses replacement bumper 461B
- Heavy duty and ideal for use on heavy doors or in high traffic areas

**Options:**

- Rubber bumper available in standard gray or optional black
- Exterior pack screw packs, stainless steel plated to match — use EXP suffix (480 x EXP) when ordering

No.	Fastener	Base	Height	Weight
480	3 ea. #12 - 24 x 1 <sup>1</sup> / <sub>4</sub> " FH WS, 3 ea Plastic Anchors	2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "	1 <sup>5</sup> / <sub>8</sub> "	4.6 lbs./10



## Door Stops No. 480H

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- Uses replacement bumper 461B
- Heavy duty and ideal for use on heavy doors or in high traffic areas

**Options:**

- Rubber bumper available in standard gray or optional black
- Exterior pack screw packs, stainless steel plated to match — use EXP suffix (480H x EXP) when ordering

No.	Fastener	Base	Height	Weight
480H	3 ea #12 x 1 <sup>1</sup> / <sub>4</sub> " FH WS, 3 ea. Plastic Anchors	2 <sup>1</sup> / <sub>2</sub> " x 1 <sup>3</sup> / <sub>4</sub> "	2 <sup>1</sup> / <sub>4</sub> "	6.2 lbs./10

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Door Stops No. 481

- Material:** Solid cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Features:**
- Uses replacement bumper 461B
  - Heavy duty and ideal for use on heavy doors or in high traffic areas
- Options:**
- Rubber bumper available in standard gray or optional black
  - Exterior pack screw packs, stainless steel plated to match – use EXP suffix (481 x EXP) when ordering

No.	Fastener	Base	Height	Weight
481	3 ea. #12 - 24 x 1" FH MS, 3 ea. anchors	2 1/2" x 1 3/4"	1 5/8"	5.8 lbs./10



## Door Stops No. 481H

- Material:** Solid cast brass with rubber bumper
- Finishes:** Available in standard architectural finishes (see page 9)
- Features:**
- Uses replacement bumper 461B
  - Heavy duty and ideal for use on heavy doors or in high traffic areas
- Options:**
- Rubber bumper available in standard gray or optional black
  - Exterior pack screw packs, stainless steel plated to match – use EXP suffix (481H x EXP) when ordering

No.	Fastener	Base	Height	Weight
481H	3 ea. #12 - 24 x 1" FH MS, 3 ea. anchors	2 1/2" x 1 3/4"	2 1/4"	7.2 lbs./10



## Heavy Duty Mounting Plate No. 481MP

- Material:** Aluminum and steel
- Finishes:** Powder coat to match stop finish
- Features:** 3/8" aluminum base plate for securely anchoring 481 or 481H door stops in heavy use areas
- Requires 3 1/2" diameter hole 3 1/2" deep. Fill with quick drying cement and set anchor plate flush to finished floor with hole pattern at appropriate location for door stop to interface with door surface

No.	Fastener	Base	Height	Weight
481MP	None	3" dia	Flush to floor	4.5 lbs./10



## Door Stop No. 482

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- Uses replacement bumper 461B
- Heavy duty and ideal for use on heavy doors or in high traffic areas

**Options:**

- Rubber bumper available in standard gray or optional black.
- Exterior pack screw packs, stainless steel plated to match – use EXP suffix (482 x EXP) when ordering.

No.	Fastener	Base	Height	Weight
482	$\frac{5}{16}$ - 18 x $1\frac{3}{4}$ " stud, anchor; #12 x $1\frac{1}{4}$ " FH WS, plastic anchor	$1\frac{1}{2}$ " x $2\frac{1}{2}$ "	$2\frac{1}{8}$ "	6.5 lbs./10



## Door Stop No. 483

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- Uses replacement bumper 461B
- Heavy duty and ideal for use on heavy doors or in high traffic areas

**Options:**

- Rubber bumper available in standard gray or optional black.
- Exterior pack screw packs, stainless steel plated to match – use EXP suffix (483 x EXP) when ordering.

No.	Fastener	Base	Height	Weight
483	$\frac{5}{16}$ - 18 x $1\frac{3}{4}$ " stud, anchor; #12 x $1\frac{1}{4}$ " FH WS, plastic anchor	$1\frac{5}{8}$ " x $2\frac{5}{8}$ "	$2\frac{3}{4}$ "	6.7 lbs./10



## Door Stop with Keeper No. 485

**Material:** Solid cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- Uses replacement bumper 461B
- Heavy duty and ideal for use on heavy doors or in high traffic areas

**Options:**

- Rubber bumper available in standard gray or optional black
- Exterior pack screw packs, stainless steel plated to match – use EXP suffix (485 x EXP) when ordering

No.	Fastener	Base	Height	Weight
485	$\frac{5}{16}$ - 18 x $1\frac{3}{4}$ " stud, anchor; #12 x $1\frac{1}{4}$ " FH WS, plastic anchor Keeper: 2 ea. #10 x 1" FH SMS	$1\frac{5}{8}$ " x $2\frac{5}{8}$ "  1" x 2"	3"	7.8 lbs./10

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Angle Door Stop No. 486

**Material:** Steel with rubber bumper

**Finishes:** US2C

**Features:** For undercut doors up to 1½"

No.	Fastener	Base	Height	Weight
486	2 ea. #12 x 1½" FH SMS, 2 ea. plastic anchors	1" x 2½"	2 <sup>5</sup> / <sub>8</sub> "	4 lbs./10




## Heavy Duty Wall Stop No. 487

**Material:** Solid cast brass with rubber bumper

**Finishes:** US26D

**Features:** Sloping design resists vandalism

No.	Fastener	Base	Projection	Weight
487	3 ea. #10 x 1" FH SMS, 3 ea. plastic anchors	2¼" x 3"	3¾"	0.8 lbs.




## Door Stop No. 488

**Material:** Solid brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:** For single doors

No.	Fastener	Base	Height	Weight
488	2 ea. #12 x 1½" FH WS, 2 ea. plastic anchors; 2 ea. #12 - 24 x 1" FH MS	1½" x 2"	1"	2.2 lbs./10




## Door Stop No. 489

**Material:** Solid brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:** For single or pair of doors

No.	Fastener	Base	Height	Weight
489	4 ea. #12 x 1½" FH WS, 4 ea. plastic anchors; 4 ea. #12 - 24 x 1" FH MS	3" x 2"	1"	4.1 lbs./10



## Door Holder with Stop No. 490

**Material:** Cast brass  
**Finishes:** US26D  
**Other:** Holder base: 2<sup>3</sup>/<sub>4</sub>" w x 2<sup>1</sup>/<sub>2</sub>" h  
 Holder projection: 2<sup>1</sup>/<sub>8</sub>"  
 Strike base: 1" w x 2" h  
 Strike projection: 2"

No.	Fastener	Weight
490	5 ea. #10 x 1" OH SMS, 3 ea. plastic anchors; 3 ea. #10 - 24 x 1 <sup>1</sup> / <sub>4</sub> " FH MS	0.8 lbs.




## Automatic Door Holder with Stop No. 491-RKW, 491R, 491S

**Material:** Cast brass  
**Finishes:** Available in standard architectural finishes (see page 9)  
**Other:** Holder base: 3" w x 3<sup>3</sup>/<sub>8</sub>" h  
 Holder projection: 2<sup>1</sup>/<sub>8</sub>"  
 Strike base: 4" w x 2" h  
 Strike projection: 1<sup>1</sup>/<sub>4</sub>"

**Options:** Strike risers available for larger clearances

**Features:**

- For applications requiring door hold-open on a frequent basis
- Screw hole design allows for precise alignment and then permanent attachment



No.	Fastener	Strike	Clearance	Weight
491-RKW	Strike: 3 ea. #12 x 1 <sup>1</sup> / <sub>4</sub> " FH WS, 3 ea. plastic anchors Body: 4 ea. #10 x 1 <sup>1</sup> / <sub>4</sub> " FH WS	Floor	1/2" or less door to floor	1.5 lbs.
491R	Strike: 3 ea. 12 - 24 x 1" FH MS, 3 ea. anchors Body: 4 ea. #10 x 1 <sup>1</sup> / <sub>4</sub> " FH WS	Floor	1/2" or less door to floor	1.5 lbs.
491S	Strike: 3 ea. 12 - 24 x 1" FH MS, 3 anchors Body: 4 ea. 10 - 24 x 1" FH MS; 4 ea. 10 - 24 x 1 <sup>3</sup> / <sub>8</sub> " sex bolt	Floor	1/2" or less door to floor	1.5 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Automatic Door Holder with Stop No. 494-RKW, 494R, 494S

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Other:** Holder base: 3" w x 3<sup>3</sup>/<sub>8</sub>" h  
Holder projection: 2<sup>1</sup>/<sub>8</sub>"  
Strike base: 2" w x 3" h  
Strike projection: 3<sup>1</sup>/<sub>4</sub>"

**Features:**

- For applications requiring door-hold-open on a frequent basis
- Screw hole design allows for precise alignment and then permanent attachment

No.	Fastener	Strike	Clearance	Weight
494-RKW	Strike: 3 ea. #12 x 1 <sup>1</sup> / <sub>4</sub> " FH WS, 3 ea. plastic anchors Body: 4 ea. #10 x 1 <sup>1</sup> / <sub>4</sub> " FH WS	Wall	3 <sup>3</sup> / <sub>4</sub> " wall to door	1.7 lbs.
494R	Strike: 3 ea. #12 - 24 x 1" FH MS, 3 ea. anchors Body: 4 ea. #10 x 1 <sup>1</sup> / <sub>4</sub> " FH WS	Wall	3 <sup>3</sup> / <sub>4</sub> " wall to door	1.7 lbs.
494S	Strike: 3 ea. #12 - 24 x 1" FH MS, 3 ea. anchors Body: 4 ea. #10 - 24 x 1" FH MS; 4 ea. #10 - 24 x 1 <sup>3</sup> / <sub>8</sub> " sex bolt	Wall	3 <sup>3</sup> / <sub>4</sub> " wall to door	1.7 lbs.

*NOTE: 494-RKW can be used as Foot Pull and Holder, see page B35.*



## Concealed Magnetic Door Stop No. 495

**Material:** Brass, Low Carbon Steel, Stainless Steel and Polycarbonate with Magnet

**Finishes:** US26D, Black, Clear

**Features:**

- Fully concealed magnetic door stop that includes a hold-open function.
- Concealed magnet technology ensures exceptional mechanical functionality.

No.	Fastener	Door Stop Overall	Weight	Material Size
495	2 ea #8 x 1" Stainless Steel Screws	1 <sup>13</sup> / <sub>16</sub> "	.37 lbs.	Magnet: 1 <sup>9</sup> / <sub>32</sub> " x Ø 1 <sup>5</sup> / <sub>16</sub> " Strike Plate: 1 <sup>15</sup> / <sub>16</sub> " x 3 <sup>5</sup> / <sub>32</sub> " Pin: 1-3/4" x Ø 3/8" Floor Insert: 1 <sup>11</sup> / <sub>16</sub> " x Ø 1 <sup>3</sup> / <sub>32</sub> "

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world



## Door Stops No. 505-RKW, 508

**Material:** Cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9).

**Options:** Rubber bumper available in standard white or optional gray and black

No.	Fastener	Base	Projection	Weight
505-RKW	#10 - 24 x 1/4" hanger bolt	1" dia.	3 1/8"	1.6 lbs./10
508	#10 - 24 x 1/4" hanger bolt	1" dia.	4 3/16"	2.2 lbs./10



## Aluminum Door Stop No. 517

**Material:** Cast aluminum with rubber bumper

**Finishes:** Bright brass (BRS) and burnished aluminum (ALM)

**Options:** Rubber bumper available in standard white or optional gray and black

No.	Fastener	Base	Projection	Weight
517	2 ea. #8 x 3/4" OH SMS	1 1/2" dia.	3 3/4"	1.1 lbs./10



## Door Stop No. 518

**Material:** Cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Options:** Rubber bumper available in standard white or optional gray and black

No.	Fastener	Base	Projection	Weight
518	2 ea. #8 x 3/4" OH SMS	1 1/2" dia.	3 3/4"	1.9 lbs./10



## Door Stop No. 519

**Material:** Cast brass with rubber bumper

**Finishes:** Available in standard architectural finishes (see page 9)

**Options:** Rubber bumper available in standard white or optional gray and black

No.	Fastener	Base	Projection	Weight
519	#10 - 24 x 1/4" hanger bolt	1 1/4" dia.	3 1/4"	1.7 lbs./10



## Replacement Bumper No. 520

**Material:** Rubber bumper

**Weight:** 0.7 lbs./10.

**Other:** Bumper replacement for No. 505, 508, 517, 518, 519.

**Options:** Available in standard white or optional gray and black.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Spring Base Door Stop No. 525

- Material:** Spring steel
- Finishes:** Antique brass (ANT) with White bumper, bright brass (BRS) with White bumper, bright nickel (NP) with White bumper, black (BLK) with Black bumper
- Features:** Heavy spring construction for durable wear

No.	Fastener	Base	Projection	Weight
525	6 x 3/4" SMS	1" dia.	3"	0.7 lbs./10



## Spring Base Door Stop No. 526

- Material:** Spring steel
- Spring Finishes:** Bright brass (BRS), bright nickel (NP)
- Rubber bumper color:** White
- Features:** Heavy spring construction for durable wear

No.	Fastener	Base	Projection	Weight
526	6 x 3/4" SMS	1" dia.	4"	0.8 lbs./10



## Heavy Duty Hinge Pin Stop No. 528

- Material:** Wrought steel with rubber bumpers
- Finishes:** Antique brass (ANT), bright brass (BRS), bright nickel (NP)
- Features:**
- Positive slip proof adjustment
  - Heavy wrought steel construction works with both 1/4" and 5/16" hinge pins

No.	Door Opening Adjustment	Weight
528	70° to 100°	1.3 lbs./10

## Introduction to Overhead Stops & Holders

Rockwood Overhead Stops and Holders are used to extend the life of the door, frame and any door closing devices. They may be necessary if there are strong winds, high traffic or abuse.

- When used in conjunction with a floor closer, you have absolute door control, top and bottom.
- Provides positive deadstop at selected degree
- There are 2 functions, 3 ways to order:
  - Hold Open** – door remains held open near deadstop location
  - Stops** – door deadstops at a particular degree of opening
  - Multi Function** – adaptable as hold open and/or stops
- Available as surface mounted or concealed
- Standard mount on push side of door (See model descriptions for pull side installations)
- Thru bolts are furnished with all surface models and must be used for installation


**WARNING: HOLD OPEN FUNCTION CANNOT BE USED ON LABELED OPENINGS!**

### To Convert from Hold Open to Stop Function:

1. Remove the plastic end cap (#1) at the spring end of the channel.
2. With  $\frac{3}{16}$ " hex key wrench, loosen the set screw in shock block.
3. Remove the shock block plate and the hold open spring from channel.
4. Remove the hold open spring from the shock block.
5. Replace the shock block and block plate into channel.
6. Replace the plastic end cap.
7. Install unit on door.
8. Adjust to desired opening and tighten set screw.

### To Select Degree of Stop (Hold Open Models):

1. Engage door in hold open position.
2. Using a  $\frac{3}{16}$ " hex wrench, loosen the set screw in the shock block.
3. Open door to desired degree of opening.
4. Tighten set screw.
5. Verify door opening position and re-adjust, if needed.



**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Heavy Duty Concealed OH100 Series

**Material:** Stainless steel

**Finishes:** US32D, 10BE

**Fasteners:** Jamb:  $\frac{1}{4}$  -20 x  $\frac{3}{4}$ " FH MS or #14 x  $1\frac{1}{2}$ " FH WS  
Door:  $\frac{5}{16}$ -18 x  $1\frac{1}{2}$ " FH MS or #18 x 3" FH WS

- Features:**
- Doors may be single or double acting
  - Non-handed
  - Slide track design
  - Recommended for high traffic, heavy abuse installations
  - Heavy shock absorber spring provides 5-7° compression before deadstop
  - Surface on/off knob on hold open models
  - Complete screw packet for installation in wood and machine screws for door and frame
  - For security areas, Torx® screws available for exposed fasteners.
  - Durable slider cam and shock block
  - 110° maximum opening
  - $\frac{3}{4}$ " minimum door thickness, for thicker doors, note thickness when ordering
  - $\frac{1}{16}$ " square channel
  - Stop function UL listed for fire door assemblies

No.	Function	Door Opening		Weight
		Butts/Offset Pivots	Center Hung	
OH101H	Hold open	24" - 28"	-	4.5 lbs.
OH102H	Hold open	28 $\frac{1}{16}$ " - 33"	30" - 36"	4.5 lbs.
OH103H	Hold open	33 $\frac{1}{16}$ " - 38"	36 $\frac{1}{16}$ " - 41"	4.5 lbs.
OH104H	Hold open	38 $\frac{1}{16}$ " - 43"	41 $\frac{1}{16}$ " - 46"	4.5 lbs.
OH105H	Hold open	43 $\frac{1}{16}$ " - 48"	46 $\frac{1}{16}$ " - 50"	4.5 lbs.
OH101S	Stop only	24" - 28"	-	4.5 lbs.
OH102S	Stop only	28 $\frac{1}{16}$ " - 33"	30" - 36"	4.5 lbs.
OH103S	Stop only	33 $\frac{1}{16}$ " - 38"	36 $\frac{1}{16}$ " - 41"	4.5 lbs.
OH104S	Stop only	38 $\frac{1}{16}$ " - 43"	41 $\frac{1}{16}$ " - 46"	4.5 lbs.
OH105S	Stop only	43 $\frac{1}{16}$ " - 48"	46 $\frac{1}{16}$ " - 50"	4.5 lbs.

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)

Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world



## Standard Duty Concealed OH200 Series

**Material:** Stainless steel

**Finishes:** US32D, 10BE

**Fasteners:** Jamb: #12-24 x 1/2" FH MS or #12 x 1 1/2" FH WS  
Door: #12-24 x 1 1/2" FH MS or #12 x 1 1/2" FH WS

- Features:**
- Doors may be single or double acting
  - Non-handed
  - Slide track design
  - Recommended for medium traffic, medium weight doors
  - Degree of opening is fully adjustable and can be adapted to changing needs
  - Heavy shock absorber spring provides 5-7° compression before deadstop
  - Multi-function unit is shipped as a stop. Can be converted to a hold open or friction in the field. MF5012 KIT (Adapter kit) included
  - Complete screw packet kit for installation in wood or metal door and frame
  - For security areas, Torx® screws available for exposed fasteners, but heavy-duty units should be considered for high security applications
  - Durable slider cam and shock block
  - 110° maximum opening
  - 3/4" square channel
  - Stop function UL listed for fire door assemblies

No.	Function	Door Opening		Weight
		Butts/Offset Pivots	Center Hung	
OH201M	Multi-function	18" - 24"	-	3.5 lbs.
OH202M	Multi-function	24 1/16" - 30"	27" - 32"	3.5 lbs.
OH203M	Multi-function	30 1/16" - 36"	32 1/16" - 38 1/2"	3.5 lbs.
OH204M	Multi-function	36 1/16" - 42"	38 9/16" - 45"	3.5 lbs.
OH205M	Multi-function	42 1/16" - 48"	45 1/16" - 48"	3.5 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Heavy Duty Surface Mounted OH900 Series

**Material:** Stainless steel

**Finishes:** US32D, 10BE

**Fasteners:** Jamb:  $\frac{1}{4}$ " -20 x  $\frac{3}{4}$ " FH MS or #14 x  $1\frac{1}{2}$ " FH WS  
Door:  $\frac{5}{16}$ "-18 x 2" FH MS and  $\frac{1}{2}$ " dia. sex bolt

- Features:**
- Doors are single acting
  - Non-handed
  - Slide track design
  - Recommended for high traffic, heavy abuse installations
  - Heavy shock absorber spring provides 5-7° compression before deadstop
  - On/off knob on hold open models
  - Complete screw packet with thru-bolts for door, wood and machine screws for frame
  - Torx® screws optional for security applications
  - Durable slider cam and shock block
  - 110° maximum opening
  - $1\frac{3}{4}$ " minimum door thickness
  - $1\frac{3}{16}$ " square channel
  - Stop function UL listed for fire door assemblies
  - For pull side mounting or flush mounting on push side or for rabbeted push side use angle jamb bracket adapter AJB900LH or AJB900RH

No.	Function	Door Opening		Weight
		Butts/Offset Pivots	Center Hung	
OH901H	Hold open	24" - 28"	-	4.5 lbs.
OH902H	Hold open	28 $\frac{1}{16}$ " - 33"	30" - 36"	4.5 lbs.
OH903H	Hold open	33 $\frac{1}{16}$ " - 38"	36 $\frac{1}{16}$ " - 41"	4.5 lbs.
OH904H	Hold open	38 $\frac{1}{16}$ " - 43"	41 $\frac{1}{16}$ " - 46"	4.5 lbs.
OH905H	Hold open	43 $\frac{1}{16}$ " - 48"	46 $\frac{1}{16}$ " - 50"	4.5 lbs.
OH901S	Stop only	24" - 28"	-	4.5 lbs.
OH902S	Stop only	28 $\frac{1}{16}$ " - 33"	30" - 36"	4.5 lbs.
OH903S	Stop only	33 $\frac{1}{16}$ " - 38"	36 $\frac{1}{16}$ " - 41"	4.5 lbs.
OH904S	Stop only	38 $\frac{1}{16}$ " - 43"	41 $\frac{1}{16}$ " - 46"	4.5 lbs.
OH905S	Stop only	43 $\frac{1}{16}$ " - 48"	46 $\frac{1}{16}$ " - 50"	4.5 lbs.

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)


Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world



## Standard Duty Surface Mounted OH1000 Series

**Material:** Stainless steel

**Finishes:** US32D, 10BE

**Fasteners:** Jamb: #12 x 1½" FH WS or #12-24 x ½" FH MS  
Door: #12-24 x 1½" FH MS and 5/16" dia. sex bolt

- Features:**
- Single acting doors
  - Non-handed
  - Slide track design
  - Recommended for medium traffic, medium weight doors
  - Degree of opening fully adjustable and can be adapted to changing needs
  - Heavy shock absorber spring provides compression before deadstop
  - Multi-function unit is shipped as a stop. Can be converted to a hold open or friction in field. MF5012 KIT (Adapter kit) included
  - Complete screw packet with thru-bolts for door, wood and machine screws for frame
  - Torx® screws optional for security applications, but heavy-duty units should be considered for high-security applications
  - Durable slider cam and shock block
  - 110° maximum opening
  - ¾" square channel
  - Stop function UL listed for fire door assemblies
  - For pull side mounting or flush and rabbeted mounting on push side use angle jamb bracket adapter JB1000

### Door Opening

No.	Function	Butts/Offset Pivots	Center Hung	Weight
OH1001M	Multi-function	18" - 24"	21" - 26½"	3.5 lbs.
OH1002M	Multi-function	24½" - 30"	26⅞" - 32"	3.5 lbs.
OH1003M	Multi-function	30½" - 36"	32½" - 38"	3.5 lbs.
OH1004M	Multi-function	36½" - 42"	38½" - 45"	3.5 lbs.
OH1005M	Multi-function	42½" - 48"	45½" - 48"	3.5 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Lever Extension Flush Bolt No. 550

**Material:** Brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 8 ea. #8 x 3/4" FH combo screws

**Features:**

- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 10'h rated up to and including 3 Hours
- 3/4" bolt throw, 3/4" rod backset
- 12" rod length (center of face to bolt end - retracted)
- 1 1/2" adjustable bolt head

**Options:**

- Other size rods available are 18", 24", 36", 48"
- Use No. 570 Dust Proof Strike (shown on page E4) to prevent dirt blocking bottom strike

No.	Size	Weight
550	Face plate: 1 1/4" x 6 3/4" Strike: 15/16" x 2 1/4" Guide: 1" x 2"	1.7 lbs./2



## Rabbit Piece No. 554


**Material:** Brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 2 ea. #8 x 1 1/4" FH WS

**Other:** For use on rabbeted doors to fill mortise cut

No.	Size	Weight
554	1/2" x 6 3/4"	1.5 lbs./10



554G

554S

## Rabbit Guides No. 554G, 554S

**Material:** Brass

**Finishes:** Brass

**Fastener:** 2 ea. #6 x 3/4" FH combo screws

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world



## Lever Extension Flush Bolt No. 555

- Material:** Brass
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** 8 ea. #8 x 3/4" FH combo screws
- Features:**
- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 10'h rated up to and including 3 Hours
  - Fits ANSI A115 door and frame preparation
  - 3/4" bolt throw, 3/4" rod backset
  - 12" rod length (center of face to bolt end - retracted)
  - 1 1/2" adjustable bolt head
- Options:**
- Other size rods available are 18", 24", 36", 48"
  - Extra long bolt head - 2 1/2" (or to your specification)
  - Use No. 570 Dust Proof Strike (shown on page E4) to prevent dirt blocking bottom strike

No.	Size	Weight
555	Face plate: 1" x 6 3/4" Strike: 1 5/16" x 2 1/4" Guide: 1" x 2"	1.5 lbs./2



## Lever Extension Flush Bolt with Bottom Fire Bolt No. 555 x 18BFB

- Material:** Flush bolt – brass  
Bottom fire bolt – stainless steel
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** 8 ea. #8 x 3/4" FH combo screws
- Features:**
- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 9'h rated up to and including 3 Hours
  - Fits ANSI A115 door and frame preparation
  - 3/4" bolt throw, 3/4" rod backset
  - 12" rod length (center of face to bolt end - retracted)
  - 1 1/2" adjustable bolt head
  - When door is subjected to 230° F the plug and black plastic cover will melt allowing the bolt to project, locking the leaves together
  - Bottom fire bolt eliminates need for floor prep.
  - Oversize fire bolt strike hole allows for slight door misalignment
- Options:**
- Other size rods available are 18", 24", 36", 48"
  - Extra long bolt head - 2 1/2" (or to your specification)

No.	Size	Weight
555 x 18BFB	Top bolt: 1" x 6 3/4" Bottom bolt: 1 3/16" dia.	0.9 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | www.rockwoodmfg.com  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Lever Extension Flush Bolt No. 556WS Windstorm

The Rockwood 556WS Flush Bolt is part of a UL certified assembly from ASSA ABLOY. Listed for use on both in-swing or out-swing paired applications, the full assembly includes doors from Ceco Door, Curries or Fleming and latching hardware from Corbin Russwin, SARGENT or ASSA ABLOY ACCENTRA™.

**Material:** Brass and Stainless Steel


**Finishes:** 26D

**Fastener:** 8 ea. #8 - 32 x 1/4" FH MS in Stainless Steel

**Features:**

- 3/4" bolt throw, 3/4" rod backset
- 12" Stainless Steel rod length (center of face to bolt end - retracted).
- UL Certified
- Tested to ASTM E330, E1886, E1996 and the TAS 201, 202, and 203. Assembly approved for use in the state of Florida including the High Velocity Hurricane Zone (HVHZ)

No.	Size	Material	Weight
556WS	Face plate: 1" x 6 <sup>3</sup> / <sub>4</sub> " x 1/8"	Brass	2.5 lbs.
	Mortise Body 1" x 5 <sup>1</sup> / <sub>4</sub> " x 1 <sup>3</sup> / <sub>8</sub> "	Brass	
	Rod 12" x 1/2"D	Stainless Steel	
	Strike: 1 <sup>5</sup> / <sub>16</sub> " x 2 <sup>1</sup> / <sub>4</sub> "	Stainless Steel	
	Guide: 1" x 2"	Stainless Steel	



## Lever Extension Flush Bolt No. 557

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:**

- 7 ea. #8 x 3/4" FH combo screws
- 4 ea. #8 - 32 x 1/2" FH MS
- 4 ea. #8 counter sunk washer

**Features:**

- For Fire Rated Plastic & Wood Covered Doors measuring up to 4'w x 10'h rated up to and including 1 1/2 Hours
- 3/4" bolt throw, 3/4" backset; door strength maintained by corner reinforcing plate

**Options:** Use No. 570 Dust Proof Strike (shown on page E4) to prevent dirt blocking bottom strike

No.	Size	Weight
557	Face plate: 1" x 6 <sup>3</sup> / <sub>4</sub> " Strike: 1 <sup>5</sup> / <sub>16</sub> " x 2 <sup>1</sup> / <sub>4</sub> "	1.7 lbs.



800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world



## Lever Extension Flush Bolt With Bottom Fire Bolt No. 557 x 19BFB

**Material:** Flush bolt – brass  
Bottom fire bolt – stainless steel

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 7 ea. #8 x 3/4" FH combo screws  
4 ea. #8 – 32 x 1/2" FH MS  
4 ea. #8 counter sunk washer

**Features:**

- For Fire Rated Plastic & Wood Covered Fire Doors measuring up to 4'w x 9'h rated up to 20 minutes
- 3/4" bolt throw, 3/4" backset; door strength maintained by corner reinforcing plate
- When door is subjected to 230°F the plug and black plastic cover will melt allowing the bolt to project, locking the leaves together
- Bottom fire bolt eliminates need for floor prep
- Oversize fire bolt strike hole allows for slight door misalignment

No.	Size	Weight
557 x 19BFB	Top bolt: 1" x 6 3/4" Bottom bolt: 1 3/16" dia.	0.9 lbs.



## Dust Proof Strike No. 570

**Material:** Brass


**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** Adjustment nut  
Spanner wrench  
2 ea. #8 x 1 OH SMS, 2 ea. plastic anchors  
2 ea. #8 – 32 x 3/4" OH MS, 2 ea. anchors

**Features:**

- Works with all Rockwood manual and automatic flush bolts
- Removable face plate for use with thresholds
- Adjustable height for carpeted areas

No.	Size	Weight
570	Face plate: 1 3/8" x 2 7/8" Barrel: 3/4" dia. x 2" depth	0.4 lbs.



## Gravity Door Coordinator No. 576

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9).

**Fastener:** Body: 2 ea. #10 x 1" FH SMS, 2 ea. #10 – 24 x 1" FH MS  
Strike: 5 ea. #8 x 1" FH SMS

**Other:**

- For use on door sizes:
  - with Astragal on active door – 18" to 48"
  - with Astragal on inactive door – 18" to 34"
  - with Astragal on both doors – 18" to 30"
- The overlap of the astragal is maximum 7/8" with door hung on standard hinges. Customer must contact the factory for all other astragal situations

**Features:** Non-handed reversible. Prevents the active door from closing until the inactive door is closed

No.	Size	Projection	Weight
576	1" x 5 7/16"	7"	2.2 lbs.

**ROCKWOOD®**


**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | www.rockwoodmfg.com  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.


## Surface Bolts No. 580, 582 Series



- Material:** No. 580: Steel, stainless steel  
No. 582: Stainless steel
- Finishes:** US3, US10B, US26D, US32D, 10BE, BSP, WSP, BPC, WPC
- Fastener:** No. 580: 8 ea. #10 x 1 1/4" FH SMS, 8 ea. #10 - 24 x 1" FH MS  
No. 582: Bolt: 4 ea. #10 - 24 x 1 1/2" PH MS; 4 ea. #10 x 1 1/4" PH WS  
Strikes: 6 ea. #10 - 32 x 1 1/2" FH MS; 6 ea. #10 - 32 x 1 1/2" FH WS
- Other:** 1 1/8" bolt throw, 1/4" x 3/4" bolt material
- Features:**
- No. 580 Series bolts are UL listed for use on inactive leaf of a pair of 3-hour labeled fire doors
  - No. 580 and No. 582 series both include a universal top strike and a mortise bottom strike
  - No. 582 Series has a bracket for padlock (padlock not included)
- Options:** Sex bolts available for extra secure mounting


No.	Bolt Length	Weight
580-8	8"	1.1 lbs.
580-12	12"	1.4 lbs.
580-18	18"	1.7 lbs.
580-24	24"	2.0 lbs.
582-8	8"	1.3 lbs.
582-12	12"	1.6 lbs.

## Heavy Duty Surface Bolts No. 585 Series



- Material:** Steel
- Finishes:** US26D, 10BE, BSP, WSP, BPC, WPC, FBPC, RPC, 314E, 315E
- Fastener:** Bolt: 4 ea. 1/4 - 20 x 2 1/4" FH MS  
4 ea. 1/4 - 20 x 1 5/8" sex bolts  
Strike: 2 ea. #14 x 2 1/2" FH SMS, 2 ea. Plastic Anchors  
2 ea. 1/4 - 20 x 1" FH MS, 2 ea. 1/4 - 20 Anchors
- Other:** 1 1/4" bolt throw, 3/4" x 3/4" bolt material
- Features:**
- \*UL listed up to 24" bolt size for use on inactive leaf of a pair of 3-hour labeled fire doors
  - Includes a universal top strike and a mortise bottom strike
  - Locks in both the up and down position
  - Bolt locks automatically when thrown – can be released only by pressing knob toward door while retracting
  - Can be used on any type of door
  - Accommodates padlock

No.	Bolt Length	Weight
585-12	12"	3.9 lbs.
585-24	24"	6.1 lbs.
585-36	36"	8.3 lbs.
585-48	48"	10.5 lbs.



## Surface Bolts No. 630 Series

**Material:** Solid brass

**Finishes:** US3, US10B, US26D, other finishes available on special order

**Features:**

- Unique fiber gasket provides slide resistance without marring surface of bolt
- 1" diameter knob
- Supplied with universal and mortise strike

No.	Fastener	Overall Size	Bolt Size	Bolt Length	Bolt Throw	Guides	Weight
630-4	8 ea. #6 x 3/4" OH SMS	1 5/8" x 4 3/8"	5/8" half round	4"	9/16"	2	2.5 lbs./5
630-8	8 ea. #6 x 3/4" OH SMS	1 5/8" x 8"	5/8" half round	8"	9/16"	2	3.9 lbs./5
630-12	10 ea. #6 x 3/4" OH SMS	1 5/8" x 12"	5/8" half round	12"	9/16"	3	5.3 lbs./5
630-24	12 ea. #6 x 3/4" OH SMS	1 5/8" x 24"	5/8" half round	24"	9/16"	4	11.8 lbs./5


**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.




## Roller Latch with Cast Strike No. 590


- Material:** Cast brass
- Finishes:** Available in standard architectural finishes (see page 9)  
Roller in white or black contingent on specified finish
- Fastener:** Body: 2 ea. #8 x 3/4" FH combo screws  
Strike: 2 ea. #8 x 3/4" FH combo screws
- Features:**
- Solid nylon roller for durable silent operation
  - Simple adjustment for roller projection

No.	Latch Face	Strike	Weight
590	1" x 3 3/8"	1 11/16" x 2 1/4"	0.6 lbs.


## Double Acting Strike No. 590DA



- Material:** Brass
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** Strike: 4 ea. #8 x 3/4" FH combo screws
- Other:** For use on double acting doors and frames with the No. 590  
Specify size required
- Features:**
- Solid nylon roller for durable silent operation
  - Simple adjustment for roller projection




No.	Latch Face	Strike	Weight
590DA (Strike Only)	1" x 3 3/8"	2 3/4" x specify	0.6 lbs.



## Roller Latch with ASA Strike No. 591

- Material:** Cast brass
- Finishes:** Available in standard architectural finishes (see page 9)  
Roller in white or black contingent on specified finish
- Fastener:** Body: 2 ea. #8 x 3/4" FH combo screws  
Strike: 2 ea. #12 - 24 x 1/2" FH MS
- Features:**
- Solid nylon roller for durable silent operation
  - Simple adjustment for roller projection


No.	Latch Face	Strike	Weight
591	1" x 3 3/8"	1 1/4" x 4 7/8"	0.6 lbs.



## Roller Latch with No. 161 Strike No. 592

- Material:** Cast brass
- Finishes:** Available in standard architectural finishes (see page 9)  
Roller in white or black contingent on specified finish
- Fastener:** Body: 2 ea. #8 x  $\frac{3}{4}$ " FH combo screws  
Strike: 2 ea. #8 x  $\frac{3}{4}$ " FH combo screws
- Features:**
- Solid nylon roller for durable silent operation
  - Simple adjustment for roller projection
  - Accepted by the New York State Office of Mental Health (OMH) for use in high risk areas


No.	Latch Face	Strike	Weight
592	1" x $\frac{3}{8}$ "	1 $\frac{1}{8}$ " x $\frac{3}{4}$ "	0.6 lbs.



## Roller Latch with Angle Stop No. 593

- Material:** Cast brass.
- Finishes:** Available in standard architectural finishes (see page 9)  
Roller in white or black contingent on specified finish
- Fastener:** Body: 2 ea. #12 x  $\frac{1}{2}$ " FH WS  
Strike: 2 ea. #8 x  $\frac{3}{4}$ " FH combo screws
- Features:**
- Mounts in header with strike in top of door
  - Solid nylon roller for durable silent operation
  - Simple adjustment for roller projection

No.	Latch Face	Strike	Projection	Weight
593	1 $\frac{1}{2}$ " x 4 $\frac{1}{2}$ "	1 $\frac{1}{8}$ " x 2 $\frac{1}{4}$ "	$\frac{5}{8}$ "	0.8 lbs.



## Roller Latch with No. 161 Strike No. 594

- Material:** Cast brass
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** Body: 2 ea. #8 x  $\frac{3}{4}$ " FH combo screws  
Strike: 2 ea. #8 x  $\frac{3}{4}$ " FH combo screws
- Features:**
- Solid nylon roller for durable silent operation
  - Simple adjustment for roller projection

No.	Latch Face	Strike	Weight
594	1 $\frac{1}{8}$ " x 2 $\frac{1}{4}$ "	1 $\frac{1}{8}$ " x 2 $\frac{3}{4}$ "	0.7 lbs.

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Secret Gate Latch No. 602


**Material:** Cast brass

**Finishes:** US4, US10, US10B, 10BE, US26D

**Features:**

- Single acting, reversible. Supplied with dummy knob
- Bolt activated by pressing button concealed on bottom of latch case

No.	Fastener	Size	Weight
602	5 ea. #7 x 1 <sup>1</sup> / <sub>4</sub> " OH WS	Case: 2 <sup>1</sup> / <sub>16</sub> " x 2 <sup>7</sup> / <sub>16</sub> " Strike: 2 <sup>1</sup> / <sub>16</sub> " x 3 <sup>3</sup> / <sub>4</sub> "	3.4 lbs./6




## Door Guard No. 603

**Material:** Cast aluminum

**Finishes:** Antique brass (ANT), bright brass (BRS), bright chrome (CRM), dull chrome (DCRM)

**Options:** 1/8" clear plastic shim - order separately as 603 SHIM

No.	Fastener	Size	Weight
603	Body: 3 ea. #6 x 1 <sup>1</sup> / <sub>2</sub> " FH SMS Strike: 4 ea. #6 x 1" FH SMS	Body: 2 <sup>9</sup> / <sub>32</sub> " x 2 <sup>1</sup> / <sub>2</sub> " Strike: 3 <sup>1</sup> / <sub>32</sub> " x 2 <sup>1</sup> / <sub>2</sub> "	3.3 lbs./10
603 SHIM		3 <sup>1</sup> / <sub>32</sub> " x 2 <sup>1</sup> / <sub>2</sub> "	



## Door Guard No. 604

**Material:** Solid cast brass

**Finishes:** US3, US4, US10, US10B, US26, US26D, US15

**Options:** 1/8" clear plastic shim - order separately as 604 SHIM

No.	Fastener	Size	Weight
604	Body: 3 ea. #6 x 1 <sup>1</sup> / <sub>2</sub> " OH SMS Strike: 4 ea. #6 x 3 <sup>3</sup> / <sub>4</sub> " OH SMS	Body: 1 <sup>1</sup> / <sub>16</sub> " x 2 <sup>9</sup> / <sub>16</sub> " Strike: 1 <sup>5</sup> / <sub>8</sub> " x 1 <sup>1</sup> / <sub>16</sub> "	4.4 lbs./10
604 SHIM		1 <sup>1</sup> / <sub>16</sub> " x 1 <sup>1</sup> / <sub>16</sub> "	



## Door Guard Protection Plates No. 605, 605SMS

**Material:** Brass

**Finishes:** US3, US4, US10, US10B, US15, US26, US26D, Stock Powder Coats


**Features:** Protects corner of door from damage by door guard arm

No.	Fastener	Size	Weight
605	Self-adhesive tape	1 <sup>1</sup> / <sub>8</sub> " x 1" x 1 <sup>1</sup> / <sub>2</sub> " return	0.3 lbs./10
605SMS	#6 x 5/8" FH SMS	1 <sup>1</sup> / <sub>8</sub> " x 1" x 1 <sup>1</sup> / <sub>2</sub> " return	0.3 lbs./10

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world




## Wall Guard No. 606-RKW

**Material:** Clear rubber

**Other:** Sold in sheets of 55

**Features:** Self-adhesive mounting

No.	Fastener	Size	Weight
606-RKW	Self-adhesive back	1" x 1"	0.4 lbs./55



## Privacy Door Latch No. PDLAA


**Material:** Zinc die cast

**Finishes:** US26D, US26, US15, BSP, US3, US4, 10BE

**Features:**

- ADA compliant
- Enhanced in room privacy
- Easy to install
- For use with UL Classified fire doors for use with hollow metal steel composite type fire doors rated up to and including 3 hrs Wood composite type fire doors rated up to and including 1½ hrs and 20 minutes without hose stream

No.	Fastener	Size	Weight
PDLAA	#12 x 1-1/4" FH SMS	1½" x 2¾"	0.8 oz.




## Door Silencer No. 608CA

**Material:** Clear rubber

**Other:** Sold in packages of 300

**Features:** Self-adhesive mounting

No.	Fastener	Size	Weight
608CA	¾" dia. x 1/8"	Metal or wood	0.2 lbs./300



## Door Silencers No. 608-RKW, 609

**Material:** Rubber

**Finishes:** 608-RKW: Gray (standard), black. 609: Gray

**Other:** Sold in packages of 100

No.	Size	Frame Type	Weight
608-RKW	½" dia. x 5/8"	Metal	1.3 lbs./500
609	¾" x ¾"	Wood	1.3 lbs./500

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

# Door Coordinators No. 2600 Series

**Material:** Steel


**Finishes:** Black, US28

**Fastener:** 7 ea. #12 - 24 x 1 1/4 TH type C tapping screws

**Size:** Standard device size 5/8" x 1 5/8" x 52"

**Features:** Non-handed. Override protection to prevent damage in case of abnormal force on door Mechanism and filler bar completely fill width of opening and when painted to match frame it becomes virtually invisible

**Ordering:** Stock Sizes



No.	Opening	Weight
2660	60"	7.0 lbs.
2672	72"	8.0 lbs.
2696	96"	9.75 lbs.

**Custom Sizes** – The 2600 Series coordinators are manufactured in different housing lengths to coordinate the full range of door sizes:


- NX2600 Series: For jamb opening widths (A + B dimension) from 48" - 54". E dimension, 42"
- 2600 Series: For jamb opening widths (A + B dimension) from 54" - 96". E dimension, 52"

**Determining Coordinator Item Number**

- Active door widths A plus inactive door width B equals the last two or three digits of all 2600 Series coordinator item numbers (2680 is for 80" door opening)
- Less than 48" jamb widths = N2600 Series (N2644 = 44" opening).
- Larger sizes are available (L, XL). Contact the factory


*NOTE: 2600 Series Coordinators are designed so that surface vertical rod strike preps can be made directly into the coordinator body.*

No.	Jamb Widths	Coordinator Length
NX2648- NX2654	48" - 54"	42"
2655 - 2660	55" - 60"	52"
2661 - 2672	61" - 72"	52"
2673 - 2696	73" - 96"	52"



*Fillers are usually supplied precut from the factory (filler bars shown on page E14).*

*NOTE: If "S" dimension is other than 5/8" advise the factory.*



800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world



## Carry Bar for No. 1600 /2600 Series Coordinator No. 1100

**Material:** Brass, steel

**Finishes:** US32D, and black prime coat

**Fastener:** 2 ea. 12-24 x  $\frac{3}{4}$ " round head machine screws  
2 ea. 12-24 x  $\frac{11}{16}$ " sex bolts

**Other:** A carry bar is used when it is possible to open the inactive door before opening the active door

No.	Size	Weight
1100	$1\frac{3}{4}$ " x $2\frac{1}{4}$ "	0.3 lbs.



## Filler Bar for No. 1600 /2600 Series Coordinator No. FB-1, FB-2

**Material:** Steel

**Finishes:** Black, US28

**Features:** Filler bar is supplied at no charge with the No. 1600 and 2600 Series coordinator (shown on pages E12 & E13)

No.	Size
FB-1	Specify length from $1\frac{5}{8}$ " to $18\frac{5}{8}$ "
FB-2	Specify length from $19\frac{5}{8}$ " to $42\frac{5}{8}$ "

Contact factory for larger sizes.



## Universal Door Coordinator No. 1700

**Material:** Steel

**Finishes:** Black prime coat, US28

**Fastener:** 4 ea. 10-24 x 2" flat head machine screws and #10 x 2" sheet metal screws

**Features:** For pairs of doors. Non-handed. Stop mounted - no mounting brackets required for stop mounted hardware.



NOTE: Not for use with surface vertical panic devices.

No.	Overall Size	Weight
1700	$1\frac{5}{8}$ " x $20\frac{3}{16}$ " x $\frac{3}{4}$ "	2.55 lbs.

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**


Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



2601AB



2601C

## Mounting Brackets (for Soffit Applied Hardware) No. 2601AB, 2601C

**Material:** Aluminum

**Finishes:** Black, US28

**Fastener:** 4 ea. 1/4" - 20 x 1/2" FH MS, 4 ea. #12 - 24 x 2" FH MS.

**Features:** Used for stop applied hardware. Prevents the inadvertent disabling of the coordinator by fasteners passing through the housing

No.	Soffit Size	Length	Weight
2601AB	7/8" - 2 1/4"	5"	0.9 lbs.
2601C	Over 2 1/4"	5"	0.8 lbs.



## Mounting Brackets (for Soffit Applied Hardware) No. 2601D

**Material:** Aluminum

**Finishes:** Black, US28

**Fastener:** 4 ea. 1/4"-20 x 1/2" Flat Head Machine Screws  
2 ea. #12-24 x 2" Flat Head Machine Screws

**Features:** Fits all frame dimensions eliminating the need to order different style mounting brackets. The low profile design enhances the appearance of the opening.

**Patent No.** 9109388

No.	Length	Width	Weight
2601D	7 13/16"	1 13/16"	.6 lbs.



## Automatic Flush Bolts No. 2840 (Automatic Top Bolt Only) No. 2842 (Set) (replaces the No. 1840 and No. 1842)

**Material:** Brass, stainless steel

**Finishes:** US3, US4, US10, 10BE, US26, US26D, US32D, BPC, BSP, FBPC, WSP

**Fastener:** No. 2842: 20 ea. #8 x 3/4" FH combo screws, 2 ea. #6 - 8 plastic anchors  
No. 2840: 10 ea. #8 x 3/4" FH combo screws. NOTE: No plastic anchor required for top only

**Features:**

- For Fire Rated Metal Doors labeled A, B, C, D & E up to 4'w x 8'h
- Non-handed
- Fully automatic- opening active door retracts top and bottom bolts
- Override feature prevents damage to doors or bolts if bolt heads are blocked from entering strikes
- Bolt head rods are adjustable up to 1 1/2"
- Thermal lock automatically locks the inactive door under high heat conditions due to fire

**Options:** No. 2842 can be used with the No. 570 Dust Proof Strike (shown on page E4).

No.	Size	Weight
2840	1" x 6 3/4"	1.2 lbs.
2842	1" x 6 3/4"	2.4 lbs.



## Combination Flush Bolts No. 2805 (Self Latching Top Bolt Only) No. 2845 (Set) (replaces No. 1805 and No. 1845)

**Material:** Brass, stainless steel

**Finishes:** US4, US10, 10BE, US26D, US32D, US32, BSP, BPC, FBPC

**Fastener:** Top: 2 ea. #8 x 1" Flat Head Combo Screws; 6 ea. #8 x 1" Flat Head Machine Screws.  
*NOTE: No plastic anchor required for top only.*  
Bottom (No. 2845 only) 4 ea. #8 x 1" Flat Head Combo Screws; 14 ea. #8 x 1" Flat Head Machine Screws, 2 ea. #6 - 8 plastic anchors.

**Features:**

- For Fire Rated Metal Doors labeled A, B, C, D & E up to 4'w x 8'h

**Top Bolt**

- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face

**Bottom Bolt (No. 2845 only)**

- Non-handed
- Fully automatic - opening active door retracts bottom bolt
- Override feature prevents damage to door or bolt if bolt head is blocked from entering strike
- Bolt head rod is adjustable up to 3/4"
- Thermal lock automatically locks the inactive door under high heat conditions due to fire

**Options:** No. 2845 can be used with the No. 570 Dust Proof Strike (shown on page E4)

No.	Size	Weight
2805	1" x 6 3/4"	1.2 lbs.
2845	1" x 6 3/4"	2.4 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Automatic Flush Bolt No. 2940 (Automatic Top Bolt Only) No. 2942 (Set) (replaces No. 1940 and No. 1942)

**Material:** Brass, stainless steel

**Finishes:** US3, US4, 10BE, US26, US26D, US32D, BPC, BSP, FBPC

**Fastener:** No. 2940: 6 ea. #8 x 3/4" FH combo screws, 2 ea. #8 - 32 x 1/2" FH MS, 3 ea. #10 x 1" FH WS  
*NOTE: No plastic anchor required for top only.*  
 No. 2942: 12 ea. #8 x 3/4" FH combo screws, 4 ea. #8 - 32 x 1/2" FH MS, 6 ea. #10 x 1" FH WS, 2 ea. #6 - 8 plastic anchors

**Features:**

- For Wood Doors labeled B, C, D & E up to 4'w x 8'h
- Non-handed
- Fully automatic—opening active door retracts top and bottom bolts
- Override feature prevents damage to doors or bolts if bolt heads are blocked from entering strikes
- Bolt head rods are adjustable up to 1/2"
- Thermal lock automatically locks the inactive door under high heat conditions due to fire

**Options:** No. 2942 can be used with the No. 570 Dust Proof Strike (shown on page E4).

No.	Size	Weight
2940	1" x 8 1/2"	1.5 lbs.
2942	1" x 8 1/2"	2.9 lbs.



## Combination Flush Bolts No. 2905 (Self Latching Top Bolt Only) No. 2945 (Set) (replaces No. 1905 and No. 1945)

**Material:** Brass, stainless steel

**Finishes:** US3, US4, 10BE, US26D, US32D, US32, BSP, BPC, BSP

**Fastener:** Top: 4 ea. #8 x 3/4" FH combo screws, 2 ea. #8 - 32 x 1/2" FH MS, 3 ea. #10 x 1" FH WS.  
*NOTE: No plastic anchor required for top only.*  
 Bottom (No. 2945 only): 10 ea. #8 x 3/4" FH combo screws, 4 ea. #8 - 32 x 1/2" FH MS, 6 ea. #10 x 1" FH WS, 2 ea. #6 - 8 plastic anchors

**Features:**

- For Wood Doors labeled B, C, D & E up to 4'w x 8'h

**Top Bolt**

- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face

**Bottom Bolt (No. 2945 only)**

- Non-handed
- Fully automatic — opening active door retracts bottom bolt
- Override feature prevents damage to door or bolt if bolt head is blocked from entering strike
- Bolt head rod is adjustable up to 3/8"
- Thermal lock automatically locks the inactive door under high heat conditions due to fire

**Options:** No. 2945 can be used with the No. 570 Dust Proof Strike (shown on page E4).

No.	Size	Weight
2905	1" x 8 1/2"	1.5 lbs.
2945	1" x 8 1/2"	2.9 lbs.





## Automatic Flush Bolt with Bottom Fire Bolt No. 2848 (replaces 1848)

**Material:** Brass, stainless steel

**Finishes:** US4, US10, 10BE, US32D, US32, BSP, BPC, FBPC

**Fastener:** 10 ea. #8 x 3/4" FH combo screws, 4 ea. plastic anchors

- Features:**
- For Fire Rated Metal Doors
  - Low (5 lbs. maximum) closing force
  - Fully automatic—opening active door retracts top bolt
  - Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
  - Bolt head rod is adjustable up to 1 1/2"
  - For fire rated metal doors labeled A, B, C, D, & E up to 4' w x 9' h
  - Thermal lock automatically locks the inactive door under high heat conditions due to fire
  - Bottom fire bolt eliminates need for floor prep
  - Oversize fire bolt strike hole allows for slight door misalignment

No.	Size	Weight
2848	Top bolt: 1" x 6 3/4" Bottom bolt: 13/16" dia.	1.3 lbs.



## Automatic Flush Bolt with Bottom Fire Bolt No. 2948 (replaces 1948)

**Material:** Brass, stainless steel

**Finishes:** US3, US4, 10BE, US32D, US32, BSP, BPC, FBPC

**Fastener:** 8 ea. #8 x 3/4" FH combo screws, 2 ea. plastic anchors;  
3 ea. #10 x 1" FH WS

- Features:**
- For Fire Rated Wood Doors
  - Low (5 lbs. maximum) closing force
  - Fully automatic—opening active door retracts top bolt
  - Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
  - Bolt head rod is adjustable up to 1 1/2"
  - For fire rated UL listed 20-minute wood core and composite doors up to 4' w x 9' h
  - Thermal lock automatically locks the inactive door under high heat conditions due to fire
  - Bottom fire bolt eliminates need for floor prep
  - Oversize fire bolt strike hole allows for slight door misalignment

No.	Size	Weight
2948	Top bolt: 1" x 8 1/2" Bottom bolt: 13/16" dia.	1.6 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Bottom Fire Bolt (for Metal Doors) No. 18BFB

**Material:** Stainless steel

**Finishes:** US32D

**Features:**

- Eliminates the bottom automatic flush bolt and dust proof strike
- When door is subjected to 230°F the plug and gray plastic cover will melt allowing the bolt to project, locking the leaves together
- UL Listed only when used with automatic top bolt

No.	Size	Weight
18BFB	Bolt: $1\frac{3}{16}$ " x $1\frac{9}{16}$ " Plug: $1\frac{7}{32}$ " dia.	0.1 lbs.



## Bottom Fire Bolt (for Wood Doors) No. 19BFB

**Material:** Stainless steel

**Finishes:** US32D

**Features:**

- Eliminates the bottom automatic flush bolt and dust proof strike
- When door is subjected to 230°F the plug and black plastic cover will melt allowing the bolt to project, locking the leaves together
- UL Listed only when used with automatic top bolt

No.	Size	Weight
19BFB	Bolt: $1\frac{3}{16}$ " x $1\frac{9}{16}$ " Plug: $1\frac{13}{64}$ " dia.	0.1 lbs.



## Cover Plate Kit (for Metal Doors) No. CPK2840

**Material:** Stainless Steel

**Finishes:** 10BE, US32D

**Fastener:** 4 ea. #8 x  $\frac{3}{4}$ " FH combo screws

**Features:** Covers existing bottom 2840 flush bolt prep

No.	Size	Weight
CPK2840	1" x $6\frac{3}{4}$ "	0.1 lbs.



## Automatic Flush Bolt with Bottom Fire Bolt No. 2960 (replaces 1960)


**Material:** Brass, Stainless Steel

**Finishes:** US3, US4, US10, 10BE, US32D, US32, BSP

**Fastener:** 4 ea. #8 x 1" FH SMS, 4 ea. #8 x 3/4" FH combo screws, 2 ea. plastic anchors

- Features:**
- For Fire Rated Wood Core & Composite Doors
  - Durable, tested over 1 million cycles
  - Smaller profile adds stability to the door
  - Only two 1/8" diameter holes for easier door preparation
  - Preparation prevents the veneer from splitting at the corners of the door
  - Quiet & smooth activation
  - Fully automatic—opening active door retracts top bolt
  - Non-handed.
  - Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
  - Low (3 lbs. maximum) closing force. ADA Compliant
  - Adjustable bolt head rod: bolts can be vertically adjusted 1/2" for unusual clearances
  - For up to 4' w x 9' h fire rated wood core & composite doors up to 20 minutes fire rating.

No.	Face Plate Size	Weight
2960	1 1/8" x 2 1/4"	0.9 lbs.



## Automatic Flush Bolts No. 2962 (replaces 1962)

**Material:** Brass, stainless steel

**Finishes:** US3, US4, US10, 10BE, US32D, US32, BSP

**Fastener:** 8 ea. #8 x 1" FH SMS, 8 ea. #8 x 3/4" FH combo screws, 4 ea. plastic anchors

- Features:**
- For Fire Rated Wood Core & Composite Doors
  - Durable, tested over 1 million cycles
  - Smaller profile adds stability to the door
  - Only two 1/8" diameter holes for easier door preparation
  - Preparation prevents the veneer from splitting at the corners of the door
  - Quiet & smooth activation
  - Fully automatic—opening active door retracts top & bottom bolts.
  - Non-handed
  - Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
  - Low (3 lbs. maximum) closing force. ADA Compliant
  - Adjustable bolt head rods: bolts can be vertically adjusted 1/2" for unusual clearances
  - For up to 4' w x 9' h fire rated wood core & composite doors up to 1 1/2 hours fire rating

No.	Face Plate Size	Weight
2962	1 1/8" x 2 1/4"	1.7 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Self Latching Flush Bolt with Bottom Fire Bolt No. 2849 (replaces 1849)

**Material:** Brass, stainless steel

**Finishes:** US4, 10BE, US32D, BSP, WPC, FBPC

**Fastener:** 8 ea. #8 x 3/4" FH combo screws, 4 ea. plastic anchors

- Features:**
- For Fire Rated Metal Doors
  - Non-handed.
  - Low (5 lbs. maximum) closing force
  - Self latching top bolt
  - Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
  - Bolt head rod is adjustable up to 1 1/2"
  - For fire rated metal doors labeled A, B, C, D, & E up to 4' w x 10' h
  - Thermal lock automatically locks the inactive door under high heat conditions due to fire
  - Bottom fire bolt eliminates need for floor prep
  - Oversize fire bolt strike hole allows for slight door misalignment

No.	Size	Weight
2849	Top bolt: 1" x 6 3/4" Bottom bolt: 1 3/16" dia.	1.3 lbs.



## Self Latching Flush Bolt with Bottom Fire Bolt No. 2949 (replaces 1949)



**Material:** Brass, stainless steel

**Finishes:** US3, US4, US10, 10BE, US32D, US32, BSP

**Fastener:** 6 ea. #8 x 3/4" FH combo screws, 2 ea. plastic anchors,  
3 ea. #10 x 1" FH WS

- Features:**
- For Fire Rated Wood Doors
  - Non-handed
  - Low (5 lbs. maximum) closing force
  - Self latching top bolt
  - Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike
  - Bolt head rod is adjustable up to 1 1/2"
  - For fire rated UL listed 20-minute wood core and composite doors up to 4' w x 9' h
  - Thermal lock automatically locks the inactive door under high heat conditions due to fire
  - Bottom fire bolt eliminates need for floor prep
  - Oversize fire bolt strike hole allows for slight door misalignment



No.	Size	Weight
2949	Top bolt: 1" x 8 1/2" Bottom bolt: 1 3/16" dia.	1.6 lbs.



## Standard Head Pivot No. CP10, CP10HD

- Material:** Solid brass leaf, Stainless steel pin
- Finishes:** US3, US4, US10, US10B, US26, US26D, other finishes available on request
- Fastener:** 6 ea. #12 x 1 1/4" FH wood screws
- Ordering:** Specify door thickness
- Features:**
- Mostly invisible when installed
  - Includes Teflon® bearing for smooth silent operation
  - Field changeable handing
  - Standard duty is made from 3/8" thick brass
  - Heavy duty (HD) is made from 1/2" thick brass

No.	Weight
CP10	1.3 lbs.
CP10HD	1.9 lbs.



## Standard Floor Pivot No. CP40, CP40HD

- Material:** Solid brass leaf, Stainless steel pin
- Finishes:** US3, US4, US10, US10B, US26, US26D, other finishes available on request
- Fastener:** 6 ea. #12 x 1 1/4" FH wood screws
- Ordering:** Specify door thickness and floor clearing
- Features:**
- Mostly invisible when installed
  - Includes Teflon® bearing for smooth silent operation
  - Field changeable handing
  - Standard duty is made from 3/8" thick brass
  - Heavy duty (HD) is made from 1/2" thick brass

No.	Weight
CP40	1.3 lbs.
CP40HD	1.9 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Door Knocker No. 611

- Material:** Solid cast brass
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** 2 ea. #8 - 32 x 2" FH MS (for standard 1<sup>3</sup>/<sub>4</sub>" doors); 2 ea. #8 finish washers
- Options:**
- Drill for door viewer No. 621 (order viewer separately)
  - Engrave numbers or name. Assorted fonts are available

No.	Size	Weight
611	3 <sup>5</sup> / <sub>8</sub> " x 6 <sup>3</sup> / <sub>4</sub> "	0.6 lbs.



No. 614

No. 614V

## Door Knockers No. 614, 614V

- Material:** Cast brass
- Finishes:** Available in standard architectural finishes (see page 9)
- Fastener:** 2 ea. #8 - 32 x 2" FH MS (for standard 1<sup>3</sup>/<sub>4</sub>" doors); 2 ea. #8 finish washers
- Features:** No. 614V includes door viewer No. 622
- Options:** Engrave numbers or name

No.	Size	Weight
614	2 <sup>1</sup> / <sub>8</sub> " x 3"	0.4 lbs.
614V	2 <sup>1</sup> / <sub>8</sub> " x 3"	0.4 lbs.



No. 619

No. 620/621




No. 624

## 160° Door Viewers No. 619, 620, 620VC, 621, 624

- Material:** Brass
- Finishes:** Antique bronze (ANT), brass (BRS), bright chrome (CRM), satin nickel (\*STNN)  
\*only available on 619, 620
- Other:** Installation - drill 1/2" hole
- Features:** No. 624 features a privacy cover to prevent visual intrusion from outside of the room

No.	Inside Cover	For Doors	Weight
619	No	1 <sup>1</sup> / <sub>16</sub> " to 1 <sup>1</sup> / <sub>16</sub> "	0.05 lbs.
620	No	1 <sup>3</sup> / <sub>8</sub> " to 2"	0.1 lbs.
620VC	Cover only		0.1 lbs./10
621	No	2" to 2 <sup>1</sup> / <sub>2</sub> "	0.1 lbs.
624	Yes	1 <sup>3</sup> / <sub>8</sub> " to 2"	0.1 lbs.

### Recommended Location for Viewers



800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world



No. 626



No. 622

## 190° Door Viewer No. 622, 622VC, 626

**Material:** Brass

**Finishes:** Antique bronze (ANT), black \*(BLK), brass (BRS), bright chrome (CRM), dull chrome (DCRM), satin nickel \*(STNN)  
\*only available on 622

**Other:** Installation – drill  $\frac{9}{16}$ " hole

**Features:** No. 626 features a privacy cover to prevent visual intrusion from outside of the room

No.	Inside Cover	For Doors	Weight
622	No	$1\frac{3}{8}$ " to $2\frac{1}{8}$ "	0.1 lbs.
622VC	Cover only		0.1 lbs./10
626	Yes	$1\frac{3}{8}$ " to $2\frac{1}{8}$ "	0.1 lbs.



No. 627, 628, 629

## 190° Door Viewer with Heavy Duty Privacy Cover No. 627, 628, 629


**Material:** Brass

**Finishes:** Bright chrome (CRM), Black (BLK)

**Other:** Installation – drill  $\frac{9}{16}$ " hole. UL fire rated for  $1\frac{1}{2}$  hours

**Features:** Heavy duty privacy cover to prevent visual intrusion from outside of the room

No.	For Doors	Weight
627	$1\frac{3}{8}$ " to $2\frac{1}{4}$ "	0.1 lbs.
628	$\frac{9}{16}$ " to $\frac{13}{16}$ "	0.1 lbs.
629	$\frac{15}{16}$ " to $1\frac{1}{4}$ "	0.1 lbs.



## Door Viewer Washer No. 618W

**Material:** Brass

**Finishes:** Polished brass (BRS), bright chrome (CRM), satin nickel (STNN), antique bronze (ANT), Black Suede Powder Coat (BSP)

**Other:** Designed for use when the door is not thick enough to meet the specifications of the viewer. Can be used with all Rockwood Door Viewers.

No.	For Doors	Dimensions
618W	$\frac{9}{16}$ " to $2\frac{1}{2}$ "	$\frac{1}{8}$ " width, $\frac{9}{16}$ " inner dia, $\frac{13}{16}$ " outer dia



## Card Holder No. 651

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 2 ea. #8 x  $\frac{3}{4}$ " OH SMS

No.	Size	Card Size	Opening	Weight
651	$2\frac{1}{2}$ " x $4\frac{1}{4}$ "	2" x $3\frac{1}{2}$ "	$1\frac{3}{4}$ " x $3\frac{1}{4}$ "	0.2 lbs.

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)

Check the web site for the up-to-date catalog

Copyright © 2012–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

<b>THIS DOOR TO REMAIN UNLOCKED DURING BUSINESS HOURS</b>	No. 660
<b>THIS DOOR TO REMAIN UNLOCKED WHILE BUILDING IS OCCUPIED</b>	No. 661
<b>THESE DOORS TO REMAIN UNLOCKED WHILE BUILDING IS OCCUPIED</b>	No. 662-RKW

## Decal No. 660, 661, 662-RKW

- Material:** Silver foil
- Fastener:** Self-adhesive mounting
- Other:** Black lettering
- Size:** 1½" x 26½"

• MEN •

• WOMEN •

• RESTROOM •

## Engraved Signs No. 670 Series

- Material:** .125" plastic or .050" aluminum, brass, bronze, stainless steel
- Finishes:** Plastic signs: available in black or brown with white lettering  
Metal signs: available in standard architectural finishes (see page 9)
- Fastener:** 2 ea. #6 x 5/8" OH SMS
- Ordering:** Specify product number, finish, and copy
- Features:**
- Standard letter size is 1" high by 1/8" wide stroke. Other sizes from 1/2" to 3" are available
  - Standard font is US Block, other fonts available
  - Sign size is determined by the height and length of the engraving and is calculated to allow for an appropriate border
- Options:**
- SA – self-adhesive mounting
  - Custom sizes and messages

No.	Message	Size
670	Specify copy	2" x width required
670M	MEN	2" x 5"
670W	WOMEN	2" x 7"
670R	RESTROOM	2" x 10"



No. 674L



No. 674H

## Engraved Signs No. 674H, 674L

- Material:** .125" plastic or .050" aluminum, brass
- Finishes:** Plastic signs: available in black or brown with white lettering  
Metal signs: available in standard architectural finishes (see page 9)
- Fastener:** Self-adhesive mounting
- Size:** 1" x 4½"

**ROCKWOOD®**  
**ASSA ABLOY**

Experience a safer  
and more open world

. MEN .

. WOMEN .

. RESTROOM .

. ADMINISTRATION .

## Barrier Free Engraved Signs (with Braille Translation) No. BF680 Series

**Material:** .125" non-glare plastic or .050" brass, bronze

**Finishes:** Plastic signs: available in black, blue, brown, or red with white lettering  
Metal signs: available in standard architectural finishes (see page 9).

**Fastener:** 2 ea. #6 x <sup>5</sup>/<sub>8</sub>" OH SMS

**Ordering:** Specify product number, finish, and copy

**Features:**

- Plastic signs meet ANSI A117.1-1998 section 703 requirements.
- 1" letter height is standard; other sizes available from <sup>5</sup>/<sub>8</sub>" to 2"
- Meets width to height ratio requirements
- Sign size is determined by the height and length of the engraving and is calculated to allow for an appropriate border
- Grade 2 braille translation on sign
- Screws provided for secure mounting
- Made to order, any copy available
- Plastic signs have easy to read letters and numbers that are raised <sup>1</sup>/<sub>32</sub>" from sign surface
- Plastic signs characters and background have a non-glare finish of contrasting light on dark color
- Metal signs have easy to read raised black lettering

**Options:**

- SA – self-adhesive mounting
- Custom sizes and messages

No.	Message	Size
BF680	Specify copy	2½" x width required
BF680M	MEN	2½" x 5"
BF680W	WOMEN	2½" x 7"
BF680R	RESTROOM	2½" x 9"

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.

## BF Series ADA Signs

- Material:** .125" non-glare plastic or .050" brass, bronze
- Finishes:** Plastic signs: available in black, blue, brown, or red with standard 1" white lettering  
Metal signs: available in standard architectural finishes (see page 9)
- Fastener:** 4 ea. #6 x  $\frac{5}{8}$ " OH SMS
- Size:** 8" x 8"
- Ordering:** Specify background finish along with any options
- Features:**
- Plastic signs:**
- Raised characters and Grade 2 Braille translation
  - Meets ADAAG Section 4.30 requirements
- Metal signs:**
- Raised black lettering and Grade 2 Braille translation.
  - Attractive architectural finishes
- Options:**
- SA – self-adhesive mounting

No. BF683



No. BF684



No. BF685



No. BF686



No. BF687



No. BF688




No. BF689



## Recommended Mounting Location for Signs

Excerpts from ADA Accessibility Guidelines for Buildings and Facilities (ADAAG).

**4.30.6 Mounting Location and Height:** Where permanent identification is provided for rooms and spaces, signs shall be installed on the wall adjacent to the latch side of the door. Where there is no wall space to the latch side of the door, including at double leaf doors, signs shall be placed on the nearest adjacent wall. Mounting height shall be 60" (1525 mm) above the finish floor to the centerline of the sign. Mounting location for such signage shall be so that a person may approach within 3" (76 mm) of signage without encountering protruding objects or standing within the swing of a door.



**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

## BFM Series ADA Molded Plastic Signs

- Material:** Molded plastic
- Colors:** 5/8" white lettering on choice of blue or black background
- Fastener:** Self-adhesive mounting
- Size:** 6" x 9"
- Ordering:** Specify product number and background color
- Features:**
  - Raised lettering and Grade 2 Braille translation
  - Meets ADAAG Section 4.30 requirements
  - Economical molded plastic

No. BFM682



No. BFM684



No. BFM685



No. BFM686



No. BFM687



No. BFM688



No. BFM689



### All Gender Restroom Signs

Economical molded plastic; 6" x 9" and 12" diameter. White lettering on Blue background. Self-adhesive mounting. BFM625 has raised lettering and Grade 2 Braille translation.



BFM624




BFM625

## Recommended Mounting Location for Signs

Excerpts from ADA Accessibility Guidelines for Buildings and Facilities (ADAAG).

**4.30.6 Mounting Location and Height:** Where permanent identification is provided for rooms and spaces, signs shall be installed on the wall adjacent to the latch side of the door. Where there is no wall space to the latch side of the door, including at double leaf doors, signs shall be placed on the nearest adjacent wall. Mounting height shall be 60" (1525 mm) above the finish floor to the centerline of the sign. Mounting location for such signage shall be so that a person may approach within 3" (76 mm) of signage without encountering protruding objects or standing within the swing of a door.



**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Hand Rail Brackets No. 700, 701, 702

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Features:**

- 700 Mounting on Concrete Wall
- 701 Mounting on Drywall
- 702 Mounting on Wood

Fastener:	Wood rail	Metal rail
700	$\frac{5}{16}$ - 18 x 1 $\frac{1}{2}$ " FH MS, anchor; 3 ea. #12 - 24 x 1" FH MS; 2 ea. #8 x $\frac{3}{4}$ " OH SMS; 1 ea. back plate	$\frac{5}{16}$ - 18 x 1 $\frac{1}{2}$ " FH MS, anchor; 3 ea. #12 - 24 x 1" FH MS; 2 ea. #8 - 32 x $\frac{3}{4}$ " OH MS; 1 ea. back plate.
701	$\frac{5}{16}$ - 18 x 3" FH MS, toggle; 3 ea. #12 - 24 x 1" FH MS; 2 ea. #8 x $\frac{3}{4}$ " OH SMS; 1 ea. back plate.	$\frac{5}{16}$ - 18 x 3" FH MS, toggle; 3 ea. #12 - 24 x 1" FH MS; 2 ea. #8 - 32 x $\frac{3}{4}$ " OH MS; 1 ea. back plate.
702	3 ea. #12 x 2" FH WS; 2 ea. #8 x $\frac{3}{4}$ " OH SMS.	3 ea. #12 x 2" FH WS; 2 ea. #8 - 32 x $\frac{3}{4}$ " OH MS.

Ordering: Specify wood rail or metal rail

No.	Base	Projection (to rail centerline)	Weight
700	2 $\frac{13}{16}$ "	3 $\frac{1}{2}$ "	2.0 lbs.
701	2 $\frac{13}{16}$ "	3 $\frac{1}{2}$ "	1.8 lbs.
702	2 $\frac{13}{16}$ "	3 $\frac{1}{2}$ "	1.5 lbs.



## Small Coat Hook No. 790

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 2 ea. #6 x <sup>5</sup>/<sub>8</sub>" OH SMS

No.	Size	Projection	Weight
790	1 <sup>1</sup> / <sub>4</sub> " w x 1 <sup>3</sup> / <sub>8</sub> " h	1 <sup>7</sup> / <sub>8</sub> "	.9 lbs./10



## Small Double Coat Hook No. 796

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 2 ea. #6 x <sup>3</sup>/<sub>4</sub>" OH SMS

No.	Size	Projection	Weight
796	1 <sup>1</sup> / <sub>8</sub> " w x 1 <sup>1</sup> / <sub>8</sub> " h	1 <sup>1</sup> / <sub>8</sub> "	1 lbs./10



## Medium Coat Hook No. 802

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 2 ea. #6 x <sup>3</sup>/<sub>4</sub>" RH WS

No.	Size	Projection	Weight
802	1 <sup>3</sup> / <sub>16</sub> " w x 1 <sup>1</sup> / <sub>2</sub> " h	3"	1.1 lbs./10



## Medium Coat Hook No. 806

**Material:** Cast brass

**Finishes:** Available in standard architectural finishes (see page 9)

**Fastener:** 2 ea. #6 x <sup>3</sup>/<sub>4</sub>" OH WS

No.	Size	Projection	Weight
806	1 <sup>1</sup> / <sub>16</sub> " w x 1 <sup>1</sup> / <sub>4</sub> " h	3 <sup>1</sup> / <sub>8</sub> "	1.4 lbs./10

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## 1½" Ball Knob No. 841

**Material:** Solid brass.

**Finishes:** US3, US4, US10, US10B, US15, US26D, 10BE, BSP, WPC, WSP

**Fastener:** #8 - 32 x 1" TH MS.

**Options:** Other screw lengths available upon request.

No.	Base	Projection	Weight
841	¾" dia.	1⅛"	2.5 lbs./10



## Utility Pull No. 845

**Material:** Aluminum, brass.

**Finishes:** US3, US4, US10, US10B, 10BE, US26, US26D, burnished aluminum (ALM).

**Fastener:** 4 ea. #8 x ¾" OH SMS.

No.	Size	Projection	Weight
845	1⅞" x 5⅞"	1½"	1.6 lbs./10 (aluminum) 2.5 lbs./10 (brass)



## Solid Wire Pull No. 850, 851, 852, 853

**Material:** Brass, stainless steel.

**Finishes:** US3, US4, US10, US10B, US26, US26D, US32D, US32DMS.

**Fastener:** #8 - 32 x 1" TH MS.

**Options:** Other CTC's available upon request.

No.	Size	CTC	Projection	Weight
850	⅝" dia.	2¾"	1¼"	3.4 lbs./25
851	⅝" dia.	3"	1¼"	3.8 lbs./25
852	⅝" dia.	3½"	1¼"	3.9 lbs./25
853	⅝" dia.	4"	1¼"	4.0 lbs./25



## Heavy Wire Pull No. 856-RKW

**Material:** Brass, bronze, stainless steel.

**Finishes:** US3, US4, US10, US10B, US26, US26D, US32D, US32DMS.

**Fastener:** #8 - 32 x 1" TH MS.

**Options:** Other CTC's available upon request.

No.	Size	CTC	Projection	Weight
856-RKW	½" dia.	4"	1¾"	4.5 lbs./10



## Flush Cup Pull No. 860

- Material:** Brass, stainless steel  
**Finishes:** US10B, 10BE, US32D  
**Fastener:** 2 ea. #4 x  $\frac{5}{8}$ " OH WS  
**Other:** See website for installation template

No.	Size	Weight
860	2 $\frac{1}{2}$ " dia.	0.9 lbs./10



## Wrought Flush Pull No. 870

- Material:** Brass, stainless steel  
**Finishes:** US3, US10B, 10BE, US32D  
**Fastener:** 2 ea. #4 x  $\frac{5}{8}$ " OH WS

No.	Size	Weight
870	1 $\frac{3}{8}$ " x 3 $\frac{3}{16}$ "	0.5 lbs./10



## Cast Flush Pull No. 872

- Material:** Cast brass  
**Finishes:** US3,US10B, 10BE,US32D  
**Fastener:** 2 ea. #4 x  $\frac{5}{8}$ " OH WS

No.	Size	Weight
872	1 $\frac{5}{16}$ " x 3 $\frac{1}{8}$ "	0.2 lbs.

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Cast Lever Edge Pull No. 880

**Material:** Cast brass  
**Finishes:** US3, US10B, US26D  
**Fastener:** 2 ea. #6 x 3/4" FH SMS

No.	Size	Weight
880	3/4" x 3 7/8"	0.2 lbs.



## Concealed Edge Pull No. 885

**Material:** Brass  
**Finishes:** Available in standard architectural finishes (see page 9)  
**Fastener:** 2 ea. #6 x 1" FH WS

No.	Size	Weight
885-RKW	1" x 4 1/4"	0.5 lbs.



## Pocket Door Pull No. 890

**Material:** Brass  
**Finishes:** US3, US10B, US26, US26D  
**Fastener:** 2 ea. #6 x 5/8" OH SMS  
**Other:** For use on 1 3/8" and 1 3/4" doors

No.	Size	Weight
890	2 1/2" w x 2 3/4" h	0.4 lbs.

*Note: Not for use in caustic environments.*



## Pocket Door Privacy Latch No. 891

**Material:** Brass  
**Finishes:** US3, US10B, US26, US26D  
**Fastener:** 4 ea. #6 x 5/8" OH SMS  
**Other:** For use on 1 3/8" and 1 3/4" doors  
**Features:**

- Turn piece locks to jamb strike
- Emergency release on opposite side

No.	Size	Weight
891	2 1/2" w x 2 3/4" h	0.4 lbs.

*Note: Not for use in caustic environments.*



## Heavy Duty Magnetic Catch No. 900

**Material:** Aluminum

**Finishes:** Brass (BRS), natural aluminum (ALM)

**Fastener:** Body: 2 ea. #6 x 1 $\frac{1}{4}$ " TH SMS  
Strike: 2 ea. #6 x 1 $\frac{1}{2}$ " FH SMS

**Features:**

- Includes installation instructions
- Dual double-pole, self-aligning magnets
- Packed with two short strikes and one long strike
- Can be used on pair of doors or single door

No.	Body Size	Strike Size	Weight
900	$\frac{9}{16}$ " x 3 $\frac{1}{8}$ " x 1"	1 ea. $\frac{5}{8}$ " x 3 $\frac{1}{8}$ " 2 ea. $\frac{5}{8}$ " x 1 $\frac{1}{8}$ "	0.25 lbs.



## Extra Heavy Duty Magnetic Catch No. 901

**Material:** Aluminum

**Finishes:** Brass (BRS), natural aluminum (ALM)

**Fastener:** Body: 2 ea. #6 x 1 $\frac{1}{2}$ " TH SMS  
Strike: 2 ea. #6 x 1 $\frac{1}{2}$ " FH SMS

**Features:**

- Includes installation instructions
- Dual triple-pole, self-aligning magnets
- Packed with two short strikes and one long strike
- Can be used on pair of doors or single door

No.	Body Size	Strike Size	Weight
901	$\frac{13}{16}$ " x 3 $\frac{1}{8}$ " x 1"	1 ea. $\frac{7}{8}$ " x 3 $\frac{1}{8}$ " 2 ea. $\frac{7}{8}$ " x 1 $\frac{1}{8}$ "	0.35 lbs.

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



No. 910

## Adjustable Ball Catch - Square Corners No. 910, 911

**Material:** Brass

**Finishes:** US26D

**Fastener:** 4 ea. #6 x 3/4" FH SMS

**Other:** No. 910: Narrow strike for mounting on door, catch in jamb  
No. 911: Wide strike for mounting on jamb, catch in door

**Features:** Dual adjustment for door clearance and holding strength

No.	Body Size	Strike Size	Weight
910	1" x 2 1/8"	1 1/16" x 2 1/8"	0.2 lbs.
911	1" x 2 1/8"	1 3/8" x 2 1/8"	0.2 lbs.



No. 911RC

## Adjustable Ball Catch - Round Corners No. 910RC, 911RC

**Material:** Brass

**Finishes:** US26D

**Fastener:** 4 ea. #6 x 3/4" FH SMS

**Other:** No. 910RC: Narrow strike for mounting on door, catch in jamb  
No. 911RC: Wide strike for mounting on jamb, catch in door

**Features:**

- 1/4" radius corners for easy mortise installation
- Dual adjustment for door clearance and holding strength


No.	Body Size	Strike Size	Weight
910RC	1" x 2 1/8"	1 1/16" x 2 1/8"	0.2 lbs.
911RC	1" x 2 1/8"	1 3/8" x 2 1/8"	0.2 lbs.



## Door Edge Filler Plate No. DF86

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** 2 ea. #12 - 24 x 1/2" FH MS  
**Other:** For gov. 86 mortise lock face


No.	Size	Weight	Pack Quantity
DF86	1 1/4" x 8" x 3/16"	11.9 lbs./25	25



## Frame Hinge Filler Plate No. DFF4

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** 2 ea. #12 - 24 x 1/2" FH MS  
**Other:** For 1 3/4" rabbet frames


No.	Size	Weight	Pack Quantity
DFF4	1 5/8" x 4 1/2"	6.8 lbs./25	25



## Frame Hinge Filler Plate No. DFF5

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** 2 ea. #12 - 24 x 1/2" FH MS  
**Other:** For 1 3/4" rabbet frames

No.	Size	Weight	Pack Quantity
DFF5	1 5/8" x 5"	7.9 lbs./25	25



## Beveled Door Hinge Filler Plate No. DHF4B

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** 2 ea. #12 - 24 x 1/2" FH MS  
**Other:** For handed doors (beveled)

No.	Size	Weight	Pack Quantity
DHF4B	1 1/2" x 4 1/2"	6.4 lbs./25	25

**ROCKWOOD**<sup>®</sup>

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



## Square Door Hinge Filler Plate No. DHF4S

- Material:** Steel
- Finishes:** Prime coat
- Fastener:** 2 ea. #12 - 24 x 1/2" FH MS
- Other:** For non-handed doors (square edge)


No.	Size	Weight	Pack Quantity
DHF4S	1 3/4" x 4 1/2"	7.7 lbs./25	25



## Beveled Door Hinge Filler Plate No. DHF5B

- Material:** Steel
- Finishes:** Prime coat
- Fastener:** 2 ea. #12 - 24 x 1/2" FH MS
- Other:** For handed doors (beveled)


No.	Size	Weight	Pack Quantity
DHF5B	1 1/2" x 5"	7.2 lbs./25	25



## Square Door Hinge Filler Plate No. DHF5S

- Material:** Steel
- Finishes:** Prime coat
- Fastener:** 2 ea. #12 - 24 x 1/2" FH MS
- Other:** For non-handed doors (square edge)


No.	Size	Weight	Pack Quantity
DHF5S	1 3/4" x 5"	8.5 lbs./25	25



## Flush Bolt Filler Plate No. FBF48

- Material:** Steel
- Finishes:** Prime coat
- Fastener:** 2 ea. #8 - 32 x 1/2" FH MS

No.	Size	Weight	Pack Quantity
FBF48	1" x 6 3/4"	6.4 lbs./25	25



## Flush Bolt Strike Filler Plate No. FBS48

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** 2 ea. #8 - 32 x 1/2" FH MS

No.	Size	Weight	Pack Quantity
FBS48	15/16" x 2 1/4"	1.3 lbs./25	25



## Door Face Filler Plate No. FC161

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** Sex bolt and sleeve  
**Other:** To cover up to 2 1/8" lock hole


No.	Size	Weight	Pack Quantity
FC161	2 5/8" dia.	4.0 lbs./25	25



## Door Face Filler Plate No. FD160

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** Sex bolt and sleeve  
**Other:** To cover up to 1 1/2" lock hole

No.	Size	Weight	Pack Quantity
FD160	1 3/4" dia.	2.0 lbs./25	25



## 4 1/2" Hinge Shim – .028" Thick No. HS42

**Material:** Steel  
**Finishes:** Galvanized coat

No.	Size	Weight	Pack Quantity
HS42	1 7/16" x 4 1/2"	2.2 lbs./50	50

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.




## 4 1/2" Hinge Shim – .065" Thick No. HS44

**Material:** Steel

**Finishes:** Galvanized coat

No.	Size	Weight	Pack Quantity
HS44	1 7/16" x 4 1/2"	4.4 lbs./50	50



## 5" Hinge Shim – .028" Thick No. HS52

**Material:** Steel

**Finishes:** Galvanized coat

No.	Size	Weight	Pack Quantity
HS52	1 7/16" x 5"	2.3 lbs./50	50



## 5" Hinge Shim – .065" Thick No. HS54

**Material:** Steel

**Finishes:** Galvanized coat

No.	Size	Weight	Pack Quantity
HS54	1 7/16" x 5"	4.5 lbs./50	50



## Latch Adapter Plate No. LA86

**Material:** Steel

**Finishes:** Prime coat

**Fastener:** 2 ea. #12 - 24 x 1/2" FH MS

**Other:** Change 86 cutout to 161 template


No.	Size	Weight	Pack Quantity
LA86	1 1/4" x 8"	7.5 lbs./25	25



## Door Edge Filler Plate No. LF161

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** 2 ea. #8 - 32 x 1/2" FH MS  
**Other:** For gov. 161 latch


No.	Size	Weight	Pack Quantity
LF161	1 1/8" x 2 1/4"	2.5 lbs./25	25



## Strike Filler Plate No. SF160

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** 2 ea. #8 - 32 x 1/2" FH MS  
**Other:** For gov. 160 latch


No.	Size	Weight	Pack Quantity
SF160	1 1/8" x 2 3/4"	2.1 lbs./25	25



## Strike Filler Plate No. SFASA

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** 2 ea. #12 - 24 x 1/2" FH MS  
**Other:** For ASA strike

No.	Size	Weight	Pack Quantity
SFASA	1 1/4" x 4 7/8"	4.9 lbs./25	25



## Strike Filler Plate No. SFB160

**Material:** Steel  
**Finishes:** Prime coat  
**Fastener:** 2 ea. #8 - 32 x 1/2" FH MS  
**Other:** For Schlage "B" lock and other dead lock strikes

No.	Size	Weight	Pack Quantity
SFB160	1 1/8" x 2 3/4"	1.9 lbs./25	25

**ROCKWOOD®**

**ASSA ABLOY**

Experience a safer  
and more open world

800 458 2424 | [www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
Check the web site for the up-to-date catalog

Copyright © 2012-2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited.



The ASSA ABLOY Group is the global leader in access solutions.  
Every day, we help billions of people experience a more open world.

ASSA ABLOY Opening Solutions leads the development within  
door openings and products for access solutions in homes, businesses  
and institutions. Our offering includes doors, frames, door and window  
hardware, mechanical and smart locks, access control and service.

**ROCKWOOD®**

**ASSA ABLOY**



Rockwood Manufacturing Company  
300 Main St.  
Rockwood, PA 15557  
[www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
[orders.rockwood@assaabloy.com](mailto:orders.rockwood@assaabloy.com)  
1 800 458 2424

ASSA ABLOY Opening Solutions  
Door Security Solutions Canada  
160 Four Valley Drive  
Vaughan, ON L4K 4T9  
[www.assaabloydss.ca](http://www.assaabloydss.ca)  
1 800 461 3007

Rockwood is a brand associated with ASSA ABLOY Accessories and Door Controls Group, Inc. Copyright © 2012-2026,  
ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the  
express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.

RM100 2555C 5133.D 3/26